

CIVIL AVIATION GUIDANCE MATERIAL – 6008(IV)

EXTENDED DIVERSION TIME OPERATIONS EDTO

CIVIL AVIATION AUTHORITY OF MALAYSIA

INTENTIONALLY LEFT BLANK



Introduction

This Civil Aviation Guidance Material 6008 Part IV (CAGM – 6008 (IV)) is issued by the Civil Aviation Authority of Malaysia (CAAM) to provide guidance for the application of extended diversion time operations (EDTO), pursuant to Civil Aviation Directives 6 Part 1 – Commercial Air Transport (CAD 6 Part 1 – CAT) and Civil Aviation Directives 6 Part 2 – General Aviation (CAD 6 Part 2 – GA (collectively referred to as "CAD").

Organisations may use these guidelines to ensure compliance with the respective provisions of the relevant CAD's issued. Notwithstanding the Regulation 204 and Regulation 205 of the Malaysian Civil Aviation Regulations 2016 (MCAR 2016), when the CAGMs issued by the CAAM are complied with, the related requirements of the CAD's may be deemed as being satisfied and further demonstration of compliance may not be required.

Note concerning the use of the terms "EDTO" vs "ETOPS"

ICAO decided, through Amendment 36 to Annex 6, Part I, to replace the previously used term ETOPS (extended range operations by twin-engine aeroplanes) with the new term EDTO (extended diversion time operations). The main reason for this change in the terminology was to better reflect the scope and applicability of these new Standards.

(Captain Chester Voo Chee Soon) Chief Executive Officer Civil Aviation Authority of Malaysia



Civil Aviation Guidance Material components and Editorial practices

This Civil Aviation Guidance Material is made up of the following components and are defined as follows:

Standards: Usually preceded by words such as *"shall"* or *"must"*, are any specification for physical characteristics, configuration, performance, personnel or procedure, where uniform application is necessary for the safety or regularity of air navigation and to which Operators must conform. In the event of impossibility of compliance, notification to the CAAM is compulsory.

Recommended Practices: Usually preceded by the words such as "*should*" or "*may*", are any specification for physical characteristics, configuration, performance, personnel or procedure, where the uniform application is desirable in the interest of safety, regularity or efficiency of air navigation, and to which Operators will endeavour to conform.

Appendices: Material grouped separately for convenience, but forms part of the Standards and Recommended Practices stipulated by the CAAM.

Definitions: Terms used in the Standards and Recommended Practices which are not selfexplanatory in that they do not have accepted dictionary meanings. A definition does not have an independent status but is an essential part of each Standard and Recommended Practice in which the term is used, since a change in the meaning of the term would affect the specification.

Tables and Figures: These add to or illustrate a Standard or Recommended Practice, and which are referred to therein, form part of the associated Standard or Recommended Practice and have the same status.

Notes: Included in the text, where appropriate, Notes give factual information or references bearing on the Standards or Recommended Practices in question but not constituting part of the Standards or Recommended Practices;

Attachments: Material supplementary to the Standards and Recommended Practices or included as a guide to their application.

The units of measurement used in this document are in accordance with the International System of Units (SI) as specified in CAD 5. Where CAD 5 permits the use of non-SI alternative units, these are shown in parentheses following the basic units. Where two sets of units are quoted it must not be assumed that the pairs of values are equal and interchangeable. It may, however, be inferred that an equivalent level of safety is achieved when set of units is used exclusively.

Any reference to a portion of this document, which is identified by a number and/or title, includes all subdivisions of that portion.

Throughout this Civil Aviation Guidance Material, the use of the male gender should be understood to include male and female persons



Record of Revisions

Revisions to this CAGM shall be made by authorised personnel only. After inserting the revision, enter the required data in the revision sheet below. The *'Initials'* has to be signed off by the personnel responsible for the change.

| Image: style im | Rev No. | Revision Date | Revision Details | Initials |
|--|---------|----------------------|------------------|----------|
| Image: symmetry interpretainImage: symmetry interpretainI | | | | |
| Interpretation <tr< td=""><td></td><td></td><td></td><td></td></tr<> | | | | |
| Interpretation <tr< td=""><td></td><td></td><td></td><td></td></tr<> | | | | |
| IndexInterfact of the second seco | | | | |
| InterpretationIn | | | | |
| Interpretation <tr< td=""><td></td><td></td><td></td><td></td></tr<> | | | | |
| AnnexAnnexAnnexIndex <td></td> <td></td> <td></td> <td></td> | | | | |
| Image: section of the section of th | | | | |
| Image: section of the section of th | | | | |
| Indext and the set of the se | | | | |
| Indext symbolIndext symbol <td></td> <td></td> <td></td> <td></td> | | | | |
| InterpretationIn | | | | |
| <table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container> | | | | |
| Indext symbolIndext symbol <td></td> <td></td> <td></td> <td></td> | | | | |
| Indext symbolIndext symbol <td></td> <td></td> <td></td> <td></td> | | | | |
| Indext symbolIndext symbol <td></td> <td></td> <td></td> <td></td> | | | | |
| IndexI | | | | |
| IndextIn | | | | |
| Image: section of the section of th | | | | |
| Image: series of the series | | | | |
| Image: series of the series | | | | |
| Image: series of the series | | | | |
| Image: section of the section of th | | | | |
| Image: series of the series | | | | |
| Image: series of the series | | | | |
| Image: second | | | | |
| Image: second | | | | |
| Image: Constraint of the second sec | | | | |
| Image: Constraint of the second sec | | | | |
| Image: Constraint of the second sec | | | | |
| Image: Constraint of the second sec | | | | |
| Image: Constraint of the second sec | | | | |
| | | | | |
| | | | | |
| | | | | |



INTENTIONALLY LEFT BLANK



Table of Contents

GENERAL INFORMATION, POLICY AND GUIDANCE FOR OPERATIONS BY TURBINE-ENGINED AEROPLANES BEYOND 60 MINUTES TO AN EN-ROUTE ALTERNATE AERODROME INCLUDING EDTO......1-1 1.1 1.2 **OPERATIONS BY AEROPLANES WITH TURBINE ENGINES BEYOND 60 MINUTES TO AN EN-ROUTE ALTERNATE** 13 1.4 CONTINUITY OF EDTO CERTIFICATION — AEROPLANES WITH TWO TURBINE ENGINES (NOT APPLICABLE TO 1.5 1.6 2 AIRCRAFT AIRWORTHINESS CONSIDERATIONS FOR EDTO2-1 2.1 2.2 2.3 3 31 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9 EDTO MAINTENANCE AND RELIABILITY REQUIREMENTS......4-1 4.1 GENERAL 4-1 4.2 4.3 Δ Δ 4.5 4.6 4.7 4.8 4.9 4.10 4.11 4.12 4.13 4.14 4.15 4.16 4.17 4.18 5 5.1 5.2



Table of Contents

| 6 | APPE | ENDICES | 6-1 |
|---------------|------|---------------------------------------|-----|
| | 6.1 | APPENDIX 1: ACCELERATED EDTO APPROVAL | 6-1 |
| | 6.2 | Appendix 2: EDTO training program | 6-7 |
| 7 ATTACHMENTS | | ACHMENTS | 7-1 |
| | 7.1 | ATTACHMENT A: EDTO APPLICATION FORM | 7-1 |

1 General Information, Policy and Guidance for Operations by Turbine-Engined Aeroplanes Beyond 60 Minutes to an En-Route Alternate Aerodrome including EDTO.

1.1 Introduction

- 1.1.1 The purpose of this Chapter is to provide guidance on the general provisions relating to operations by turbine- engined aeroplanes beyond 60 minutes' flying time to an en-route alternate aerodrome and extended diversion time operations contained in CAD 6 Part 1 Chapter 4, 4.7. The guidance will also assist operators in obtaining EDTO specific approval for two-engine transport category aeroplanes to operate over a specified route containing a point farther than applicable threshold time at the approved one-engine-inoperative (OEI) cruise speed (under standard conditions in still-air) from an adequate aerodrome. The threshold is a point on the route beyond which the provisions of this CAGM apply. Specific criteria are included for diversion times of 90, 120, and 180 minutes, and beyond 180 minutes. The provisions in CAD 6 Part 1 Chapter 4, 4.7, are divided into:
 - a) the basic provisions that apply to all aeroplanes operating beyond 60 minutes to an en-route alternate aerodrome; and
 - b) provisions to fly beyond a threshold time, and up to a maximum diversion time, approved by the CAAM, that may be different for each operator/aeroplane type combination.

This Chapter provides guidance on the means of achieving the required level of safety envisaged.

- 1.1.2 Similar to the threshold time, the maximum diversion time is the range (expressed in time) from a point on a route to an en-route alternate aerodrome up to which the CAAM grants an approval. The capable range of the aircraft, taking into consideration any limitation of the aeroplane's type certificate, and also the operator's previous experience on similar aircraft types and routes will be taken into consideration during the maximum diversion time approval process.
- 1.1.3 The material in this Chapter is organised to address guidance on operations beyond 60 minutes to an en-route alternate aerodrome for all aeroplanes with turbine engines (paragraph 1.2) and guidance for extended diversion time operations (paragraph 1.3). The EDTO paragraph is further divided into general provisions (paragraph 1.3.1), provisions that apply to aeroplanes with more than two engines (paragraph 1.3.2) and provisions that apply to aeroplanes with two engines (paragraph 1.3.3). The paragraphs on aeroplanes with two engines and more than two engines are organised in exactly the same way. It should be noted that these paragraphs may appear to be similar and thus repetitive; however, there are requirement differences based on the aeroplane type. The reader should see

paragraphs 1.2 and 1.3.1 and then either 1.3.2 for aeroplanes with more than two engines or 1.3.3 for aeroplanes with two engines.

1.2 Operations By Aeroplanes With Turbine Engines Beyond 60 Minutes To An En-Route Alternate Aerodrome

1.2.1 <u>General</u>

1.2.1.1 All provisions for operations by aeroplanes with turbine engines beyond 60 minutes to an en-route alternate aerodrome also apply to extended diversion time operations (EDTO). Figure 1 illustrates generically the integration of operations beyond 60 minutes to an en-route alternate aerodrome and EDTO.



Figure 1 – Generic EDTO graphical representation

- 1.2.1.2 In applying the requirements for aeroplanes with turbine engines in CAD 6 Part 1 Chapter 4, 4.7, it should be understood that:
 - a) operational control refers to the exercise, by the operator, of responsibility for the initiation, continuation, termination or diversion of a flight;
 - b) flight dispatch procedures refer to the method of control and supervision of flight operations. This does not imply a specific requirement for licensed flight dispatchers or a full flight following system;
 - c) operating procedures refer to the specification of organisation and methods established to exercise operational control and flight dispatch procedures

in the appropriate manual(s) and should cover at least a description of responsibilities concerning the initiation, continuation, termination or diversion of each flight as well as the method of control and supervision of flight operations; and

- d) training programme refers to the training for pilots and flight operations officers/flight dispatchers in operations covered by this and following paragraphs.
- 1.2.1.3 Aeroplanes with turbine engines operating beyond 60 minutes to an en-route alternate aerodrome are not required to have specific additional approval by the CAAM except if they engage in extended diversion time operations.
- 1.2.2 <u>Conditions to be used when converting diversion times to distances.</u>
- 1.2.2.1 For the purpose of this guidance, an approved one-engine-inoperative (OEI) speed or approved all-engines- operative (AEO) speed is any speed within the certified flight envelope of the aeroplane.
- 1.2.2.2 Determination of the 60-minute distance aeroplanes with two turbine engines:
- 1.2.2.2.1 For determining whether a point on the route is beyond 60 minutes to an enroute alternate, the operator should select an approved OEI speed. The distance is calculated from the point of the diversion followed by cruise for 60 minutes, in ISA and still-air conditions, as shown in Figure 2. For the purposes of computing distances, credit for driftdown may be taken.



Figure 2 – Sixty-minute distance – aeroplanes with two turbine engines

- 1.2.2.3 Determination of the 60-minute distance aeroplanes with more than two turbine engines
- 1.2.2.3.1 For determining whether a point on the route is beyond 60 minutes to an enroute alternate, the operator should select an approved AEO speed. The

distance is calculated from the point of the diversion followed by cruise for 60 minutes, in ISA and still-air conditions, as shown in Figure 3.

1.2.3 <u>Training</u>

1.2.3.1 Training programmes should ensure that the requirements of CAD 6 Part 1 Chapter 9, 9.4.3.2, are complied with such as, but not limited to, route qualification, flight preparation, concept of extended diversion time operations and criteria for diversions.



Figure 3 – Sixty-minute distance – aeroplanes with more than two turbine engines.

1.2.4 Flight dispatch and operational requirements

- 1.2.4.1 In applying the general flight dispatch requirements of CAD 6 Part 1 Chapter 4 particular attention should be paid to the conditions which might prevail any time that the operation is beyond 60 minutes to an en-route alternate aerodrome, e.g. systems degradation and reduced flight altitude. For compliance with the requirement of CAD 6 Part 1 Chapter 4, 4.7, at least the following aspects should be considered:
 - a) identify en-route alternate aerodromes;
 - ensure that, prior to departure, the flight crew is provided with the most upto-date information on the identified en- route alternate aerodromes, including operational status and meteorological conditions and, in flight, make available means for the flight crew to obtain the most up-to-date weather information;
 - c) methods to enable two-way communications between the aeroplane and the operator's operational control centre;
 - ensure that the operator has a means to monitor conditions along the planned route including the identified alternate aerodromes and ensure that procedures are in place so that the flight crew are advised of any situation that may affect the safety of flight;

- e) ensure that the intended route does not exceed the established aeroplane threshold time unless the operator is approved for EDTO operations;
- f) pre-flight system serviceability including the status of items in the minimum equipment list;
- g) communication and navigation facilities and capabilities;
- h) fuel requirements; and
- i) availability of relevant performance information for the identified en-route alternate aerodrome(s).
- 1.2.4.2 In addition, operations conducted by aeroplanes with two turbine engines require that, prior to departure and in flight, the meteorological conditions at identified en-route alternate aerodromes will be at or above the aerodrome operating minima required for the operation during the estimated time of use.
- 1.2.5 En-route alternate aerodromes
- 1.2.5.1 Aerodrome(s) to which an aircraft may proceed in the event that a diversion becomes necessary while en route, where the necessary services and facilities are available, where aircraft performance requirements can be met, and which are expected to be operational if required, need to be identified any time that the operation is beyond 60 minutes to an en-route alternate aerodrome.

Note.— En-route alternate aerodromes may also be the take-off and/or destination aerodromes.

1.3 Extended Diversion Time Operations (EDTO) Requirements

1.3.1 <u>Basic concept</u>

- 1.3.1.1 In addition to the provisions in paragraph 1.2, this paragraph addresses the provisions that apply to operations by aeroplanes with two or more turbine engines where the diversion time to an en-route alternate aerodrome is greater than the threshold time established by the CAAM (extended diversion time operations).
- 1.3.1.2 EDTO significant systems
- 1.3.1.2.1 EDTO significant systems may be the aeroplane propulsion system and any other aeroplane systems whose failure or malfunctioning could adversely affect safety particular to an EDTO flight, or whose functioning is specifically important to continued safe flight and landing during an aeroplane EDTO diversion.
- 1.3.1.2.2 Many of the aeroplane systems that are essential for non-extended diversion time operations may need to be reconsidered to ensure that the redundancy

level and/or reliability will be adequate to support the conduct of safe extended diversion time operations.

- 1.3.1.2.3 The maximum diversion time should not exceed the value of the EDTO significant system limitation(s), if any, for extended diversion time operations identified in the aeroplane flight manual, directly or by reference, reduced by an operational safety margin of 15 minutes.
- 1.3.1.2.4 The specific safety risk assessment to approve operations beyond the time limits of an EDTO significant time- limited system per the provisions in CAD 6 Part 1 Chapter 4, 4.7.2.5.1, should be based on the safety risk management guidance contained in the *Safety Management Manual (SMM)* (ICAO Doc 9859) and CAD 19. Hazards should be identified and safety risks assessed according to predicted probability and the severity of the consequences based on the worst foreseeable situation. When addressing the following components of the specific safety risk assessment it should be understood that:
 - a) capabilities of the operator refer to the operator's quantifiable in-service experience, compliance record, aeroplane capability and overall operational reliability that:
 - are sufficient to support operations beyond the time limits of an EDTO significant time-limited system;
 - 2) demonstrate the ability of the operator to monitor and respond to changes in a timely manner; and
 - there is an expectation that the operator's established processes, necessary for successful and reliable extended diversion time operations, can be successfully applied to such operations;
 - b) overall reliability of the aeroplane refers to:
 - quantifiable standards of reliability taking into account the number of engines, aircraft EDTO significant systems and any other factors that may affect operations beyond the time limits of a particular EDTO significant time-limited system; and
 - relevant data from the aeroplane manufacturer and data from the operator reliability programme used as a basis to determine overall reliability of the aeroplane and its EDTO significant systems;
 - c) reliability of each time-limited system refers to quantifiable standards of design, testing and monitoring that ensure the reliability of each particular EDTO significant time-limited system;
 - d) relevant information from the aeroplane manufacturer refers to technical data and characteristics of the aeroplane and worldwide fleet operational data provided by the manufacturer and used as a basis to

determine overall reliability of the aeroplane and its EDTO significant systems; and

- e) specific mitigation measures refer to the safety risk management mitigation strategies, which have manufacturer concurrence, that ensure an equivalent level of safety is maintained. These specific mitigations shall be based on:
 - technical expertise (e.g. data, evidence) proving the operator's eligibility for an approval of operations beyond the time limit of the relevant EDTO significant system; and
 - an assessment of relevant hazards, their probability and the severity of the consequences that may adversely impact the safety of the operation of an aeroplane operated beyond the limit of a particular EDTO significant time-limited system.

1.3.1.3 Threshold time

1.3.1.3.1 It should be understood that the threshold time established in accordance with CAD 6 Part 1 Chapter 4, 4.7, is not an operating limit. It is a flight time to an en-route alternate aerodrome, which is established by the CAAM as being the EDTO threshold beyond which particular consideration should be given to the aeroplane capability as well as the operator's relevant operational experience, before granting an EDTO approval.

1.3.1.4 *Maximum diversion time*

- 1.3.1.4.1 It should be understood that the maximum diversion time approved in accordance with CAD 6 Part 1 Chapter 4, 4.7, should take into consideration the most limiting EDTO significant system time limitation, if any, indicated in the aeroplane flight manual (directly or by reference) for a particular aeroplane type and the operator's operational and EDTO experience, if any, with the aeroplane type or, if relevant, with another aeroplane type or model.
- 1.3.2 EDTO for aeroplanes with more than two turbine engines
- 1.3.2.1 General
- 1.3.2.1.1 In addition to the provisions in paragraph 1.2 and 1.3.1 of this Chapter, this paragraph addresses the provisions that apply in particular to aeroplanes with more than two turbine engines (see Figure 4).

Note.— EDTO may be referred to as ETOPS in some documents.



Figure 4 – Generic EDTO graphical representation for aeroplanes with more than two turbine engines

- 1.3.2.2 Operational and diversion planning principles
- 1.3.2.2.1 When planning or conducting extended diversion time operations, the operator and pilot-in-command should ensure that:
 - a) the minimum equipment list, the communications and navigation facilities, fuel and oil supply, en-route alternate aerodromes and aeroplane performance are appropriately considered;
 - b) if no more than one engine is shut down, the pilot-in-command may elect to continue beyond the nearest en-route alternate aerodrome (in terms of time) if the pilot-in-command determines that it is safe to do so. In making this decision the pilot-in-command should consider all relevant factors; and
 - c) in the event of a single or multiple failure of an EDTO significant system or systems (excluding engine failure), the aircraft can proceed to and land at the nearest available en-route alternate aerodrome where a safe landing can be made unless it has been determined that no substantial degradation of safety will result from any decision made to continue the planned flight.

1.3.2.2.2 EDTO critical fuel

1.3.2.2.2.1 An aeroplane with more than two engines engaged in EDTO operations should carry enough fuel to fly to an en-route alternate aerodrome as described in 1.3.2.6. This EDTO critical fuel corresponds to the additional

fuel that may be required to comply with CAD 6 Part 1 Chapter 4, 4.3.6.3 f) 2).

- 1.3.2.2.2.2 The following should be considered, using the anticipated mass of the aeroplane, in determining the corresponding EDTO critical fuel:
 - a) fuel sufficient to fly to an en-route alternate aerodrome, considering at the most critical point of the route, simultaneous engine failure and depressurisation or depressurisation alone, whichever is more limiting;
 - the speed selected for the diversions (i.e. depressurisation, combined or not with an engine failure) may be different from the approved AEO speed used to determine the EDTO threshold and maximum diversion distance (see 1.3.2.8);
 - b) fuel to account for icing;
 - c) fuel to account for errors in wind forecasting;
 - d) fuel to account for holding an instrument approach and landing at the en-route alternate aerodrome;
 - e) fuel to account for deterioration in cruise fuel-burn performance; and
 - f) fuel to account for APU use (if required).

Note.— Guidance on EDTO critical fuel planning can be found in the Flight Planning and Fuel Management Manual (ICAO Doc 9976).

- 1.3.2.2.3 The following factors may be considered in determining if a landing at a given aerodrome is the more appropriate course of action:
 - a) aeroplane configuration, mass, systems status and fuel remaining;
 - d) wind and weather conditions en-route at the diversion altitude, minimum altitudes en-route and fuel consumption to the en-route alternate aerodrome;
 - e) runways available, runway surface condition and weather, wind and terrain in the proximity of the en-route alternate aerodrome;
 - f) instrument approaches and approach/runway lighting available and rescue and firefighting services (RFFS) at the en-route alternate aerodrome;
 - g) the pilot's familiarity with that aerodrome and information about that aerodrome provided to the pilot by the operator; and
 - h) facilities for passenger and crew disembarkation and accommodation.

1.3.2.3 Threshold time

1.3.2.3.1 The threshold time in CAD 6 Part 1 Chapter 4.7 has been established by the CAAM to maintain a required level of safety taking into consideration:

- a) the airworthiness certification of the aeroplane type does not restrict operations beyond the threshold time, taking into account the aeroplane system design and reliability aspects;
- b) specific flight dispatch requirements are met;
- c) necessary in-flight operational procedures are established; and
- d) the operator's previous experience on similar aircraft types and routes is satisfactory.
- 1.3.2.3.2 For determining whether a point on a route is beyond the EDTO threshold to an en-route alternate aerodrome, the operator should use the approved speed as described in 1.3.2.8.
- 1.3.2.4 *Maximum diversion time*
- 1.3.2.4.1 The CAAM takes into consideration the aeroplane's EDTO significant systems (e.g. limiting time limitation, if any, and relevant to that particular operation) for a particular aeroplane type and the operator's operational and EDTO experience with the aeroplane type or, if relevant, with another aeroplane type or model, when approving the maximum diversion time.
- 1.3.2.4.2 For determining the maximum diversion distance to an en-route alternate, the operator should use the approved speed as described in 1.3.2.8.
- 1.3.2.4.3 The operator's approved maximum diversion time should not exceed the most limiting EDTO significant system time limitation identified in the aeroplane flight manual, reduced by an operational safety margin of 15 minutes.
- 1.3.2.5 EDTO significant systems
- 1.3.2.5.1 In addition to the provisions in 1.3.1.1, this paragraph addresses particular provisions for aeroplanes with more than two turbine engines.
- 1.3.2.5.2 Consideration of time limitations
- 1.3.2.5.2.1 For all operations beyond the EDTO threshold, the operator should consider, at time of dispatch and as outlined below, the most limiting EDTO significant system time limitation, if any, indicated in the aeroplane flight manual (directly or by reference) and relevant to that particular operation.
- 1.3.2.5.2.2The operator should check that from any point on the route, the maximum
diversion time does not exceed the most limiting EDTO significant system
time limitation, reduced by an operational safety margin of 15 minutes.



Chapter 1 – General Information, Policy and Guidance for Operations by Turbine-Engined Aeroplanes Beyond 60 Minutes to an En-Route Alternate Aerodrome including EDTO

- 1.3.2.5.2.3 The maximum diversion time subject to cargo fire suppression time limitations are considered part of the most limiting EDTO significant time limitations in 1.3.3.5.2.2.
- 1.3.2.5.2.4 For that purpose, the operator should consider the approved speed as described in 1.3.2.8.2 or consider adjusting that speed with forecast wind and temperature conditions for operations with longer threshold times (e.g. beyond 180 minutes).
- 1.3.2.6 En-route alternate aerodromes
- 1.3.2.6.1 In addition to the en-route alternate aerodrome provisions described in 1.2.5 the following apply:
 - a) for route planning purposes, identified en-route alternate aerodromes, which could be used if necessary, need to be located at a distance within the maximum diversion time from the route; and
 - a) in extended diversion time operations, before an aeroplane crosses its threshold time during flight, there should always be an en-route alternate aerodrome within the approved maximum diversion time whose conditions will be at or above the operator's established aerodrome operating minima for the operation during the estimated time of use.
 - b) if any conditions, such as weather below landing minima, are identified that would preclude a safe approach and landing at that aerodrome during the estimated time of use, an alternative course of action should be determined such as selecting another en-route alternate aerodrome within the operator's approved maximum diversion time.

Note.— En route alternate aerodromes may also be the take-off and/or destination aerodromes.

- 1.3.2.7 Operational approval procedure
- 1.3.2.7.1 During the approval procedure, a maximum diversion time will be established and the following steps will be carried out by the CAAM in addition to the requirements set forth in this CAGM being met:
 - a) check that the operator's past experience and compliance record is satisfactory and the operator has established the processes necessary for successful and reliable extended diversion time operations and shown that such processes can be successfully applied throughout such operations;
 - b) check that the operator's procedures are acceptable based on certified aeroplane capability and adequate to address continued safe operation in the event of degraded aeroplane systems;

- c) check the operator's crew training programme and maintenance personnel training programme are adequate for the proposed operation;
- d) check the documentation accompanying the authorisation covers all relevant aspects; and
- e) determine that it has been shown (e.g. during the EDTO certification of the aeroplane) that the flight can continue to a safe landing under the anticipated degraded operating conditions which would arise from:
 - the most limiting EDTO significant system time limitation, if any, for extended diversion time operations identified in the aeroplane flight manual, directly or by reference; or
 - 2) any other condition which the CAAM considers to be equivalent in airworthiness and performance risk.
- f) issue a specific operational approval.
- 1.3.2.8 Conditions to be used when converting diversion times to distances for the determination of the geographical area beyond threshold and within maximum diversion distances
- 1.3.2.8.1For the purpose of this guidance, an approved AEO speed is any all-
engines-operative speed within the certified flight envelope of the aeroplane.

Note.— See 1.3.2.5.2.2 for operational considerations.

- 1.3.2.8.2 When applying for EDTO the operator should identify the AEO speed(s), considering ISA and still-air conditions, that will be used to calculate the threshold and maximum diversion distances. These distances require an approval from the CAAM. The speed that will be used to calculate the maximum diversion distance may be different from the speed used to determine the 60-minute and EDTO thresholds.
- 1.3.2.8.3 Determination of the EDTO threshold
- 1.3.2.8.3.1 For determining whether a point on the route is beyond the EDTO threshold to an en-route alternate, the operator should use the approved speed (see 1.3.2.8.1 and 1.3.2.8.2). The distance is calculated from the point of the diversion followed by cruise for the threshold time as determined in CAD 6 Part 1 Chapter 4.7.2 and shown in Figure 5.



Figure 5 – Threshold distance – aeroplanes with more than two turbine engines

- 1.3.2.8.4 Determination of the maximum diversion time distance
- 1.3.2.8.4.1 For determining the maximum diversion time distance to an en-route alternate, the operator should use the approved speed (see 1.3.2.8.1 and 1.3.2.8.2). The distance is calculated from the point of the diversion followed by cruise for the maximum diversion time as approved by the CAAM and shown in Figure 6.
- 1.3.2.9 Airworthiness certification requirements for extended diversion time operations beyond the threshold time
- 1.3.2.9.1 There are no additional EDTO airworthiness certification requirements for aeroplanes with more than two engines.
- 1.3.2.10 Maintaining operational approval
- 1.3.2.10.1 In order to maintain the required level of safety on routes where these aeroplanes are permitted to operate beyond the established threshold time, it is necessary that:
 - a) specific flight dispatch requirements are met;
 - b) the necessary in-flight operational procedures are established; and
 - c) specific operational approval is granted by the CAAM.



Figure 6 – Maximum diversion distance – aeroplanes with more than two turbine engines

- 1.3.2.11 *Airworthiness modifications and maintenance programme requirements*
- 1.3.2.11.1 There are no additional EDTO airworthiness or maintenance requirements for aeroplanes with more than two engines.
- 1.3.3 EDTO for aeroplanes with two turbine engines
- 1.3.3.1 General
- 1.3.3.1.1 In addition to the provisions in paragraph 1.2 and 1.3.1, this paragraph addresses the provisions that apply in particular to aeroplanes with two turbine engines (see Figure 7).
- 1.3.3.1.2 EDTO provisions for aeroplanes with two turbine engines do not differ from the previous provisions for extended range operations by aeroplanes with two turbine engines (ETOPS). Therefore, EDTO may be referred to as ETOPS in some documents.
- 1.3.3.2 Operational and diversion planning principles
- 1.3.3.2.1 When planning or conducting extended diversion time operations, the operator and pilot-in-command should normally ensure that:
 - a) the minimum equipment list, the communications and navigation facilities, fuel and oil supply, en-route alternate aerodromes or aeroplane performance are appropriately considered;
 - b) in the event of an aeroplane engine shutdown, the aircraft can proceed to and land at the nearest (in terms of the least flying time) en-route alternate aerodrome where a safe landing can be made; and
 - c) in the event of a single or multiple failure of an EDTO significant system or systems (excluding engine failure), the aircraft can proceed to and

land at the nearest available en-route alternate aerodrome where a safe landing can be made unless it has been determined that no substantial degradation of safety will result from any decision made to continue the planned flight.



Figure 7 – Generic EDTO graphical representation for aeroplanes with two turbine engines

- 1.3.3.2.2 EDTO critical fuel
- 1.3.3.2.2.1An aeroplane with two engines engaged in EDTO operations should carry
enough fuel to fly to an en-route alternate aerodrome as described in
1.3.3.6. This EDTO critical fuel corresponds to the additional fuel that may
be required to comply with CAD 6 Part 1 Chapter 4, 4.3.6.3 f) 2).
- 1.3.3.2.2.2 The following should be considered, using the anticipated mass of the aeroplane, in determining the corresponding EDTO critical fuel:
 - a) fuel sufficient to fly to an en-route alternate aerodrome, considering at the most critical point of the route, failure of one engine or simultaneous engine failure and depressurisation or depressurisation alone, whichever is more limiting;
 - the speed selected for the all-engines-operative diversion (i.e. depressurisation alone) may be different from the approved OEI speed used to determine the EDTO threshold and maximum diversion distance (see 1.3.3.8);

- the speed selected for the OEI diversions (i.e. engine failure alone and combined engine failure and depressurisation) should be the approved OEI speed used to determine the EDTO threshold and maximum diversion distance (see 1.3.3.8);
- b) fuel to account for icing;
- c) fuel to account for errors in wind forecasting;
- d) fuel to account for holding an instrument approach and landing at the en-route alternate aerodrome;
- e) fuel to account for deterioration in cruise fuel-burn performance; and
- f) fuel to account for APU use (if required).

Note.— Guidance on EDTO critical fuel planning can be found in the Flight Planning and Fuel Management Manual(ICAO Doc 9976).

- 1.3.3.2.3 The following factors may be considered in determining if a landing at a given aerodrome is the more appropriate course of action:
 - a) aeroplane configuration, mass, systems status and fuel remaining;
 - b) wind and weather conditions en route at the diversion altitude, minimum altitudes en route and fuel consumption to the en-route alternate aerodrome;
 - c) runways available, runway surface condition and weather, wind and terrain in the proximity of the en-route alternate aerodrome;
 - d) instrument approaches and approach/runway lighting available and rescue and firefighting services (RFFS) at the en-route alternate aerodrome;
 - e) the pilot's familiarity with that aerodrome and information about that aerodrome provided to the pilot by the operator; and`
 - f) facilities for passenger and crew disembarkation and accommodation.

1.3.3.3 Threshold time

- 1.3.3.3.1The threshold time in CAD 6 Part 1 Chapter 4.7 has been established by the
CAAM to maintain a required level of safety taking into consideration:
 - a) the airworthiness certification of the aeroplane type specifically permits operations beyond the threshold time, taking into account the aeroplane system design and reliability aspects;
 - b) the reliability of the propulsion system is such that the risk of double engine failure from independent causes is extremely remote;
 - c) any necessary special maintenance requirements are fulfilled;

- d) specific flight dispatch requirements are met;
- e) necessary in-flight operational procedures are established; and
- f) the operator's previous experience on similar aircraft types and routes is satisfactory.
- 1.3.3.3.2 For determining whether a point on a route is beyond the EDTO threshold to an en-route alternate aerodrome, the operator should use the approved speed as described in 1.3.3.8.
- 1.3.3.4 *Maximum diversion time*
- 1.3.3.4.1 The CAAM takes into consideration the EDTO certified capability of the aeroplane, the aeroplane's EDTO significant systems (e.g. limiting time limitation, if any, and relevant to that particular operation) for a particular aeroplane type and the operator's operational and EDTO experience with the aeroplane type or, if relevant, with another aeroplane type or model, when approving the maximum diversion time.
- 1.3.3.4.2 For determining the maximum diversion distance to an en-route alternate, the operator should use the approved speed as described in 1.3.3.8.
- 1.3.3.4.3 The operator's approved maximum diversion time should not exceed the EDTO certified capability of the aeroplane or the most limiting EDTO significant system time limitation identified in the aeroplane flight manual, reduced by an operational safety margin of 15 minutes.
- 1.3.3.5 EDTO significant systems
- 1.3.3.5.1 In addition to the provisions in 1.3.1.1, this paragraph addresses particular provisions for aeroplanes with two turbine engines.
- 1.3.3.5.1.1 The reliability of the propulsion system for the aeroplane/engine combination being certified is such that the risk of double engine failure from independent causes is assessed as provided for in the *Airworthiness Manual* (ICAO Doc 9760) and found acceptable to support the diversion time being approved.

Note.— EDTO may be referred to as ETOPS in some documents.

- 1.3.3.5.2 Consideration of time limitations
- 1.3.3.5.2.1 For all operations beyond the EDTO threshold, the operator should consider, at time of dispatch and as outlined below, the EDTO certified capability of the aeroplane and the most limiting EDTO significant system time limitation, if any, indicated in the aeroplane flight manual (directly or by reference) and relevant to that particular operation.

Chapter 1 – General Information, Policy and Guidance for Operations by Turbine-Engined Aeroplanes Beyond 60 Minutes to an En-Route Alternate Aerodrome including EDTO

- 1.3.3.5.2.2 The operator should check that from any point on the route, the maximum diversion time at the approved speed as described in 1.3.3.8.2 does not exceed the most limiting EDTO significant system time limitation, other than the cargo fire suppression system, reduced by an operational safety margin of 15 minutes.
- 1.3.3.5.2.3 The operator should check that from any point on the route, the maximum diversion time at all-engines operating cruise speed, considering ISA and still-air conditions, does not exceed the cargo fire suppression system time limitation, reduced by an operational safety margin of 15 minutes.
- 1.3.3.5.2.4 The operator should consider the approved speed as described in 1.3.3.5.2.2 and 1.3.3.5.2.3 or consider adjusting that speed with forecast wind and temperature conditions for operations with longer threshold times (e.g. beyond 180 minutes).
- 1.3.3.6 *En-route alternate aerodromes*
- 1.3.3.6.1 In addition to the en-route alternate aerodrome provisions described in 1.2.5, the following apply:
 - a) for route planning purposes, identified en-route alternate aerodromes, which could be used if necessary, need to be located at a distance within the maximum diversion time from the route; and
 - b) in extended diversion time operations, before an aeroplane crosses its threshold time during flight, there should always be an en-route alternate aerodrome within the approved maximum diversion time whose conditions will be at or above the operator's established aerodrome operating minima for the operation during the estimated time of use.
 - c) If any conditions, such as weather below landing minima, are identified that would preclude a safe approach and landing at that aerodrome during the estimated time of use, an alternative course of action should be determined such as selecting another en-route alternate aerodrome within the operator's approved maximum diversion time.
- 1.3.3.6.2 During flight preparation and throughout the flight the most up-to-date information on the identified en-route alternate aerodromes, including operational status and meteorological conditions, should be provided to the flight crew.

Note.— En route alternate aerodromes may also be the take-off and/or destination aerodromes.

1.3.3.7 *Operational approval procedure*

- 1.3.3.7.1 During the approval procedure, a maximum diversion time will be established and the following steps will be carried out by the CAAM in addition to the requirements set forth in this CAGM being met:
 - a) check the operator's past experience and compliance record is satisfactory and the operator has established the processes necessary for successful and reliable extended diversion time operations and shown that such processes can be successfully applied throughout such operations;
 - b) check the operator's procedures are acceptable based on certified aeroplane capability and adequate to address continued safe operation in the event of degraded aeroplane systems;
 - c) check that the operator's crew training programme is adequate for the proposed operation;
 - d) check that the documentation accompanying the authorisation covers all relevant aspects; and
 - e) determine that it has been shown (e.g. during the EDTO certification of the aeroplane) that the flight can continue to a safe landing under the anticipated degraded operating conditions which would arise from:
 - the most limiting EDTO significant system time limitation, if any, for extended diversion time operations identified in the aeroplane flight manual, directly or by reference; or
 - 2) total loss of engine-generated electric power; or
 - 3) total loss of thrust from one engine; or
 - 4) any other condition which is considered by the CAAM to be equivalent in airworthiness and performance risk.
 - f) Issue a specific operational approval.
- 1.3.3.8 Conditions to be used when converting diversion times to distances for the determination of the geographical area beyond threshold and within maximum diversion distances
- 1.3.3.8.1 For the purpose of this guidance, an approved OEI speed is any one-engineinoperative speed within the certified flight envelope of the aeroplane.

Note.— See 1.3.3.5.2.2 for operational considerations.

1.3.3.8.2 When applying for EDTO the operator should identify, the OEI speed(s), considering ISA and still-air conditions, that will be used to calculate the threshold and maximum diversion distances. These distances require the approval from the CAAM. The identified speed that will be used to calculate the maximum diversion distance should be the same one used to determine

fuel reserves for OEI diversions. This speed may be different from the speed used to determine the 60-minute and EDTO thresholds.

- 1.3.3.8.3 Determination of the EDTO threshold
- 1.3.3.8.3.1 For determining whether a point on the route is beyond the EDTO threshold to an en-route alternate, the operator should use the approved speed (see 1.3.3.8.1 and 1.3.3.8.2). The distance is calculated from the point of the diversion followed by cruise for the threshold time as determined in CAD 6 Part 1 Chapter 4.7.2 and shown in Figure 8. For the purposes of computing distances, credit for driftdown may be taken.



Figure 8 – Threshold distance – aeroplanes with two turbine engines

- 1.3.3.8.4 Determination of the maximum diversion time distance
- 1.3.3.8.4.1 For determining the maximum diversion time distance to an en-route alternate, the operator should use the approved speed (see 1.3.3.8.1 and 1.3.3.8.2). The distance is calculated from the point of the diversion followed by cruise for the maximum diversion time and shown in Figure 9. For the purposes of computing distances, credit for driftdown may be taken.



Figure 9 – Maximum diversion distance — aeroplanes with two turbine engines

- 1.3.3.9 Airworthiness certification requirements for extended diversion time operations beyond the threshold time
- 1.3.3.9.1 During the airworthiness certification procedure for an aeroplane type intended for extended diversion time operations, special attention should be paid to ensure that the required level of safety will be maintained under conditions which may be encountered during such operations, e.g. flight for extended periods following failure of an engine and/or the aeroplane's EDTO significant systems. Information or procedures specifically related to extended diversion time operations should be incorporated into the aeroplane flight manual, the maintenance manual, the EDTO configuration, maintenance and procedure (CMP) document or other appropriate document.
- 1.3.3.9.2 Aeroplane manufacturers should supply data specifying the aeroplane's EDTO significant systems and, where appropriate, any time-limiting factors associated with those systems.

Note 1.— Criteria on aeroplane system performance and reliability for extended diversion time operations are contained in the Airworthiness Manual (ICAO Doc 9760).

Note 2.— EDTO may be referred to as ETOPS in some documents.

1.3.3.10 Maintaining operational approval

1.3.3.10.1 In order to maintain the required level of safety on routes where these aeroplanes are permitted to operate beyond the established threshold time, it is necessary that:

- a) the airworthiness certification of the aeroplane type specifically permits operations beyond the threshold time, taking into account the aeroplane's system design and reliability aspects;
- b) the reliability of the propulsion system is such that the risk of double engine failure from independent causes is extremely remote, assessed as provided for in the *Airworthiness Manual* (ICAO Doc 9760) and found acceptable to support the diversion time being approved;
- c) any special maintenance requirements are fulfilled;
- d) specific flight dispatch requirements are met;
- e) the necessary in-flight operational procedures are established; and
- f) specific operational approval is granted by the CAAM.

Note 1.— The airworthiness considerations applicable to extended diversion time operations are provided in the Airworthiness Manual (ICAO Doc 9760), Part IV, Chapter 5.

Note 2.— EDTO may be referred to as ETOPS in some documents.

- 1.3.3.11 *Airworthiness modifications and maintenance programme requirements*
- 1.3.3.11.1 Each operator's maintenance programme should ensure that:
 - a) the titles and numbers of all airworthiness modifications, additions and changes which were made to qualify aeroplane systems for extended diversion time operations are provided to the CAAM;
 - b) any changes to maintenance and training procedures, practices or limitations established in the qualification for extended diversion time operations are submitted to the CAAM before such changes are adopted;
 - c) a reliability monitoring and reporting programme is developed and implemented prior to approval and continued after approval;
 - d) prompt implementation of required modifications and inspections which could affect propulsion system reliability is undertaken;
 - e) procedures are established which prevent an aeroplane from being dispatched for an extended diversion time operation after engine shutdown or EDTO significant system failure on a previous flight until the cause of such failure has been positively identified and the necessary corrective action has been completed. Confirmation that such corrective action has been effective may, in some cases, require

the successful completion of a subsequent flight prior to dispatch on an extended diversion time operation;

- f) a procedure is established to ensure that the airborne equipment will continue to be maintained at the level of performance and reliability required for extended diversion time operations; and
- g) a procedure is established to minimise scheduled or unscheduled maintenance during the same maintenance visit on more than one parallel or similar EDTO significant system. Minimisation can be accomplished by staggering maintenance tasks, performing and/or supervising maintenance by a different technician, or verifying maintenance correction actions prior to the aeroplane entering an EDTO threshold.

1.4 Approval Procedures

1.4.1 Application for EDTO approval

- 1.4.1.1 Requests for approval of EDTO operations with aeroplanes having two or more engines should be submitted by the candidate EDTO operator with the necessary elements to the CAAM. These elements are those necessary for the CAAM to determine the applicable approval process (i.e. "in- service" or "accelerated" EDTO authorisation – refer to paragraph 1.4.2) and launch the assessment of the operator's readiness for EDTO.
- 1.4.1.2 These necessary elements are typically:
 - a) the targeted date of start of EDTO;
 - b) the contemplated maximum diversion time;
 - c) the concerned aeroplane model(s) and fleet(s) (MSNs); and
 - d) the intended EDTO route(s) or operational area(s).
- 1.4.1.3 Other elements may be provided if deemed relevant by the candidate EDTO operator to support its application.
- 1.4.1.4 EDTO approvals are specific approvals typically granted individually by aeroplane/engine combination (AEC) and area of operation for multiple geographic regions.
- 1.4.1.5 The request for approval of EDTO operations should be submitted as an advance notice in accordance with the five-phase process (see 5.1), so that the CAAM can plan and launch the necessary oversight actions.
- 1.4.1.6 The required duration of this advance notice prior to the proposed start of EDTO operations are:

- a) up to 60 working days for in-service EDTO approval; and
- b) up to 180 working days for accelerated EDTO approval.
- 1.4.2 <u>EDTO specific approval requirements aeroplanes with two turbine engines</u>
- 1.4.2.1 For operations with transport category aeroplanes with two turbine engines, the EDTO specific approval requires:
 - a) validation or acceptance by the CAAM of the EDTO certification (also called EDTO type design and reliability approval) of the aeroplane granted by the State of Design of the aircraft manufacturer. The aeroplane type design should meet the requirements for EDTO design features and criteria specified in the regulations;
 - b) conformity of the "candidate" aircraft (MSN), including auxiliary power unit (APU) and engines, to the applicable EDTO configuration requirements listed in the EDTO configuration, maintenance and procedures (CMP) document;
 - c) a system to maintain and dispatch an EDTO aeroplane in accordance with an approved maintenance, reliability and training programme that includes EDTO requirements specified in Chapter 4;
 - d) demonstration that the maintenance checks, servicing and programmes called for in Chapter 4 are properly conducted;
 - e) demonstration that the operational limitations, flight preparation and inflight procedures called for in Chapter 3 are properly conducted; and
 - authorisation of the operator based on its application package: routes, desired diversion time, fleet, area of operations, planned date for the start of EDTO flights, experience records, manuals, training, etc.
- 1.4.2.2 The AEC and the general scope of the operation will be reviewed by the flight operations inspector (FOI) and the airworthiness inspector (AWI) to determine if there are any factors that could affect the safe conduct of operations before an operations specification is issued
- 1.4.2.3 In summary, an operator that wants to operate EDTO flights with transport category aeroplanes with two turbine engines has to demonstrate that the aircraft is configured for EDTO and that the organisation, means and processes comply with applicable EDTO regulation and, for transport category aeroplanes with two turbine engines only, with the EDTO CMP requirements.
- 1.4.2.4 The complexity of this demonstration is basically linked to:
 - a) the operator's experience with EDTO, long-range operations, the area of operation, the aircraft type, the engines, etc.;
 - b) the contemplated degree of direct in-service experience reduction; and

- c) the type of intended EDTO operations (area of operations, frequency of EDTO flights, diversion time requested).
- 1.4.2.5 There are two types of EDTO authorisation, either an "in-service" EDTO authorisation or an "accelerated" EDTO authorisation. The specific approval method for these authorisations are described hereafter, and related compliance demonstrations are detailed in this CAGM.
- 1.4.2.6 The specificity of an "accelerated" EDTO authorisation is that the operator has to build a programme of process validation to address the lack of direct experience (with EDTO and/or with the candidate aircraft).
- 1.4.2.7 This process validation may involve transfer of experience and use of proven processes, simulated EDTO flights, assistance from an operator with EDTO experience and assistance from the manufacturer. The main objective of this programme is the transfer of EDTO experience into the candidate operator's organisation and operations. The required amount of process validation is directly linked to the operator's background and EDTO objectives.

Note. – Experience means any experience gained by flight crews, continuing airworthiness personnel and flight dispatch personnel, while working with other EDTO approved operators, particularly when such experience is with the same airframe or airframe/engine combination.

- 1.4.2.8 *"In-service" EDTO specific approval for operations with transport category aeroplanes with two turbine engines*
- 1.4.2.8.1 An "in-service" EDTO authorisation by specific approval is either:
 - a) a. 90-minute
 - When the operator has accumulated more than one year of direct in-service experience with the aeroplane/engine combination without EDTO. In this case, the operator may apply for a diversion time 90-minute maximum.
 - b) b. 120-minute
 - When the operator has accumulated more than one year of direct in-service experience with the aeroplane/engine combination in 90 minutes. In this case, the operator may apply for a diversion time 120-minute maximum.
 - c) c. Up to 180-minute
 - 1) When the operator has accumulated more than one year of EDTO experience at up to 120- minute maximum diversion time with the aeroplane/engine combination. In that case, the operator may apply for a diversion time 180-minutes maximum

- d) d. 180-minute and more
 - Approval for EDTO operations beyond 180-minute diversion time requires prior authorisation for 180-minute EDTO operations. Authorisation for EDTO operations beyond 240-minute diversion time requires a minimum of two years of experience with 180minute or higher EDTO operations.
- 1.4.2.8.2 The required amount of prior in-service experience listed above may be reduced (or increased) at the discretion of the CAAM based on compensating factor.

Note.— Authorisation for EDTO operations beyond 180-minute diversion time requires prior authorisation for 180-minute EDTO operations. Authorisation for EDTO operations beyond 240-minute diversion time requires a minimum of two years of experience with 180-minute or higher EDTO operations.

- 1.4.2.9 "Accelerated" EDTO specific approval for operations with transport category aeroplanes with two turbine engines
- 1.4.2.9.1 An "accelerated" EDTO authorisation by specific approval is either:
 - a) when the operator plans to start EDTO with less than one year of direct in-service experience with the aircraft; or
 - b) when the operator has accumulated direct in-service experience with the aircraft, but plans to conduct EDTO beyond existing EDTO approval given as in para 1.4.2.8.1 with less than one year of existing EDTO approval .
- 1.4.2.9.2 The operator may apply for any diversion time up to 120 minutes and may start EDTO at entry into service.

Note1.— Authorisation for EDTO operations beyond 180-minute diversion time requires prior experience with 180-minute EDTO operations.

Note. 2 —The details requirements for accelerated EDTO approval may refers to Appendix 1.

- 1.4.3 <u>EDTO authorisation requirements aeroplanes with more than two turbine engines</u>
- 1.4.3.1 For operations with transport category aeroplanes with more than two turbine engines, the EDTO authorisation by specific approval should require:
 - a review of the time capabilities of the relevant EDTO time-limited systems (TLSs). This review should be performed, although the EDTO certification is not required for an aeroplane with more than two engines, in order to

adequately consider the relevant time capabilities during EDTO operations. On most aeroplanes with more than two engines, the only relevant TLS is the cargo fire protection system; and

- authorisation of the operator based on its application package: routes, desired diversion time, fleet, area of operations, planned date for the start of EDTO flights, experience records, manuals, training, etc.
- 1.4.3.2 The AEC and the general scope of the operation will be reviewed by the FOI and the AWI to determine if there are any factors that could affect the safe conduct of operations before an operations specification is issued.
- 1.4.3.3 In summary, an operator that wants to operate EDTO flights with transport category aeroplane with more than two turbine engines has to demonstrate that its organisation, means and processes comply with applicable EDTO regulation and, for transport category aeroplanes with two turbine engines only, with the EDTOCMP requirements.
- 1.4.3.4 The complexity of this demonstration is linked to:
 - a) the operator's experience with EDTO, long-range operations, the area of operation, the aircraft type, the engines, etc.;
 - b) the contemplated degree of direct in-service experience reduction; and
 - c) the type of contemplated EDTO operations (area of operations, frequency of EDTO flights, diversion time requested).
- 1.4.3.5 There are no specific categories for EDTO approval for operations with transport category aeroplanes with more than two turbine engines, i.e. there are neither specific diversion time categories nor specific methods of authorisation.
- 1.4.4 Granting of EDTO authorisation
- 1.4.4.1 The following criteria should be met prior to conducting EDTO operations:
 - a) satisfy the authorisation considerations (operational criteria to be met for the granting of the authorisation) specified in Chapter 3 and chapter 4 of this CAGM;
 - b) demonstrate that EDTO flight release practices, policies and procedures are established; and
 - c) conduct operational validation flight(s). Such validation flight(s) should be performed on proposed route(s) that the operator intends to operate, as detailed in its EDTO specific approval authorisation request. The intent of the validation flight is to ensure that the required EDTO flight operations and maintenance (as applicable) processes and procedures are capable of supporting those operations.

Note.— Depending on the scope of EDTO authorisation (operator experience with the area of operations and aircraft model, contemplated diversion time, etc.) the validation flight in the aeroplane may be replaced by a flight on an approved simulator.

1.4.4.2 When the foregoing has been reviewed and found acceptable, a recommendation from the FOI and the AWI will be forwarded to the responsible director for authorisation by specific approval, and the applicant will be issued an operations specification to conduct EDTO operations within specified limitations.

1.5 Continuity Of EDTO Certification — Aeroplanes With Two Turbine Engines (Not Applicable To Aeroplanes With More Than Two Engines)

- 1.5.1 The EDTO certification is not granted permanently. It is dependent on a continued surveillance by the State of Design of the in-service reliability of the worldwide fleet of the concerned aircraft model/type.
- 1.5.2 The certified EDTO capability of the aircraft may therefore be reduced, suspended or even revoked if no solution exists to a major problem. This revisited EDTO capability should be reflected as applicable in relevant aircraft documentation.
- 1.5.3 Existing ETOPS certifications granted prior to the implementation of the new EDTO Standards remain valid and do not require recertification for EDTO. Refer to Paragraph 2.2 for further information and guidelines on EDTO certification of aeroplanes with two turbine engines.

1.6 Continuity Of EDTO Authorisation

- 1.6.1 The EDTO authorisation is not granted permanently. It is dependent on a continued surveillance by the CAAM of the operator's in-service reliability (concerning the EDTO fleet of aircraft).
- 1.6.1.1 The approval for conducting EDTO applies to an individual operator and to a specific airframe-engine combination of that operator's fleet. The approval, in general, is not transferable with the aircraft, and EDTO with a transferred aircraft should be the subject of an approval by the CAAM.
- 1.6.1.2 Where an aircraft is transferred from an authorised EDTO operator to an operator with limited EDTO experience and vice versa, the following factors should be considered:
 - a) the degree to which the original operator remains responsible for the EDTO elements of the operation in respect of the aircraft being transferred;
 - b) the operator experience with the specific airframe-engine combinations;
 - c) the experience level of the acquiring operator flight crew members and maintenance personnel; and
- d) the procedures used to ensure that only an EDTO-certified aircraft will be dispatched on an EDTO segment.
- 1.6.1.3 Arrangements and procedures regarding the approval of EDTO with a transferred aircraft Is usually acceptable to the CAAM. The experience of the State of Registry's operator being used to approve the new operator EDTO should be clearly identified in the transfer arrangements
- 1.6.2 The operator's procedures and training for EDTO are required to be maintained once an EDTO specific approval is issued.
- 1.6.3 Subject to 1.6.4, where an air operator ceases actual EDTO operations for a period exceeding a time determined by the CAAM to be unacceptable, an application for reinstatement may be required to be submitted in accordance with Paragraph 1.4.
- 1.6.4 Where an air operator ceases actual EDTO operation for a period exceeding the time stated in 1.6.3 but maintains simulated EDTO processes, procedures and training as prescribed in this CAGM, EDTO specific approval may be maintained until actual EDTO operation is resumed.
- 1.6.4.1 However, when actual EDTO operation resumes following a period of EDTO inactivity that exceeds the time defined in 1.6.3, recurrent training should be completed by each flight crew member before conducting EDTO operations as per the requirements stipulated by the CAAM, and EDTO recurrent training should be completed by each flight dispatcher involved in EDTO operations and relevant maintenance and engineering staff as per those requirements.
- 1.6.5 Existing ETOPS authorisations granted prior to the implementation of the new EDTO Standards remain valid and do not require to be reauthorised for EDTO.
- 1.6.6 For minor revisions to EDTO/ETOPS authorisations, the authorisation exercise should be focused on the requested changes to the programme. The intent is not to re-evaluate the entire approved programme unless warranted by reliability or operational concerns.

INTENTIONALLY LEFT BLANK

2 Aircraft Airworthiness Considerations for EDTO

2.1 Background

- 2.1.1 In the context of this manual, the term "aircraft airworthiness considerations for EDTO" refers to the assessment for EDTO of the type design, reliability and maintenance programme of the concerned aircraft model (i.e. a given AEC) for EDTO. The aim of this assessment is to ensure that:
 - a) the design features are suitable for the intended EDTO operations. Equipment required for EDTO should be properly identified;
 - b) the reliability of relevant aircraft systems is suitable for the intended EDTO operations. Modifications to systems that may be necessary to achieve the desired level of reliability should be properly identified; and
 - c) the aircraft maintenance and reliability programmes can contribute to maintaining the desired level of reliability of relevant aircraft systems for EDTO. Special maintenance programme requirements for EDTO should be properly identified.
- 2.1.2 When ETOPS was initially introduced in 1985, the intent was to ensure that the level of safety of operations on extended diversion time routes (i.e. routes beyond 60 minutes from an alternate aerodrome) with twin-engine aeroplanes was consistent with the level of safety achieved with aeroplanes with more than two engines operated on the same routes. This was achieved through the implementation of the initial ETOPS requirements, which addressed both the authorisation of the operator and the certification of the aeroplane.
- 2.1.3 EDTO is an evolution of ETOPS based on industry best practices and lessons learned during the first 25 years of ETOPS operations.
- 2.1.4 The airworthiness considerations for aeroplanes with two turbine engines, which include the identification of the time limitation of relevant TLSs, are therefore an evolution of the ETOPS criteria introduced in 1985, and are further detailed in Paragraph 2.2.
- 2.1.5 The airworthiness considerations for aeroplanes with more than two turbine engines were discussed during the development of the EDTO criteria. In this context, a review was performed of the reliability of operations on extended diversion time routes with aeroplanes with more than two engines, and it was concluded that both the basic type certification standards and maintenance programme provided the required level of safety for EDTO and remained suitable for EDTO operations.
- 2.1.5.1 There are no additional maintenance requirements or any additional certification requirements for aeroplanes with more than two engines. This

means that for EDTO with Tris/Quads, there is no need for a review; both remain acceptable for EDTO operations.

2.1.5.2 Nevertheless, It has been concluded that a review of the limitation of relevant TLSs, if any, was necessary for aeroplanes with more than two engines engaged in EDTO. This specific airworthiness consideration for aeroplanes with more than two turbine engines is further detailed in Paragraph 2.3.

2.2 Airworthiness considerations for aeroplanes with two turbine engines

- 2.2.1 General
- 2.2.1.1 The EDTO certification of the aircraft is granted by the State of Design of the aircraft manufacturer. This EDTO certification may also be called EDTO type design and reliability approval of the aircraft.
- 2.2.1.2 The EDTO certification of the aircraft is a prerequisite to the start of EDTO operations (see Chapter 3). This EDTO certification requires validation or acceptance by the CAAM before the intended start of EDTO (see 1.4.2).
- 2.2.1.3 The EDTO certification is always granted to a given AEC. It is not granted indefinitely and is subject to continued surveillance by the State of Design of the in-service reliability of the worldwide fleet of the concerned aeroplane/engine combination (see 1.5).

Note 1.— ETOPS certifications granted before issuance or implementation of the new EDTO criteria remain valid (see 1.5.3).

Note 2.— EDTO certification may be called ETOPS certification in some documents as the term "ETOPS" may still be used instead of "EDTO" (see Foreword, Note concerning the use of the terms EDTO vs ETOPS).

- 2.2.1.4 CAD 6 Part 1, Paragraph 4.7, provides the basic requirements for the authorisation of EDTO operations and the requirement for a specific approval. Paragraph1.1 to 1.3 contains guidance on the setting of a threshold time, maximum diversion time and the means of achieving the required level of safety.
- 2.2.1.5 Paragraph 2.2.2 provides further information on the EDTO certification requirements. Nevertheless, the EDTO certification criteria are detailed in Chapter 5 of the *Airworthiness Manual* (ICAO Doc 9760), which contains the airworthiness requirements for EDTO, and in particular guidance on the continuing airworthiness and airworthiness approval for aeroplanes with two turbine engines (except Paragraph 5.2 which is dedicated to the considerations for aeroplanes with more than two turbine engines). They are therefore not repeated in this manual.

| CAAM Cha | oter 2 – Aircraft Airworthiness Consideration for EDTO |
|-------------|---|
| 2.2.1.6 | The certified EDTO capability of the aeroplane is reflected in the type certificate data sheet (TCDS), the aircraft flight manual (AFM) or AFM EDTO supplement, as applicable, and the EDTO CMP document. |
| 2.2.1.7 | The EDTO certification of the aircraft granted by the State of Design should |

- 2.2.1.7 The EDTO certification of the aircraft granted by the State of Design should then be validated or accepted by the CAAM prior to the intended start of EDTO operations by the operator.
- 2.2.2 EDTO certification of aeroplanes with two turbine engines
- 2.2.2.1 Basic concept
- 2.2.2.1.1 The basic concept of the EDTO certification, as for EDTO authorisation, is to prevent the diversion to occur and to protect the safety of the aircraft should the diversion occur. Accordingly, the main intent of the EDTO certification requirements is to introduce:
 - a) reliability objectives, to minimise the occurrence of failures that could lead to a diversion; and
 - b) design features to retain a high level of systems performance.
- 2.2.2.2 EDTO design and reliability assessment
- 2.2.2.2.1 The EDTO certification of an aircraft is an assessment of compliance of the candidate aircraft with all the design provisions and reliability objectives of the applicable EDTO certification criteria (e.g., EASA CS25.1535 or FAA 14CFR 25.1535).
- 2.2.2.2.2 The State of Design will determine that the design features for a new transport category type design with two turbine engines intended to be used in EDTO are suitable for such operations. In the event that an existing aeroplane's operation is expanded to include EDTO operations, dedicated evaluation of some design features may be necessary.
- 2.2.2.3 Modifications to some systems may be required to achieve the desired reliability or system performance. In particular, the EDTO significant systems for the particular AEC should be shown to be designed to fail-safe criteria and to have achieved a level of reliability suitable for the intended operation of the aeroplane (see 2.2.3).
- 2.2.2.3 EDTO configuration, maintenance and procedures (CMP) document
- 2.2.2.3.1 The EDTO certification is reflected by the issuance of an EDTO CMP document. The EDTO CMP document gathers the required CMP and dispatch standards. For EDTO operations, the aircraft should be configured, maintained and operated according to the EDTO CMP document requirements.

- 2.2.2.3.2 The EDTO CMP document is approved by the State of Design. It is issued for the initial EDTO certification. It may be revised to reflect the conclusions of the in-service experience review (reliability surveillance performed by the State of Design). Refer to Paragraph 2.2.5 for further information on continued validity of EDTO certification.
- 2.2.2.4 Master minimum equipment list (MMEL)/minimum equipment list (MEL) for EDTO
- 2.2.2.4.1 Many airworthiness considerations for flight dispatch may already be incorporated into approved programmes for other aeroplanes or non-EDTO. The nature of EDTO necessitates a re-examination of these programmes to ensure that they are adequate for this purpose. System redundancy levels appropriate to EDTO should be reflected in the MMEL. An air operator's MEL may be more restrictive than the MMEL considering the kind of EDTO proposed and equipment and service problems unique to the operator.
- 2.2.2.5 Aircraft maintenance programme for EDTO
- 2.2.2.5.1 In the context of the EDTO certification, a review of the aircraft maintenance programme should be performed to confirm that it adequately supports the targeted EDTO operations. This review should address the scheduled and unscheduled maintenance tasks, as well as the pre-departure service checks (pre-flight, transit, daily and weekly checks, as applicable).
- 2.2.2.5.2 The maintenance tasks related to EDTO should be identified, in order to clarify when a given task has to be performed and/or released by an EDTO qualified technician. These tasks should be related to the EDTO significant systems identified for the applicable aeroplane engine configuration (see Chapter 4).
- 2.2.2.5.3 The maintenance tasks related to EDTO are tasks impacting EDTO significant system(s). In other words, tasks which are not impacting any EDTO significant system(s) should not be considered as EDTO-related tasks.
- 2.2.2.5.4 If needed, the EDTO-related tasks may be further categorised as follows:

EDTO specific task

This is any task that is uniquely required when the aircraft is operated on EDTO and identified in the associated CMP document.

These tasks may originate from either a specific:

a) aircraft configuration mandatory for EDTO, e.g., cargo fire protection system with increased protection time; or

- b) constraint related to the EDTO mission profile, e.g., increased flight duration, maximum EDTO diversion time (up to 180 minutes and beyond, etc.); or
- c) MMEL constraint for EDTO (e.g., SATCOM inoperative is a no-go item for EDTO beyond 180 minutes).
- d) These tasks and the related interval (defined through above relevant maintenance and/or safety analyses) should be listed in the EDTO CMP document.
- e) The operator should ensure that these tasks are revised in their approved maintenance programme and scheduled and performed in accordance with the applicable interval. In case of mixed EDTO/non-EDTO operations, compliance with the EDTO interval is required.

Note 1.— In the context above, "mixed EDTO/non-EDTO operations" means the same aircraft (or fleet of aircraft) is continuously operated on both EDTO and non-EDTO flights.

Note 2.— In case of "mixed EDTO/non-EDTO operations", any tasks to be performed prior to an EDTO flight (e.g., tasks from the EDTO predeparture service check) are not required to be performed before the non-EDTO flights.

EDTO relevant task

This is any task (other than EDTO specific task) impacting an EDTO significant system and addressing:

- a) an EDTO significant functional failure; or
- a reliability constraint with system/component design and requiring a different interval than the one quoted in the basic (non-EDTO) maintenance planning document (MPD) for the task to support EDTO operations.
- c) These tasks may be identified as EDTO relevant tasks to restore and/or maintain the reliability levels required for EDTO. These tasks may be listed in the EDTO CMP document.
- d) The operator should ensure that dual maintenance (scheduled or unscheduled) on identical (or substantially similar) EDTO significant systems during the same maintenance visit is to be specifically managed by the operator approved EDTO/ETOPS programme (see Chapter 4). This is to preclude common cause human failure modes.

2.2.2.6 Issuance of EDTO certification

- 2.2.2.6.1 Upon satisfactory completion of an engineering type design review and test programme, which may include certification flight test evaluation or other dedicated bench test and analyses, an EDTO certification (type design and reliability approval) is issued. The AFM or AFM EDTO supplement, as applicable, the EDTO CMP document and TCDS, or any other relevant manufacturer documentation or tools, should contain the following information as applicable:
 - a) special limitations, including any limitations associated with operation of the aeroplane up to the maximum EDTO capability being approved;
 - b) the airborne equipment, installation and flight crew procedures required for EDTO operations;
 - c) EDTO performance information including fuel consumption rates;
 - d) markings or placards;
 - e) the maximum diversion time capability of the aeroplane for EDTO as well as the time capability of the TLSs, e.g., the most limiting fire suppression system for Class C cargo or baggage compartments and the most limiting EDTO significant system other than fire suppression systems (see 2.2.4); and
 - f) the following or similar statement: "The type design, reliability and performance of this aeroplane/engine combination has been evaluated in accordance with the [state applicable EDTO certification criteria] and found suitable for [state maximum approved diversion time] EDTO operations when the configuration, maintenance, and procedures standards contained in [identify the applicable approved EDTO CMP document] are met. The actual maximum approved diversion time for this aeroplane may be less, based on its most limiting system time capability or other applicable limitation. This finding does not constitute an authorisation to conduct EDTO."
- 2.2.2.6.2 Paragraph 4.10 provides further guidelines and examples on how the above data may be included in the relevant manuals, documents and tools.
- 2.2.3 EDTO significant systems
- 2.2.3.1 An EDTO significant system is a system whose failure or degradation could adversely affect the safety of an EDTO flight or whose continued functioning is important to the safe flight and landing of an aeroplane during an EDTO diversion. Such systems include, but are not limited to:
 - a) electrical systems, including battery (if relevant);
 - b) hydraulics;
 - c) pneumatic systems;

- d) flight instrumentation;
- e) fuel systems;
- f) flight controls;
- g) ice protection systems;
- h) engine start and ignition;
- i) engine system instruments;
- j) navigation and communications;
- k) engines;
- I) auxiliary power units;
- m) air conditioning and pressurisation;
- n) cargo fire suppression;
- o) engine fire protection;
- p) emergency equipment; and
- q) any other equipment required for EDTO.
- 2.2.3.2 EDTO/ETOPS significant systems are identified to support EDTO/ETOPS design standards as well as support the acceptance of maintenance and operational procedures.
- 2.2.3.3 Classification of each EDTO significant system fall into either a Group 1 or a Group 2 system as follows:
 - a) an EDTO significant system is classified in Group 1 when its importance for EDTO relates to the number of engines of the aeroplane. Under this principle, this category contains the EDTO significant systems that are specifically more important for the safety of EDTO operations of two-engine aircraft; and
 - b) an EDTO significant system is classified in Group 2 when its importance for EDTO is the same for two-, three- and four-engine aircraft.
- 2.2.3.4 The identification of EDTO Group 1 systems is done through the assessment of the consequence of an engine failure. Therefore, these Group 1 systems are typically more relevant to twin-engine aeroplanes compared to four-engine aeroplanes.
- 2.2.3.5 Group 2 systems, which are typically common to two-, three- and four-engine aircraft, are not affected by these additional requirements related to reliability demonstration because it is considered that the basic type certification adequately covers the need. Nevertheless, the consequence of failure of such a system would still require to be addressed in the frame of the reliability (and

maturity) demonstration for EDTO, and any required corrective action could be mandated further to an assessment of the impact of the concerned system failure on the safety of the flight.

- 2.2.3.6 This classification is only necessary for the aircraft manufacturer when conducting the EDTO reliability demonstration under the early EDTO certification method in the context of aircraft certification activities, as additional requirements apply to Group 1 systems. The objective of the early EDTO demonstration is to validate the reliability of the aeroplane at entry into service, in accordance with the early EDTO certification process. This demonstration of reliability is required only for the EDTO Group 1 systems.
- 2.2.3.7 It is important to note that the Group 1 and Group 2 EDTO significant systems should be equally considered by the EDTO operator. In other words, this distinction is not needed in the context of EDTO operations and should not lead to a different consideration and treatment of Group 1 and Group 2 systems by the EDTO operator.
- 2.2.4 Time-limited systems (TLSs)
- 2.2.4.1 As per the EDTO certification criteria, the time capability of the cargo fire suppression system (for cargo or baggage compartments) and the other most time-limiting EDTO significant system must be demonstrated.

Note 1.— For aeroplanes with no time-limited EDTO significant system (other than the cargo fire suppression system), the value of "the other most limiting EDTO significant system" corresponds to the maximum diversion time assumptions taken in the safety analyses. In other words, there is no identified system, and this limitation therefore applies to all systems other than the cargo fire protection system.

Note 2.— The requirement to determine the time capability of "the other most limiting EDTO significant system" has been introduced by the new EDTO criteria. As explained in Paragraph 2.2.1, the ETOPS certifications granted before issuance or implementation of the new EDTO criteria remain valid. Therefore, for these ETOPS certifications, the time capability of "the other most limiting EDTO significant system" is not provided, and it is considered to be no less than the approved ETOPS (or EDTO) maximum diversion time capability of the concerned aircraft.

- 2.2.4.2 The time capability of the TLSs (i.e., the most limiting fire suppression system and the most limiting EDTO significant system other than the fire suppression system) are recorded in the AFM or AFM EDTO supplement, as applicable, the EDTO CMP document and TCDS, or in any other relevant manufacturer documentation or tools.
- 2.2.4.3 The time capability of the TLSs has to be adequately considered in the operational dispatch of the aircraft. Refer to Chapter 3 for detailed guidelines

on the consideration of the TLSs versus the maximum diversion time for the dispatch of the aircraft on EDTO routes.

- 2.2.5 Continued validity of EDTO certification (airworthiness monitoring)
- 2.2.5.1 As explained in Paragraph 1.5, the EDTO certification is not granted permanently. It is subject to continued surveillance by the State of Design of the in-service reliability of the worldwide fleet of the concerned aircraft model/type. This reliability surveillance may result in changes to the EDTO standards for the airframe or engines (i.e., service bulletins issued by the aeroplane manufacturer, maintenance or procedures mandated to restore the reliability).

Note.— Existing ETOPS certifications granted prior to the implementation of the new EDTO Standards remain valid and do not require recertification for EDTO.

- 2.2.5.2 These modifications/service bulletins, maintenance tasks or procedures necessary to restore the reliability may therefore be mandated through a new issue of the EDTO CMP document and/or dedicated mandatory continuing airworthiness information (MCAI).
- 2.2.5.3 The certified EDTO capability of the aircraft may therefore be reduced, suspended or even revoked if no solution exists to a major problem. This revised EDTO capability should be reflected as applicable in dedicated revision of the TCDS, AFM (or AFM EDTO supplement, as applicable) and EDTO CMP document (and/or through dedicated MCAI). EDTO operations of the concerned aircraft should not be performed beyond the revised EDTO capability.

2.3 Airworthiness considerations for aeroplanes with more than two turbine engines

- 2.3.1 General
- 2.3.1.1 As explained in Paragraph 2.1, EDTO certification is not required for aeroplanes with more than two engines. This means that the configuration and maintenance standards defined through the basic type certification of an aeroplane with more than two engines are considered as adequate for EDTO operations.
- 2.3.1.2 Nevertheless, a review of the TLS, if any, on aeroplanes with more than two engines should be performed by the aircraft manufacturer. The objective of this review is to confirm whether these time limitations have to be considered for the dispatch of EDTO flights and if the corresponding time limitation should be provided in relevant aircraft documentation.

- 2.3.1.3 As explained in Paragraph 2.1.5, there are no additional EDTO certification, maintenance procedures or maintenance programme requirements for aeroplanes with more than two engines.
- 2.3.2 EDTO certification of aeroplanes with more than two turbine engines
- 2.3.2.1 The subject of EDTO certification is not applicable to aeroplanes with more than two engines.
- 2.3.3 EDTO significant systems
- 2.3.3.1 EDTO significant systems are explained in Paragraph 2.2.3. As there are typically no additional EDTO airworthiness certification, maintenance procedures or maintenance programme requirements for aeroplanes with more than two engines, the consideration of the EDTO significant system is only necessary for the identification of the time capability of the most time-limiting EDTO significant system.
- 2.3.4 Time-limited systems (TLSs)
- 2.3.4.1 The time capability of the most time-limiting EDTO significant system must be identified. In most cases, this most time-limiting EDTO significant system is the cargo fire suppression system (for cargo or baggage compartments).
- 2.3.4.2 The time capability of the most time-limiting EDTO significant system should be reflected in the relevant manufacturer documentation or tools.
- 2.3.4.3 The time capability of the most time-limiting EDTO significant system has to be adequately considered in the operational dispatch of the aircraft. Refer to Chapter 3 for detailed guidelines on the consideration of this TLS versus the maximum diversion time for the dispatch of the aircraft on EDTO routes.
- 2.3.5 Continued validity of EDTO certification (airworthiness monitoring)
- 2.3.5.1 The subject of continued validity of EDTO certification is not applicable to aeroplanes with more than two engines.
- 2.3.5.2 As explained in 2.1.5, there are typically no additional EDTO airworthiness certification, maintenance procedures or maintenance programme requirements for aeroplanes with more than two engines.

3 EDTO Flight Operations Requirements

3.1 General

- 3.1.1 As explained in paragraph 1.4, an air operator's application to conduct EDTO operations, will be assessed based on the air operator's overall safety record, past performance, flight crew training, flight dispatcher training, maintenance training and maintenance reliability programmes. The data provided with the request should substantiate the air operator's ability to safely conduct and support these operations and should include the means used to satisfy the criteria outlined in this paragraph and in Chapter 4.
- 3.1.2 The operator should obtain from the CAAM an EDTO authorisation by specific approval before starting commercial operations of transport category aeroplanes over a specified route containing a point beyond the applicable EDTO threshold time.

Note 1.— Previously issued specific approvals for ETOPS programmes continue to be valid. Requests for new EDTO authorisations or changes to existing programmes will be assessed under the criteria outlined in this manual.

Note 2.— Minor revisions to existing approved ETOPS/EDTO programmes are addressed in 1.6.6.

- 3.1.3 The threshold time for transport category aeroplanes are established in CAD 6 Part 1 Chapter 4.7 for two-engine transport category aeroplanes and for transport category aeroplanes with more than two engines.
- 3.1.3.1 The threshold time for two-engine transport category aeroplanes conducting EDTO operations is set at 60 minutes in CAD 6 Part 1 Chapter 4.7. It is possible to select a greater threshold time value after a thorough assessment by the CAAM of the impact of such a value on non-EDTO operations by non-EDTO certified two-engine transport category aeroplanes.
- 3.1.3.2 The threshold time for transport category aeroplanes with more than two engines conducting EDTO operations is set at 180 minutes. It is possible to select another threshold time value after a thorough assessment by the CAAM of the impact of such value on existing operations and on the time limitations, if any, of transport category aeroplanes with more than two engines operated beyond the threshold time.

3.2 Conversion of threshold and maximum diversion time into distance

- 3.2.1 General
- 3.2.1.1 In order to relate threshold and maximum diversion times to an area of geographic applicability, the time value of interest must be converted into an

equivalent distance value which is typically expressed as a still-air (zero wind) range in nautical miles based on an assumed diversion speed schedule.

- 3.2.1.2 This distance value is then used to construct diversion radius arcs around enroute alternate aerodromes to establish the non-EDTO and EDTO areas of operation.
- 3.2.1.3 Guidance on performing the time-to-distance conversion is provided in 1.3.2.8.4. The conversion calculation itself is typically performed using aeroplane manufacturer data derived from operational documents and software tools or from basic aerodynamic speed relationships, as appropriate.
- 3.2.1.4 It should be noted that the 60-minute (non-EDTO) and EDTO areas of operation are defined in international standard atmosphere (ISA) and still-air (zero wind) conditions. Therefore, actual diversion times may be higher than the diversion times used to establish the corresponding area of operation. This is expected and does not constitute an area of operation exceedance as long as the planned route of flight remains within the applicable still-air range from an enroute alternate aerodrome.
- 3.2.1.5 The basic concepts of still-air diversion distance and area of operation are common to two-engine aeroplanes and to aeroplanes with more than two engines; however, the assumed flight conditions under which these assessments are performed differ as described in the following paragraphs. It should also be noted that the diversion speed/distance assessment is typically applied to a particular geographic area and AEC, and may vary for different fleets and regions. Also, the speed used to calculate the EDTO threshold distances for a particular operation may be different than the speed used to determine the EDTO maximum diversion distance.
- 3.2.2 Determining the applicable threshold/diversion distances aeroplanes with two engines
- 3.2.2.1 The time-to-distance conversion for two-engine aeroplanes is performed using an operator-selected one-engine-inoperative (OEI) speed which must be within the certified operational envelope of the candidate aeroplane. This calculation is by convention typically based on a still-air standard day thrust limited driftdown profile starting from normal cruise altitude at an assumed reference mass with maximum continuous thrust set on the remaining operating engine after the point of engine failure.
- 3.2.2.2 The OEI speed schedule is normally represented as a Mach/IAS (indicated airspeed) combination with constant Mach targeted during the initial portion of the driftdown profile followed by constant IAS after the aeroplane passes through the Mach/IAS transition altitude as illustrated in Figure 3.2-1.

- 3.2.2.3 Operators applying for EDTO authorisation should include justification for their selected OEI speed schedule and diversion distance calculation with their EDTO authorisation application.
- 3.2.2.4 Typical justification would consist of supporting manufacturer data derived from operational documents and/or software tools. Additional justification may include relevant operator performance calculations and flight planning system implementation. Table 3-1 is a typical example of manufacturer diversion distance information for operational planning and justification (data formats may vary).
- 3.2.2.5 The time-to-distance conversion for two-engine aeroplanes is sometimes, but not normally, based on a constant true airspeed (TAS) assumption instead of the more typical Mach/IAS OEI speed schedule described above, due to local regulation variations or limitations in operator flight planning systems.
- 3.2.2.6 While the constant TAS method may have been used in some legacy EDTO programmes, industry standards have evolved to the more typical driftdown calculation based on Mach/IAS speed parameters which can actually be targeted by the flight crew. The relationship between time and distance is non-linear with this calculation approach due to the variation in altitude with time during the thrust limited driftdown portion of the engine failure profile.



Figure 3.2-1. Driftdown profile example: Max OEI speed / Max continuous thrust (MCT)

| MAXIMUM DIVERSION DISTANCE | | | | | | | | | |
|----------------------------|--------------------------------|----------------------|-----|-----|------|------|------|--|--|
| Speed | A/C mass at | Diversion time (Min) | | | | | | | |
| schedule | critical point (x 1 000 kg) | diversion | 60 | 120 | 180 | 300 | 370 | | |
| | 170 | 190 | 439 | 866 | 1294 | | | | |
| | 190 | 180 | 436 | 860 | 1285 | 2136 | 2500 | | |
| MCT/220KT | 210 | 170 | 434 | 853 | 1272 | 2110 | 2500 | | |
| MC1/330K1 | 230 | 160 | 431 | 844 | 1257 | 2083 | 2500 | | |
| | 250 | 150 | 427 | 834 | 1241 | 2056 | 2500 | | |
| | 270 | 140 | 422 | 823 | 1225 | 2027 | 2496 | | |
| | 170 | 220 | 424 | 837 | 1249 | | | | |
| | 190 | 220 | 424 | 836 | 1249 | 2073 | 2500 | | |
| MCT/200KT | 210 | 220 | 419 | 827 | 1238 | 2062 | 2500 | | |
| NIC 1/300KT | 230 | 210 | 415 | 818 | 1224 | 2036 | 2500 | | |
| | 250 | 190 | 412 | 806 | 1200 | 1988 | 2448 | | |
| | 270 | 180 | 407 | 795 | 1184 | 1960 | 2413 | | |

Table 3-1. Example EDTO diversion distance information

3.2.2.7 <u>Sixty-minute threshold</u> – The 60-minute threshold distance calculation is used to determine whether the Standards for two-engine aeroplanes set forth in CAD 6 Part 1, 4.7.1, are applicable. The calculation is normally based on a high engine inoperative speed up to the maximum permissible operating speed or Mach number (VMO/MMO) in order to maximise the 60- minute area of operation.

3.2.2.8 <u>EDTO threshold</u> – The EDTO threshold distance calculation is used to determine whether the Standards set forth in CAD 6 Part1, 4.7.2, are applicable. This calculation is also used to determine the EDTO entry and exit points in an EDTO operational area. The calculation is based on a 60-minute diversion time as in 3.2.2.7.

Note. — The EDTO threshold distance calculation will be common to the 60minute threshold distance calculation for a given region and aeroplane type.

- 3.2.2.9 EDTO maximum diversion distance
- 3.2.2.9.1 The EDTO maximum diversion distance calculation for two-engine aeroplanes is required if an operation has been determined to have a need to exceed the geographic area constraints defined by the EDTO threshold distance.
- 3.2.2.9.2 The time-to-distance conversion is performed at the operator's approved or proposed OEI cruise speed and maximum EDTO diversion time for a particular aeroplane type (AEC) and operational area. This defines the maximum still-air radius that a flight can be from an en-route alternate aerodrome. These computations are typically performed considering a relatively high OEI speed to maximise the EDTO area of operations; however, other considerations such as diversion fuel requirements may dictate a lower speed selection. The selected EDTO OEI speed schedule also has implications on EDTO diversion fuel planning which is discussed in 3.5.3.
- 3.2.2.9.3 For EDTO operations, the threshold and maximum diversion distance calculations should normally be based on the same OEI speed schedule.
- 3.2.3 Determining the applicable threshold/diversion distances aeroplanes with more than two engines
- 3.2.3.1 For aeroplanes with more than two engines, the speed used to convert the 60minute, EDTO thresholds and EDTO maximum diversion times to corresponding diversion distance values is not an OEI speed as for two-engine aeroplanes, but rather an assumed all-engine cruise speed which is selected by the operator based on the performance characteristics of the particular AEC. As with two-engine aeroplanes, the selected speed must be within the aeroplane's certified operational flight envelope, and thus, must be less than or equal to the maximum operational speed (MMO and/or VMO) defined in the AFM or other relevant documentation or tool(s) from the aeroplane manufacturer.
- 3.2.3.2 The selected all-engine cruise speed used to calculate the applicable distances for aeroplanes with more than two engines does not have any fuel planning implications, so typically the highest possible speed may be used to maximise

the corresponding operational area. EDTO diversion fuel planning is discussed in 3.5.3

- 3.2.3.3 Further, the most favourable cruise altitude may be used in the calculation since altitude capability constraints are not a factor. For a given selected all-engine cruise speed and altitude, the time-to-distance relationship for aeroplanes with more than two engines is essentially a TAS conversion based on standard aerodynamic relationships and therefore the aeroplane/engine specific manufacturer diversion distance information is not required.
- 3.2.3.4 Operators applying for EDTO authorisation should include justification for their selected all-engine cruise speed with their EDTO authorisation application. Typical justification would consist of supporting performance calculations and manufacturer data derived from operational documents or software tools. Additional justification may include details on flight planning system implementation.
- 3.2.3.5 <u>Sixty-minute threshold</u> The 60-minute threshold distance calculation is used to determine whether the Standards for aeroplanes with more than two engines set forth in CAD 6 Part1, 4.7.1, are applicable. The calculation is normally based on a high all-engine cruise speed up to MMO/VMO in order to maximise the 60-minute area of operation.
- 3.2.3.6 <u>EDTO threshold</u> The EDTO threshold distance calculation is used to determine whether the Standards set forth in CAD 6 Part1, 4.7.1, are applicable. This calculation is also used to determine the EDTO entry and exit points in an EDTO operational area. The calculation is based on a 180-minute diversion time.
- 3.2.3.7 EDTO maximum diversion distance
- 3.2.3.7.1 The EDTO maximum diversion distance calculation for aeroplanes with more than two engines is required if an operation has been determined to have a need to exceed the geographic area constraints defined by the EDTO threshold distance. The time-to-distance conversion is performed at the operator's approved or proposed all-engine cruise speed and maximum EDTO diversion time for a particular aeroplane type (AEC) and operational area, and defines the maximum still-air radius that a flight can be from an en- route alternate aerodrome. As with the 60-minute and EDTO threshold distance calculations, the highest available all- engine cruise speed and most favourable altitude are generally used for this calculation to maximise the operational area, although some operators may choose to use different speed and altitude assumptions.
- 3.2.3.7.2 For EDTO operations, the threshold and maximum diversion distance calculations should normally be based on the same AEO speed schedule.

3.3 Operations beyond 60 minutes

- 3.3.1 Operations beyond 60 minutes from an en-route alternate aerodrome should incorporate the Standards set forth in CAD 6 Part1, 4.7.1. These operations may involve an EDTO authorisation, depending upon:
 - a) the applicable EDTO threshold times; and
 - b) the maximum diversion time used by the operator for the operations.
- 3.3.2 For two-engine aeroplanes, operations beyond 60 minutes would constitute an EDTO operation. For aeroplanes with more than two engines, an operation beyond 60 minutes would not involve EDTO authorisation, unless that operation is conducted beyond 180 minutes.
- 3.3.3 Regardless of whether EDTO is involved, all operations beyond 60 minutes from an en-route alternate aerodrome should incorporate suitable operational control and flight dispatch procedures, operating procedures and training programmes to support the operation. A specific approval is not required for these operations if they are not conducted beyond the applicable EDTO threshold; however, approved operating manuals and procedures should include the appropriate considerations as outlined in this CAGM.
- 3.3.4 En-route alternate aerodrome considerations two-engine aeroplanes
- 3.3.4.1 En-route alternate aerodromes are aerodromes to which an aeroplane may proceed in the event that a diversion becomes necessary while en-route, where the necessary services and facilities are available, where aircraft performance requirements can be met, and which are expected to be operational if required. Take-off and/or destination aerodromes may also be designated as en-route alternate aerodromes.
- 3.3.4.2 All operations beyond 60 minutes should include the identification of en-route alternate aerodromes in the dispatch process. The operational status of these aerodromes including meteorological conditions should be evaluated and the most up-to-date available information provided to the flight crew prior to departure. The flight crew should also have a means to obtain en-route alternate aerodrome weather updates as required during the flight.
- 3.3.4.3 The en-route alternate aerodrome assessment (irrespective of EDTO) should ensure that the forecast conditions at identified aerodromes will be at, or above, the operator's established aerodrome operating minima at the estimated time of use.
- 3.3.4.4 Additional considerations for EDTO alternate aerodromes are discussed in paragraph 3.5.2. These additional EDTO considerations are relevant to operations beyond 60 minutes.

- 3.3.5 En-route alternate aerodrome considerations aeroplanes with more than two engines
- 3.3.5.1 En-route alternate aerodromes are aerodromes to which an aeroplane may proceed in the event that a diversion becomes necessary while en-route, where the necessary services and facilities are available, where aircraft performance requirements can be met, and which are expected to be operational if required. Take-off and/or destination aerodromes may also be designated as en-route alternate aerodromes.
- 3.3.5.2 All operations beyond 60 minutes should include the identification of en-route alternate aerodromes in the dispatch process. The operational status of these aerodromes including meteorological conditions should be evaluated and the most up-to-date available information provided to the flight crew prior to departure. The flight crew should also have a means to obtain en-route alternate aerodrome weather updates as required during the flight.
- 3.3.5.3 There is no specific requirement that weather conditions at identified en-route alternate aerodromes are forecast to be at, or above, the operator's established aerodrome operating minima.

3.4 Operations beyond EDTO threshold time considerations

Operations beyond the EDTO threshold time for the applicable aeroplane type require an EDTO specific approval and should incorporate the Standards set forth in CAD 6 Part1, 4.7.2. Specific considerations for maximum diversion time authorisation levels appropriate to two-engine aeroplanes and to aeroplanes with more than two engines are addressed in the following paragraphs.

- 3.4.1 Approval levels EDTO operations with two-engine aeroplanes
- 3.4.1.1 The EDTO operational approval level granted to an applicant will be consistent with the operational need (route requirements), the aeroplane EDTO capability, relevant operational experience and robustness of the operator's EDTO programme compliance. All EDTO authorisations require the operator to implement supporting flight operations and maintenance programmes as discussed in this chapter and in Chapter 4, respectively. These programmes should address continuing airworthiness, release considerations including weather and MEL, flight planning, training, en-route alternate aerodromes and communication capability.
- 3.4.1.2 The operational EDTO programmes, in general, contain the same basic elements regardless of the EDTO diversion time authorisation, but should be tailored as applicable to the relevant level of approved diversion time.
- 3.4.1.3 The following are major EDTO diversion time categories are typically authorised.

| VI) | |
|------|---|
| | Chapter 3 – EDTO Flight Operations Requirements |

3.4.1.4 Up to 90-minute authorisation

- 3.4.1.4.1 EDTO authorisations up to 90 minutes are generally associated with benign operational areas where higher diversion times are not required to support direct routing. In this case, some relaxation in the operational programme requirements relative to higher EDTO times may be implemented.
- 3.4.1.4.2 For instance, if the AEC does not have an EDTO certification for at least 90 minutes diversion time, the aircraft design features, and reliability should be assessed versus the relevant EDTO design requirements. This assessment should confirm the suitability of the aircraft for such operations without requiring a formal EDTO certification.
- 3.4.1.4.3 Consideration may be given to the authorisation of EDTO up to 90 minutes for operators with minimal or no in-service experience with the AEC. This determination considers such factors as the proposed area of operations, the operator's demonstrated ability to successfully introduce aeroplanes into operations, and the quality of the proposed continuing airworthiness and operations programmes.
- 3.4.1.4.4 Minimum equipment list (MEL) restrictions for 120 minutes EDTO should be used if available, unless there are specific restrictions for 90 minutes or less.
- 3.4.1.5 Beyond 90-minute and up to 180-minute authorisation
- 3.4.1.5.1 EDTO authorisations up to 180 minutes support most EDTO operational areas and reflect the vast majority of worldwide EDTO operations.
- 3.4.1.5.2 The AEC must be approved for EDTO in the type certification up to at least the maximum diversion time being requested (e.g., 120, 180 minutes).
- 3.4.1.5.3 The operator must comply with the MEL requirements appropriate to the approved maximum diversion time (e.g., 120 minute EDTO and beyond). The operator's MEL cannot be less restrictive that the MMEL appropriate to the approved maximum diversion time.
- 3.4.1.6 15% diversion time authorisation increases
- 3.4.1.6.1 If the certified EDTO capability of the aeroplane is 120- or 180-minute maximum diversion time, an operator may request an increase in the operator's approved diversion time for specific routes or on an exceptional basis provided:
 - a) the requested operator's approved diversion time does not exceed:
 - 1) 115% of the certified maximum diversion time capability of the aeroplane for EDTO; and

- 2) the capability of the most limiting EDTO significant system other than fire suppression systems minus 15 minutes;
- b) the operator's dispatch process (fuel calculation, MEL, etc.) supports the resulting increased diversion time; and
- c) such increases may require an assessment of the overall type design including TLSs and demonstrated reliability if the certified EDTO capability of the aeroplane is less than the contemplated increased diversion time.
- 3.4.1.7 Beyond 180-minute authorisation
- 3.4.1.7.1 Beyond 180-minute maximum diversion time, authorisation may be required for direct routing in some operational areas based on limited availability of en-route alternate aerodromes, or to manage day-of-flight operational exceptions. These may include, for instance, the North Pacific areas as well as routes which traverse the southern oceanic regions.
- 3.4.1.7.2 Authorisation to conduct operations with diversion times exceeding 180 minutes may be granted to operators with previous EDTO experience and an existing 180-minute EDTO authorisation on the AEC listed in their application (see 1.4.2). The authorisation by specific approval to operate EDTO by more than 180 minutes may be area- specific, based on the availability of en-route alternate aerodromes in the operational area.
- 3.4.1.7.3 In view of the long diversion time involved, the operator is responsible to ensure at the flight planning stage, that on any given day in the forecast conditions (such as prevailing winds, temperature and applicable diversion speed), a diversion to an en-route alternate aerodrome will not exceed the capability of:
 - a) the most limiting EDTO significant system other than fire suppression systems minus 15 minutes at the approved OEI cruise speed; and
 - d) the cargo fire suppression system minus 15 minutes, at the AEO cruise speed.
- 3.4.2 Authorisation levels EDTO operations with aeroplanes with more than two engines
- 3.4.2.1 Operations up to 180 minutes

Operations up to 180 minutes diversion time from an en-route alternate aerodrome by aeroplanes with more than two engines do not require an EDTO authorisation.

3.4.2.2 Beyond 180-minute authorisation

- 3.4.2.2.1 EDTO authorisation is typically required for aeroplanes with more than two engines if the intended operation exceeds 180 minutes diversion time from an en-route alternate aerodrome. There are no specific maximum diversion time authorisation levels other than to allow operations beyond the applicable threshold time; rather it is the EDTO TLS capability of the particular aeroplane which establishes the basis for diversion time planning to an en-route alternate aerodrome. The EDTO TLS is typically determined by the cargo fire suppression system capacity unless another EDTO system time limitation has been specified by the aeroplane manufacturer (see 2.3.4). Operational planning considerations as relate to EDTO TLSs are addressed in paragraph 3.5.
- 3.4.2.2.2 As with two-engine aeroplanes, EDTO authorisations for aeroplanes with more than two engines require the operator to implement a supporting flight operations programme. This programme should address release considerations including weather and MEL, flight planning, training, en-route alternate aerodromes and communication capability (see 3.5).
- 3.4.2.2.3 EDTO authorisations for aeroplanes with more than two engines do not, however, require an EDTO certification (see 2.3.1.3). Further, EDTO maintenance procedures or EDTO maintenance programme requirements are not applicable to aeroplanes with more than two engines as discussed in 4.1.1.
- 3.4.3 Polar operations -RESERVED-

3.5 Flight preparation considerations

The flight preparation considerations discussed in these paragraphs are in addition to, or to amplify, the standard operating requirements and specifically apply to EDTO operations. Although many of the following criteria may be incorporated into approved programmes for non-EDTO aeroplanes or route structures, the nature of EDTO necessitates that compliance with these criteria be re-examined to ensure that approved programmes are adequate for the intended EDTO operations.

- 3.5.1 EDTO area of operations
- 3.5.1.1 General
- 3.5.1.1.1 Following satisfactory compliance with the criteria outlined in these paragraphs, an air operator may be authorised to conduct EDTO with a particular AEC within a particular area of operation. The EDTO area of operation is limited by the maximum approved diversion time to an en-route alternate aerodrome at the approved diversion speed (under ISA conditions in still-air) from any point along the proposed route of flight.

3.5.1.1.2 The EDTO area of operations is established during the flight preparation process based on the designated en-route alternate aerodromes (see 3.5.2) and the maximum diversion distance corresponding to the approved EDTO maximum diversion time and speed (see 3.2.3.7 and 3.2.2.9). This area is typically represented graphically by maximum diversion distance arcs or circles around the selected en-route alternate aerodromes to establish a geographic boundary limitation for the planned route of flight. Examples of EDTO area of operations illustrations are provided in 3.5.1.3.

Note.— The EDTO area boundary for route-planning purposes is based on a constant, still-air diversion distance radius from overhead the aerodrome location and neither considers potential routing nor approach path and descent profile, wind and temperature variations which may be encountered during an actual diversion.

- 3.5.1.1.3 The area(s) of operation approved for EDTO will be specified in the operations specification of the air operator. Flight dispatch limitations should specify the maximum diversion time from an EDTO en-route alternate aerodrome for which an air operator can conduct a particular EDTO operation. The planned maximum diversion time at the approved diversion speed shall not be any greater than the value specified in the operations specification.
- 3.5.1.1.4 Refer to 3.2.2.9 (for twin-engine aeroplanes) or 3.2.3.7 (for aeroplanes with more than two engines) for guidelines on how to convert maximum diversion time into distance.
- 3.5.1.2 EDTO entry and exit points EDTO sector
- 3.5.1.2.1 The EDTO sector comprises the portion or portions of an EDTO route that extends beyond the threshold circles (i.e., the 60-minute circles in the example shown below) centred on each en-route alternate aerodrome. The beginning of the EDTO sector is the first point on the route that is beyond the EDTO threshold time/distance from an en-route alternate aerodrome and is also called the EDTO entry point (EEP). The end of the EDTO sector is the last point on the route that is beyond the EDTO threshold time/distance from an en-route alternate aerodrome, which is also called the EDTO exit point (EXP).
- 3.5.1.2.2 For example, the illustration in Figure 3.5-1 depicts an EDTO route from Mauritius (MRU) to Kuala Lumpur (KUL) based on a 60-minute EDTO threshold time. The EEP is reached once the route passes the 60-minute area circle centred around MRU. The EXP is the point on the route defined by the 60-minute area circle centred around Banda Aceh (BTJ).
- 3.5.1.2.3 As depicted in Figure 3.5-1, the aerodromes which define the EDTO entry and exit points on an EDTO route are not necessarily the departure and destination airports, but rather the last aerodrome within the applicable

threshold time before the start of the EDTO sector and the first aerodrome after the EDTO sector where the remainder of the flight remains within the EDTO threshold time.

3.5.1.2.4 The EDTO entry and exit points on any given EDTO route are based on ISA still-air conditions and do not shift with prevailing winds. The EDTO sector which is defined by these points represents the portion of the route where the EDTO flight-planning considerations discussed in this chapter (fuel, alternate aerodromes, TLSs) are applied.



Figure 3.5-1. Example EDTO entry and exit points on EDTO route

- 3.5.1.2.5 An EDTO route may have multiple EDTO sectors if the route enters and exits EDTO airspace more than once or has a non-EDTO segment in the middle of the EDTO sector. Approved operators may plan such a flight based on multiple EDTO sectors (as illustrated in Figure 3.5-2a) or alternatively by treating the entire portion of the flight between the first EEP and the last EXP as a single EDTO sector (as illustrated in Figure 3.5-2b).
- 3.5.1.3 EDTO equal time points
- 3.5.1.3.1 An equal time point (ETP) is the point of equal flying time between two EDTO en-route alternate aerodromes. The ETP can also be defined as, "the point at the farthest 'air mile' distance from a pair of EDTO en-route alternate aerodromes". The ETP(s) define(s) the point(s) of the route from where the EDTO flight planning requirements discussed in this chapter (fuel, alternate aerodromes, TLSs) apply.

3.5.1.3.2 Unlike the EDTO entry and exit points which are based on still-air conditions, ETPs consider actual weather conditions (wind, temperature) and so their position on the route may be offset from the geometric midpoint between any given pair of EDTO en-route alternate aerodromes. If the flight level, wind and temperature are the same in both diversion directions, then the ETP is the geographic midpoint on the route between the EDTO en-route alternate aerodromes. If the weather conditions are different, the ETP moves along the route towards the most adverse en-route weather conditions.



Figure 3.5-2a. Example of multiple EDTO sectors



Figure 3.5-2b. Example of multiple EDTO sectors treated as a single sector

- 3.5.1.3.3 In the example shown in Figure 3.5-3a for a 120-minute EDTO flight from Mauritius to Kuala Lumpur, two EDTO ETPs are depicted in the EDTO sector. The first equal time point (ETP1) is defined by Mauritius and Gan Island as the first pair of designated EDTO en-route alternate aerodromes. The second equal time point (ETP2) is defined by the second pair of EDTO alternate aerodromes, Gan Island and Banda Aceh.
- 3.5.1.3.4 As shown in Figure 3.5-3b, a third equal time point (ETP3) is defined by the last pair of aerodromes, Banda Aceh (last EDTO alternate aerodrome) and Kuala Lumpur (destination aerodrome); however, it should be noted that ETP3 in this example is not within the EDTO sector, and thus EDTO flight planning considerations would not apply.
- 3.5.1.3.5 Figure 3.5-4 depicts the same route based on a 180-minute maximum diversion time with KUL as the last designated EDTO alternate aerodrome.
- 3.5.1.3.6 An EDTO route will typically have at least one ETP and may have several depending on the length of the EDTO sector, the selected EDTO en-route alternate aerodromes, and the applicable EDTO maximum diversion time.
- 3.5.1.3.7 The operator may elect to designate a single EDTO en-route alternate aerodrome to establish the EDTO area of operation, in which case there will be no ETP. See Figure 3.5-5. In such a case, diversion fuel and TLS protections should be assessed for any potential diversion track between the EDTO entry and exit points.
- 3.5.1.4 Equal time point (ETP) calculations
- 3.5.1.4.1 The flight condition, flight level and associated forecast weather used to determine the position of EDTO ETPs within the EDTO sector may vary depending on the particular EDTO flight planning requirement being addressed, the type of aeroplane and other specific requirements such as EDTO Critical Fuel Scenarios.
- 3.5.1.4.2 ETPs need to be established for:
 - a) computing the EDTO diversion fuel (see 3.5.3.2 and 3.5.3.3);
 - b) checking the maximum diversion time versus the applicable TLS values (see 3.5.4); and
 - c) in-flight diversion decision-making (see 3.6.2).
- 3.5.1.4.3 ETPs established for the purpose of EDTO diversion fuel planning are typically determined based on a decompression flight level of 10 000 ft (3 000 m). A higher decompression flight level may be assumed if supported by the aeroplane's supplemental oxygen supply and/or required to maintain minimum en-route altitudes along the diversion flight path. A second ETP

based on engine inoperative altitude may also be determined if diversion fuel protection is required for an engine–failure-only condition.

Note 1.— Operators may elect to standardise on a single ETP calculation (either decompression or engine failure) to simplify their flight planning process and flight plan presentation.



Figure 3.5-3a. Example EDTO equal time points (ETPs) (120 minutes)



Figure 3.5-3b.Example equal time point out of EDTO sector (ETP3)



Figure 3.5-4. Example EDTO equal time points (ETPs) (180 minutes)



Figure 3.5-5. Single EDTO alternate example with no EDTO equal time points (ETPs) (180 minutes)

- 3.5.1.4.4 ETP determination for the purpose of EDTO TLS planning may introduce yet another ETP calculation based on all-engine cruise speed and flight level, as this is the relevant flight condition used to evaluate cargo fire suppression diversion time protection for EDTO operations beyond 180 minutes. For aeroplanes where another EDTO significant system time other than cargo fire suppression has been established, the ETP basis used to evaluate diversion time protection for the other system is typically an engine failure condition with forecast weather conditions considered if the EDTO operation is beyond 180 minutes.
- 3.5.1.4.5 For EDTO operations up to and including 180 minutes, EDTO TLS requirements are typically directly related to the still-air EDTO maximum diversion time with a minimum additional margin of 15 minutes. For these operations, forecast weather conditions are not considered for EDTO TLS planning and therefore it is not necessary to determine TLS ETPs for EDTO flight planning purposes.
- 3.5.1.4.6 For in-flight progress monitoring and diversion decision-making, EDTO ETPs are typically considered to be the points along the route where the preferred or primary en-route diversion aerodrome switches to the next EDTO alternate listed on the operational flight plan. At the ETP itself, the diversion time to each of the two en-route alternate aerodromes which define the ETP is the same; however, as the flight passes the ETP it will get progressively closer to one aerodrome which becomes the new primary diversion aerodrome and progressively further away from the other aerodrome which was primary before passing the ETP. This same transition will occur at each ETP in the EDTO sector for cases where multiple ETPs are listed and a single listed EDTO alternate will be primary between any two sequential ETPs. Decompression ETPs are typically used as the basis for en-route progress monitoring relative to EDTO diversion aerodromes; however, operators may elect to also evaluate AEO and/or OEI ETPs for diversion decision-making, depending on the nature of the in-flight emergency and with due consideration for the increased complexity of managing multiple decision points between diversion aerodromes.

Note. — Operators are to include the EDTO ETPs in the operational flight plan navigation log and/or as position fixes on the flight management system navigation displays to aid the flight crew with flight progress monitoring relative to the EDTO sector.

3.5.1.4.7 In the event of a diversion on an EDTO flight, the flight crew is not obligated to divert to the primary EDTO alternate aerodrome listed on the flight plan and may chose a different aerodrome as the nearest suitable landing site if this is deemed to be a safer course of action based on prevailing operational conditions.

- 3.5.1.4.8 Other considerations related to in-flight decision making are discussed in 3.6.2.
- 3.5.2 Alternate aerodromes for EDTO
- 3.5.2.1 General
- 3.5.2.1.1 Alternate aerodromes, for the purposes of EDTO planning, are those aerodromes which an operator has been authorised to designate for enroute diversion planning within an approved EDTO area of operation. The operational assessment of these aerodromes typically involves two separate considerations, namely:
 - a) the basic adequacy of the aerodrome to support a safe approach and landing independent of operational variances; and
 - b) the forecast conditions at the designated aerodromes to support a safe approach and landing at the expected times of use during a particular EDTO flight.
- 3.5.2.1.2 These separate and complementary considerations are defined as "adequate aerodromes" and "EDTO alternate aerodromes".
- 3.5.2.1.3 An "adequate aerodrome" is an aerodrome which has been assessed to meet fundamental considerations other than weather, such as required runway length and an available approach procedure. These aerodromes are generally listed in the approved operator operations manual.
- 3.5.2.1.4 An "EDTO alternate aerodrome" is an adequate aerodrome which has been designated for a particular EDTO flight based on a dispatch assessment of the operational criteria outlined in the following paragraphs. The designated aerodromes should be listed in the operational flight plan.
- 3.5.2.2 Landing performance considerations
- 3.5.2.2.1 The runway length assessment for the adequate aerodromes selected to support an EDTO operation should typically be based on the AFM landing performance information provided by the manufacturer and defined in accordance with 2.2.7.1 item e) of CAD 8 Airworthiness of Aircraft, Part IIIB. The required runway length at the expected landing mass may be based on the dry runway performance considerations outlined in 1.6 of Appendix 10 in CAD 6 Part 1. Another method to determine the landing distance that can realistically be achieved in line operations (e.g., considering actual aeroplane stopping performance and runway surface condition) may be used, subject to approval from the CAAM.
- 3.5.2.2.2 Overweight landing procedures may need to be considered for EDTO diversion planning. For aeroplanes equipped with fuel jettison systems,

expected landing mass may be reduced to allow for fuel jettisoning provided the operator can demonstrate that flight crews are properly trained and that diversion fuel requirements (see 3.5.3) are not compromised.

- 3.5.2.2.3 The EDTO alternate aerodromes selected for a particular EDTO flight should be further evaluated to ensure sufficient runway length for the conditions at the expected time of arrival as part of the dispatch planning assessment. This assessment should take into account probable wind speed and direction, as well as expected runway surface condition.
- 3.5.2.2.4 For aerodromes with limiting local terrain, an evaluation of go-around climb gradient capability in the event of a missed approach following an OEI diversion may also need to be considered in the landing performance assessment.
- 3.5.2.3 Validity period/time window
- 3.5.2.3.1 The validity period is the time window during which a designated EDTO alternate aerodrome should be assessed for EDTO dispatch purposes to have the necessary conditions to allow a safe approach and landing in the event of an en-route EDTO diversion. The applicable time window should consider the earliest to latest expected arrival times for each EDTO alternate aerodrome based on the planned departure time. The validity period for a given EDTO alternate aerodrome is typically determined based on a diversion from the first and last EDTO ETPs for this alternate.
- 3.5.2.3.2 Figure 3.5-6a illustrates this concept for the MRU-KUL route using GAN as an example. A "forward" diversion to GAN from ETP1 (MRU/GAN) would constitute the earliest estimated time of arrival (ETA) since ETP1 is the first point on the route where GAN becomes the primary planned EDTO alternate. Similarly, a "backward" diversion to GAN from ETP2 would represent the latest ETA since ETP2 is the last point along the route where GAN is the primary planned EDTO alternate.



Figure 3.5-6a. EDTO alternate validity period

- 3.5.2.3.3 The earliest to latest arrival times may consider different diversion flight profiles, for example, high speed vs low speed cruise, or may be standardised on a specific EDTO non-normal flight profile, such as an engine failure or decompression, depending on the operational flight planning system implementation. Further, the required validity period should be expanded to include additional margins such as one hour after the latest arrival time and one hour before the earliest arrival time.
- 3.5.2.3.4 For cases where the EDTO alternate aerodrome is located before the EDTO EEP (e.g., first EDTO alternate) or after the EDTO EXP (e.g., last EDTO alternate), the concept of earliest to latest arrival time is less obvious because there is not both a "forward" and a "backward" diversion track within the EDTO sector as was illustrated in Figure 3.5-6a. For these cases, the validity period as determined by the operational flight planning system should consider the potential en-route diversion exposure during the EDTO portion of the flight to include the EEP if the EDTO alternate aerodrome is located before the start of the EDTO sector and the EXP for the case of the last EDTO alternate aerodrome located after the EDTO sector.
- 3.5.2.3.5 This concept is illustrated in Figure 3.5-6b using MRU and KUL as examples. The validity period exposure for MRU as the first EDTO alternate aerodrome positioned before the start of the EDTO sector would be a backward diversion from the EEP and a backward diversion from ETP1 based on the assumed diversion flight profile(s) implemented in the operational flight planning system. The route of flight from the EEP to ETP1 is also the portion of the EDTO sector where MRU is the primary planned EDTO alternate aerodrome. Similarly, the validity period for KUL would consider a forward

diversion from ETP2 and from the EXP to cover the portion of the EDTO sector where KUL is the primary planned diversion alternate aerodrome



Figure 3.5-6b. Validity period of EDTO alternates located before or after the EDTO sector

- 3.5.2.3.6 Another unique case for the purpose of validity period determination is when a single EDTO alternate aerodrome is used to cover the entire EDTO sector as was previously discussed in 3.5.1.3 (Figure 3.5-5). For this case there are no EDTO ETPs, and the single EDTO alternate is therefore the primary planned diversion aerodrome for the entire EDTO sector. Consequently, the validity period should consider a forward diversion from the EEP to establish the earliest expected arrival time and a backward diversion from the EXP to establish the latest expected arrival time. This concept is illustrated in Figure 3.5-6c.
- 3.5.2.3.7 The EDTO alternate aerodrome validity period assessment should consider forecast weather conditions including visibility and ceiling minima based on the latest available information with appropriate dispatch planning margins as discussed in the next paragraph. Hours of operation, NOTAMs, forecast winds and other operational factors may also be included in the assessment to ensure that a safe approach and landing can be accomplished within the applicable time window.
- 3.5.2.4 EDTO alternate aerodrome weather minima
- 3.5.2.4.1 EDTO alternate aerodrome weather minima, for the purpose of dispatch planning, is defined in 4.3.4 of CAD 6 Part 1 to include specific criteria for
ceiling and visibility to ensure that forecast weather conditions will allow a safe approach and landing in the event of an en-route EDTO diversion. These weather minima should be assessed based on the latest available forecast information for the required validity period (see 3.5.2.3) for each designated EDTO alternate aerodrome.



Figure 3.5-6c. Validity period of the single EDTO alternate

- 3.5.2.4.2 The EDTO dispatch planning minima requirements are expressed as additives to the published operating minima for a particular approach. The intent of the requirements is that the aerodrome minima assessed for dispatch planning purposes are more conservative than the actual published operating minima required to conduct an approach and landing. This is to allow for the potential of deteriorating weather conditions after the EDTO flight has commenced, as illustrated in the following example. EDTO alternate aerodrome status monitoring and weather minima considerations once the EDTO flight is en-route are addressed separately in Paragraph 3.6.2.2.
- 3.5.2.4.3 Table 3-2 states the weather minima defined for EDTO flight preparation purposes in 4.3.4 of CAD 6 Part 1.

| Approach facility | Ceiling | Visibility |
|--|--|---|
| Precision approach | Authorised DH/DA plus an increment of 60 m (200 ft) | Authorised visibility plus an increment of 800 m |
| Non-precision approach or circling approach | Authorised MDH/MDA plus an increment of 120 m (400 ft) | Authorised visibility plus an increment of 1 500 m |

Table 3-2. Example EDTO dispatch planning minima

- 3.5.2.4.4 As a practical example of applying the dispatch planning minima depicted in Table 3-2, consider Gan Island, Maldives (GAN) which was used to illustrate the EDTO sector and EDTO ETP concepts discussed in 3.5.1.2 and 3.5.1.3.
- 3.5.2.4.5 GAN has a single landing surface as depicted in Figure 3.5-7 with opposing runway ends, RWY 10 and RWY 28. Each runway has several published non-precision approach procedures which provide for VOR DME, VOR, NDB and GPS approaches. Operators will typically plan for the most favourable authorised approach procedure and runway end when applying the EDTO planning minima, which in this case would be the GPS approach procedure from the standpoint of required ceiling or minimum descent altitude (MDA) as depicted in Figure 3.5-8 for RWY 28.



Figure 3.5-7.Gan Island Airport (GAN) example diagram

| RWY 28 | MDA | RVR | Circling |
|-----------|--------|---------|------------------|
| A | | | 400 ft (1 600 m) |
| В | 360 ft | 1 200 m | 500 ft (1 600 m) |
| С | | | 600 ft (2 400 m) |
| D | 360 ft | 2 000 m | 700 ft (3 600 m) |

Figure 3.5-8.GAN RWY 28 GPS approach minima

3.5.2.4.6 For an Approach Category D aeroplane planning for a straight-in approach to land, the required operating minima based on Figure 3.5-8 would be a ceiling (MDA) of 360 ft and a visibility of 2 000 m. Applying the additional margins depicted in Table 3-2 would yield required EDTO dispatch planning minima of 760 ft (360 ft + 400 ft) ceiling and 3 500 m (2 000 m + 1 500 m) visibility.

3.5.2.4.7 These more conservative weather minima would apply for dispatch planning purposes only and would need to be verified based on the latest available weather forecasts for the required validity period/time window discussed in 3.5.2.3

Note 1.— Circle-to-land approach procedures are not normally used for EDTO planning; however, if used, the same dispatch margins would apply to the published circling approach minima.

Note 2.— Approved required navigation performance (RNP) approach procedures may be utilised for EDTO planning, based on the requirements as per 7.2.2 of Annex 6, Part 1. Refer also to CAGM 6008 (II) – PBN for further guidance on PBN operations, which remains valid for EDTO.

3.5.2.4.8 Consideration for conditional forecast elements should also be taken into account, for example, a PROB 40 or TEMPO condition below the lowest applicable operating minima. For aerodromes with low landing minima (e.g., Category 2/3), contingent upon operator approval and aeroplane capability to conduct such operations, it may be used as an EDTO alternate provided the additives to the published operating minima as stated in 4.3.4 of CAD 6 Part 1 are added during dispatch planning.

Note.— The terms "Operating minima" or "landing minima" refer to the minima on the applicable approach chart, and not to the EDTO planning minima described in 3.5.2.4.2.

- 3.5.2.4.9 When dispatching under the provisions of the MEL, those MEL limitations affecting instrument approach minima should be considered in assessing the EDTO alternate aerodrome minima as should any NOTAMs affecting the published approach procedure.
- 3.5.2.4.10 The EDTO planning minima apply for dispatch only. Once the flight has commenced, the normal published operating minima required to conduct a safe approach and landing are applicable (see 3.6.2.2).
- 3.5.2.5 Rescue and firefighting services (RFFS)
- 3.5.2.5.1 In accordance with CAD 6 Part 1, 4.1.6, the RFFS protection of the EDTO alternate aerodromes that are deemed acceptable by the operator shall be contained in the operations manual.
- 3.5.2.5.2 As per the guidance contained in related CAD 6 Part 1, Attachment I, an acceptable RFFS protection for en-route EDTO alternate aerodromes may be either:
 - aerodrome RFFS Category 4 for aeroplanes with maximum certificated take-off mass of over 27 000 kg, or aerodrome RFFS Category 1 for all other aeroplanes, if the operator can provide 30 minutes of notification; or

- c) if the operator cannot provide the above 30 minutes of notification, an acceptable RFFS protection may be two categories below the aeroplane RFFS category.
- 3.5.2.5.3 In the case where the departure and/or the destination aerodromes and/or the departure and/or the destination alternate aerodromes are also EDTO alternate aerodromes, the acceptable RFFS protection would need to comply with the most restrictive of the applicable requirements of CAD 6 Part1, Attachment I.

Note. — Further reductions of the RFFS capability for all-cargo operations might be acceptable. Refer to CAD 6 Part 1, Attachment I for related applicable guidance.

- 3.5.3 EDTO fuel requirements
- 3.5.3.1 General
- 3.5.3.1.1 In addition to the normal contingency and reserve fuel requirements associated with non-EDTO flight operations, fuel planning for an EDTO flight must also consider the potential for an en-route diversion to a designated EDTO alternate aerodrome. This additional fuel planning protection is referred to as the EDTO critical fuel scenario and is an important aspect of the EDTO flight preparation process.
- 3.5.3.1.2 The EDTO critical fuel requirement considers the potential for the following three failure scenarios from the most fuel-critical EDTO ETP or "critical point" (CP) between designated EDTO alternate aerodromes as illustrated in Figure 3.5-9:
 - a) all-engine depressurisation;
 - b) one-engine-inoperative depressurisation; and
 - c) engine failure only (two-engine aeroplanes only).
- 3.5.3.1.3 The fuel required to satisfy the most limiting of these diversion scenarios will determine if additional EDTO critical fuel reserves are required for an EDTO flight. If the EDTO critical diversion fuel is less than the normal planned mission and reserve fuel remaining at the CP, there is no additional EDTO fuel uplift required. If, however, the normal planned fuel on board at the CP does not satisfy the critical fuel requirement, then additional EDTO reserve fuel uplift is required.



Figure 3.5-9. EDTO critical fuel scenarios

- 3.5.3.1.4 Figure 3.5-10a illustrates the case where no additional EDTO critical fuel uplift is required. The normal fuel calculation build-up on the left side of the figure depicts the total fuel uplift for an example flight including taxi, trip, contingency and normal reserve fuel. The right side of the figure depicts the normal trip fuel burn up to the CP and then the fuel required to satisfy the critical fuel diversion scenario. Since the total fuel required to satisfy EDTO fuel requirements on the right side of the figure is less than the normal fuel uplift on the left side of the figure, there is no need to adjust the normal planned fuel load for the purpose of EDTO diversion fuel protection.
- 3.5.3.1.5 Alternatively, Figure 3.5-10b illustrates a case where additional fuel uplift is required to satisfy EDTO fuel planning requirements. In this case, the EDTO fuel planning build-up shown on the right of the figure is greater than the normal fuel calculation shown on the left. As such, the normal planned fuel load must be adjusted by the additional fuel which represents the difference between the EDTO fuel calculation and the original normal fuel calculation.
- 3.5.3.1.6 Further details concerning the EDTO critical fuel calculation are provided in 3.5.3.2. Example operational applications are addressed in 3.5.3.3.
- 3.5.3.2 EDTO critical fuel reserve calculation
- 3.5.3.2.1 The EDTO critical fuel calculation can be best described in further detail by separating the diversion profiles into individual flight segments as follows:
 - a) descent from normal cruise altitude;
 - b) cruise to EDTO alternate aerodrome;
 - c) descend and hold over EDTO alternate aerodrome;
 - d) approach and land at EDTO alternate aerodrome; and

e) additional fuel allowances.



Figure 3.5-10b. Additional EDTO fuel required

- 3.5.3.2.2 Some common considerations should include the following:
 - a) Descent from normal cruise altitude
 - For the AEO and OEI depressurisation scenarios, an emergency descent to depressurisation altitude per the particular aeroplane's emergency descent procedures. The depressurisation altitude is typically considered to be 3 000 m (10 000 ft); however, a higher altitude may be planned for if the aeroplane is equipped with sufficient supply for the planned diversion time.

Note. — Although oxygen requirements are generally considered to be separate from EDTO requirements, oxygen requirements still need to be complied with for both EDTO and non-EDTO operations. This includes the assumed depressurisation diversion flight level used to calculate the EDTO critical fuel scenario which may be constrained by available oxygen supply. Oxygen requirements are addressed in 4.3.9 of CAD 6, Part I.

2) For the engine failure only scenario, if applicable, a normal idle descent to thrust limited altitude or a thrust limited driftdown profile with MCT on the operating engine. The assumed driftdown speed is typically the same Mach/IAS speed schedule that is used to determine the maximum EDTO diversion distance (see 3.2.1). It may therefore be a different speed than the one selected to define the EDTO threshold.

Note. — While an engine failure only critical fuel scenario is defined in 1.3.3.2.2, for two-engine aeroplanes, this condition is rarely limiting. This is because the depressurisation scenarios are typically based on a lower diversion flight level and thus carry a higher diversion fuel requirement. Consequently, some operators will not include the engine failure only scenario in their EDTO dispatch fuel calculations if determined to be a non-limiting condition.

- b) Cruise to EDTO alternate aerodrome
 - 1) For two-engine aeroplanes, the cruise speed used to calculate the engine failure critical fuel scenarios (engine failure combined with decompression and engine failure alone) should be the same as the approved OEI speed used to determine the EDTO maximum diversion distance (see 3.2.1). The cruise speed used for the all-engine decompression scenario calculation may be a different speed and is typically assumed to be all-engine long-range cruise (LRC) speed. There is no requirement to use the approved OEI speed for the all-engine critical fuel calculation.

Note. — The OEI speed used to calculate EDTO maximum diversion distance and engine inoperative critical fuel requirements for two-engine aeroplanes may vary for different geographic regions depending on route requirements, EDTO maximum diversion time, and availability of en-route

diversion aerodromes. Further, the OEI speed used to establish the 60minute and threshold distances for a non-EDTO operation may be different than the speed selected for an EDTO operation. EDTO fuel planning requirements are not applicable to an operation that remains within the established EDTO threshold distance.

- 2) For aeroplanes with more than two engines, there is no particular relationship between the speed used to establish maximum diversion distance and the assumed cruise speeds for the EDTO critical fuel calculation. Specifically, the speeds used to calculate the AEO and OEI decompression scenarios may be different speeds than the approved AEO speed used to determine the EDTO maximum diversion distance (see 3.2.2). The engine failure only scenario is not applicable to aeroplanes with more than two engines.
- The relationship between the speed basis for threshold distance, EDTO maximum diversion distance and the EDTO critical fuel calculations is summarised in Table 3-3.

| | 60 Min/EDTO Threshold Distance | EDTO max diversion distance | Critical Fuel – All engine depressurisation | Critical Fuel – Engine inoperative depressurisation | Critical Fuel – Engine failure only |
|--|--------------------------------------|-----------------------------------|---|---|---|
| Two engine aeroplanes | Any selected OEI speed | Approved OEI speed | Any selected AEO speed | Approved OEI speed | Approved OEI speed |
| Aeroplanes with more than two engines | Any selected AEO speed | Approved AEO speed | Any selected AEO speed | Any selected OEI speed | Not applicable |

Table 3-3.EDTO critical fuel scenario cruise speed modes

c) Descend and hold over EDTO alternate aerodrome

The critical fuel calculation should allow for a normal descent to 450 m (1 500 ft) above the EDTO alternate aerodrome followed by 15 minutes of holding. The descent is initiated from either depressurisation or engine inoperative altitude depending on the particular scenario.

d) Approach and land at EDTO alternate aerodrome

Fuel allowance for a standard instrument approach and landing should be included. A missed approach fuel allowance may also be specified in some State regulations; however, this additional fuel is not included in the EDTO Standards.

e) Additional fuel allowances

1.3.2.2.2 and 1.3.3.2.2 describes certain additional fuel allowances which should be included in the EDTO critical fuel calculation. These additional fuel allowances are summarised as follows:

• Fuel to account for icing:

This allowance is typically based on the higher of two fuel requirements, as determined from operational fuel planning data provided by the aeroplane manufacturer and the operator's assessment of potential diversion icing exposure for the EDTO flight:

- 1) fuel to account for engine anti-ice, and if applicable, wing antiice, for the entire time during which icing is forecast; or
- 2) fuel for the effect of potential ice accumulation on unheated surfaces (airframe icing) for 10% of the time during which icing is forecast including the fuel used for engine and wing anti-ice during this period.
- Fuel to account for errors in wind forecasting:

This fuel allowance is typically determined by applying a 5% factor to the forecast wind magnitude (increase for headwind, decrease for tailwind) if the operator is using actual forecast winds based on a wind forecast model accepted by the authority. If the operator is not using actual forecast winds based on a wind model accepted by the authority, an additional 5 % fuel allowance should be applied to the total critical fuel requirement to allow for errors in wind data.

• Fuel to account for deterioration in cruise fuel-burn performance:

This additional fuel allowance is typically based on operational analysis of actual cruise fuel mileage performance using tools provided by the aeroplane manufacturer or other sources. The analysis is normally performed for each aeroplane conducting EDTO operations, as deterioration factors can vary within an operator's fleet. If the operator is not performing cruise fuel mileage analysis for its EDTO operation, an additional 5 % fuel factor should be added to the total critical fuel requirement to account for potential deterioration in cruise fuel-burn performance. Note. — The fuel-burn performance of a particular aeroplane may be better than the performance level used for operational flight planning. For cases where the actual aeroplane performance has been determined to be better than the planning database level, the fuel-burn deterioration factor should be zero.

• Fuel to account for auxiliary power unit (APU) use (if required):

If the APU is a required power source for the EDTO critical fuel diversion scenarios, the additional fuel consumption required to operate the APU should be included in the relevant diversion scenarios. For most aeroplanes, APU fuel is included in the engine failure critical fuel scenarios but is typically not included in the all-engine depressurisation scenario unless required by aeroplane specific operating procedures.

- Fuel to account for any relevant configuration deviation list (CDL) and/or MEL items.
- 3.5.3.3 EDTO critical fuel operational application
- 3.5.3.3.1 The operational application of the EDTO critical fuel requirement consists of the requisite flight preparation calculations and the presentation of these results on the operational flight plan. The operator's flight planning system should have the capability to determine the critical fuel required (CFR) as described above and the normal planned fuel load at each EDTO ETP to determine if a fuel load adjustment is needed for a particular EDTO flight.
- 3.5.3.3.2 Flight planning system implementations and flight plan formats for EDTO critical fuel can vary, and it is important to recognise that operators engaged in EDTO operations may use different methods to meet the requirements. Figure 3.5-11a provides an example of a typical flight plan presentation of EDTO critical fuel information for the MRU KUL route. In this example, no additional critical fuel uplift is required because the normal fuel on board (FOB) is greater than the CFR at each of the two EDTO ETPs. This can be seen by comparing the FOB and CFR values and also because there is excess fuel (EXC) at each ETP. Note that in this example, ETP2 is the CP since the EXC is the lowest, even though there is no critical fuel adjustment required.

| | | | | | | | TIME TO |
|------|-----------|-----------|-----------|--------|--------|--------|-------------|
| | | DIST | W/C | CFR | FOB | EXC | ETP / ALT |
| ETP1 | FIMP/VRMG | 0873/0845 | P012/P000 | 016493 | 031564 | 015071 | 01.57/02.26 |
| | S14456 E0 | 71438 | | | | | |
| ETP2 | VRMG/WMKK | 0964/0994 | P003/P013 | 018164 | 019569 | 001405 | 04.23/02.45 |
| | S06438 E0 | 88048 | | | | | |



3.5.3.3.3 Figure 3.5-11b depicts a case for the same EDTO route example where a critical fuel adjustment is applied. Note that in this case, the CFR and FOB values are equal at ETP2 and the EXC is zero which indicates that the required fuel load was adjusted to meet the critical fuel requirement. The additional fuel adjustment, when required, will often also be indicated as "EDTO ADD" or "EDTO EXTRA" on the flight plan fuel build-up summary (Figure 3.5-11c).

 DIST
 W/C
 CFR
 FOB
 EXC
 ETP / ALT

 ETP1
 FIMP/VRMG
 0873/0845
 P012/P000
 016493
 030159
 013666
 01.57/02.26

 S14456
 E071438
 ETP2
 VRMG/WMKK
 0964/0994
 P003/P013
 018164
 018164
 000000
 04.23/02.45

 S06438
 E088048
 E088048
 E088048
 E088048
 E088048
 E088048



| | FUEL | TIME | | | | | OWE | 85061 | PYLD | 26803 |
|-----------|--------|-------|---|--------------|---|---|------|--------|------|--------|
| DEST WMKK | 34963 | 6+58 | • | | • | • | EZFW | 111864 | MZFW | 120300 |
| RESV | 3406 | 0+47 | | | | | ETOW | 154500 | MTOW | 154500 |
| DEST-MNVR | 0 | 0+ 0 | | • | • | | ELDW | 119537 | MLDW | 127800 |
| ALTERNATE | 0 | 00+00 | | 1.0 | | | | | | |
| HOLD-ALT | 2203 | 00+30 | | 3 • 3 | | • | | | | |
| EDTO ADD | 2064 (| 0+28 | | | | | | | | |
| REQD | 042636 | 08+43 | | | | | | | | |
| EXTRA | 000000 | 00+00 | | | | | | | | |
| TAXI | 100 | | | | | | | | | |
| TOTAL | 042736 | 08+43 | | | | | | | | |

Figure 3.5-11c. EDTO critical fuel flight plan adjustment

- 3.5.4 Time-Limited System (TLS) considerations
- 3.5.4.1 General
- 3.5.4.1.1 There are two kinds of TLS:
 - a) the systems limited by their capacity, e.g., the cargo fire extinguishers. Per design they cease to function once exhausted. The sizing of those systems may therefore have an impact on the aeroplane's maximum diversion time capability; and
 - b) the systems for which time capability is determined by their endurance or reliability. Systems falling into this category are normally designed to function over a duration which largely exceeds the duration of one flight. Therefore, the sizing of those systems usually has no impact on the aeroplane's maximum diversion time capability. For this reason, it is usually the maximum diversion time assumptions from the safety analyses that will define the related time limitation.

- 3.5.4.1.2 The time limitation of these systems may have to be considered in the design and the operation of an aeroplane for EDTO to ensure that EDTO operations are conducted within diversion times compatible with the capabilities of the relevant TLSs (see 2.2.4). Accordingly, this constraint applies only to timelimited EDTO significant systems which are defined in 2.2.3.
- 3.5.4.1.3 When the ETOPS rules were first published in 1985, it was required to consider only the time capability of the cargo fire suppression system, and this capability had to match the contemplated maximum approved diversion time (ISA, still-air) with an additional 15-minute margin. This margin was deemed to be sufficient to account for operational variances such as winds over the diversion for all operations up to 180 minutes maximum diversion time (ISA, still-air).
- 3.5.4.1.4 However, for operations beyond 180 minutes maximum diversion time, wind effects for these higher diversion times can be more significant, therefore the traditional 15-minute margin may not be sufficient if the maximum diversion time was not corrected with the actual forecast wind. This is why the concept of consideration of TLSs has been slightly revised with the introduction of the EDTO criteria.
- 3.5.4.1.5 As before, the aircraft manufacturer should identify the capability of the most time-limiting EDTO significant system which is usually the cargo fire suppression system. However, for aeroplanes with two turbine engines certified under the new criteria, the aircraft manufacturer should also identify the capability of the other most limiting EDTO significant system. (This is not required for aeroplanes with more than two engines.) The corresponding limitations are identified in relevant aeroplane documentation (e.g., for a twin in the EDTO CMP document as well as in the AFM).

Note.— Identification of the other most limiting EDTO significant system is performed by the manufacturer during the EDTO certification of the aeroplane which is not required by ICAO Standards for aeroplanes with more than two engines or for aeroplanes with two turbine engines certified against previous ETOPS Standards. Therefore, for aeroplanes with more than two engines, the time capability of the other most limiting EDTO significant system should also be identified and considered for EDTO operations of these aeroplanes.

- 3.5.4.1.6 As per the EDTO criteria in CAD 6 Part 1, these time limitations must be considered by the EDTO operators at time of dispatch, and the way these time limitations have to be considered is slightly different for EDTO up to 180 minutes and for EDTO beyond 180 minutes, as detailed in the following paragraphs.
- 3.5.4.2 EDTO up to 180 minutes (including the 15 % operational extension)

- 3.5.4.2.1 The time required to fly the distance to the planned EDTO alternate or alternates (including a 15-minute margin for approach and landing) at the approved OEI cruise speed in still-air and standard day temperature, should not exceed the time specified in the AFM (or other relevant aeroplane documentation) for the aeroplane's most TLS(s) time.
- 3.5.4.2.2 Considering the current rate of cargo fire occurrences (on a passengercarrying aeroplane) and the rate of engine failure, the probability of a simultaneous cargo fire and engine failure would be extremely remote (in the order of 10-13 per flight hour). Therefore, for the cargo fire suppression system, it may be acceptable to consider the AEO cruise speed (instead of the OEI cruise speed) when checking the time required to fly the distance to the planned EDTO alternate or alternates (including a 15-minute margin for approach and landing).

Note.— Initial ETOPS regulations implemented in 1985 required the use of the OEI cruise speed and flight level when checking the cargo fire suppression system time limitation. Consequently, most ETOPS/EDTO certified twin- engine aeroplanes have their cargo fire suppression system sized accordingly. Therefore, for twin-engine aeroplanes, it is acceptable to consider the same approved OEI cruise speed for the check of the aeroplane's most TLS(s) time.

- 3.5.4.2.3 Figure 3.5-12 illustrates the case of an operator with a 180-minute EDTO authorisation. In this example, as stated above, the operator has to check that the time specified in the AFM (or other relevant aeroplane documentation):
 - a) for the aeroplane's cargo fire suppression system, is equal to or greater than the granted maximum diversion time plus 15 minutes, i.e., 195 minutes in this case; and
 - b) for the aeroplane's most TLS time (other than cargo fire suppression), if any, is equal to or greater than the granted maximum diversion time plus 15 minutes, i.e., 195 minutes in this case. As explained in 3.5.4.1, this check is applicable only to aeroplanes certified against the new EDTO criteria.



Figure 3.5-12. Time-limited systems considerations for EDTO up to 180 minutes (example for 180 minutes)

- 3.5.4.2.4 It should be noted that some MMEL/MEL items may reduce the time capability of the EDTO TLS(s) (see also 3.5.5.2). These reductions should be taken into account when planning the aircraft on an EDTO sector, to ensure that the aircraft remains within the reduced time limitations as explained above. For example, an inoperative cargo fire suppression bottle would lead to a reduction of the related EDTO TLS capability.
- 3.5.4.3 EDTO beyond 180 minutes
- 3.5.4.3.1 A check should be performed at dispatch to confirm that the time required to fly the distance to the planned EDTO alternates (including the 15-minute margin for approach and landing) does not exceed:
 - a) for all aeroplanes, the time specified in the AFM (or other relevant aeroplane manufacturer documentation) for the aeroplane's cargo fire suppression system, considering a diversion at AEO cruise speed and altitude corrected for forecast wind and temperature; and
 - b) for twin-engine aeroplanes, the time specified in the AFM for the aeroplane's most TLS time (other than cargo fire suppression), considering a diversion at the approved OEI cruise speed and altitude corrected for forecast wind and temperature.
- 3.5.4.3.2 Any MMEL/MEL items impacting the capability of the EDTO TLS(s) should be taken into account, and corrected time limitations should be considered when performing this check (see also 3.5.5.2).

- 3.5.4.3.3 Figure 3.5-13 illustrates the case of an operator with a 240-minute EDTO authorisation which would result in a given diversion distance based on the approved cruise speed (OEI or AEO as explained in 3.2) and flight level in still-air and standard day temperature. Considering the forecast weather conditions (wind and temperature) along the concerned diversion track(s), the operator determines that the time needed to fly the resulting diversion distance is 216 minutes at the AEO speed and FL, and 248 minutes at the OEI speed and FL. Therefore, the operator has to check that the time specified in the AFM (or other relevant aeroplane manufacturer documentation):
 - a) for the aeroplane's cargo fire suppression system, is equal to or greater than the AEO diversion time plus 15 minutes, i.e., 231 minutes in this case; and
 - b) for the aeroplane's most TLS time (other than cargo fire suppression), is equal to or greater than the OEI diversion time plus 15 minutes, i.e., 263 minutes in this case. As explained in 3.5.4.1, this check is applicable only to aeroplanes with a dedicated EDTO certification.
- 3.5.4.3.4 Should the time limitation(s) be exceeded, the operator should plan the aeroplane on another track, possibly with a reduced diversion distance, to ensure that the aircraft remains within the relevant system time limitations as described above.



Figure 3.5-13. Time-limited systems considerations for EDTO beyond 180 minutes (example for 240 minutes)

3.5.4.3.5 Figure 3.5-14 provides an example of how the capabilities of the relevant EDTO TLSs may be documented in the AFM for a two-engine aeroplane certified for EDTO beyond 180 minutes. In this AFM example, the time capability of the cargo fire suppression system is stated to be 220 minutes so the maximum planned all-engine diversion time based on forecast weather conditions for EDTO flight preparation purposes would be limited to 205 minutes. In the above dispatch example (Figure 3.5-13), the actual allengine diversion time was determined to be 216 minutes. This is greater than the example AFM capability minus 15 minutes, so a new dispatch solution would need to be established (e.g., re-route and/or closer EDTO alternates) to satisfy the all-engine EDTO TLS diversion planning requirement. The example AFM TLS capability for OEI diversion planning is stated to be 290 minutes, so the actual forecast diversion time must be no greater than 275 minutes. Since the actual OEI diversion time in the dispatch example (Figure 3.5-13) was determined to be only 248 minutes, the OEI TLS planning requirement is satisfied. However, since both the AEO and OEI planning requirements must be satisfied, the dispatch solution would still need to be adjusted to ensure that the calculated all-engine diversion time with consideration for forecast weather conditions is less than or equal to 205 minutes.

Aeroplane Flight Manual EDTO beyond 180 minutes – time-limited system capabilities

The time capability of the cargo fire suppression system is **220 minutes** The time capability of all other EDTO significant systems is **290 minutes**



- 3.5.5 EDTO technical status of the aeroplane
- 3.5.5.1 General
- 3.5.5.1.1 As per CAD 6 Part1, 4.7.2, it is the responsibility of the operator to ensure that the relevant time limitations of the aeroplane engaged in EDTO operations are not exceeded, and, for aeroplanes with two turbine engines, that the aeroplane is certified and configured for the planned EDTO mission.
- 3.5.5.1.2 As the time limitations of a given aeroplane may be impacted by the configuration and/or the maintenance programme of the aeroplane, the operator should implement tools and/or procedures to ensure that the relevant EDTO capability and time limitation(s) of the aeroplane dispatched are compatible with the contemplated EDTO flight, as explained in 3.5.4.
- 3.5.5.1.3 In addition, as explained in Chapter 2, the EDTO certification of the aeroplane entails the issuance of an EDTO CMP document, which provides the required configuration, maintenance, procedures and dispatch

standards. For EDTO operations, the aircraft should therefore be configured, maintained and operated according to the EDTO CMP document requirements. This means that the operator should implement tools and/or procedures to track any aeroplane discrepancies that may impact the EDTO serviceability and operational capability of the aeroplane.

Note.— As explained in 2.1.5, the basic type certification standards and maintenance programme of aeroplanes with more than two engines provide the required level of safety intended for EDTO and are suitable for EDTO operations. Accordingly, the EDTO Standards do not introduce additional maintenance requirements or any additional certification requirements for aeroplanes with more than two engines. Therefore, in this case the EDTO status of aeroplanes with more than two engines is directly linked to the status of the relevant TLS. In other words, only maintenance or configuration changes to the relevant TLS may impact the EDTO status of aeroplanes with more than two engines.

- 3.5.5.1.4 An EDTO maintenance release statement should provide the flight crew with the assurance that:
 - a) the aircraft condition has been checked and confirmed to comply with the applicable EDTO dispatch requirements set forth in the company policies and applicable MEL;
 - b) the EDTO items of the applicable maintenance line check have been accomplished;
 - c) the aircraft configuration has been checked and confirmed to comply with the applicable configuration standards set forth in the EDTO CMP document (as applicable); and
 - d) the capability of relevant TLS(s) has been assessed.
- 3.5.5.1.5 The EDTO maintenance procedures manual (or equivalent) should define the content of the EDTO service check, and the procedures associated with the EDTO maintenance release (see also Chapter 4).
- 3.5.5.2 Maintenance release twin-engine aeroplanes
- 3.5.5.2.1 The EDTO status of the aeroplane should be confirmed before each EDTO flight. For that purpose, an EDTO release statement should be provided to the flight dispatcher by the relevant operator maintenance organisation (typically the maintenance control centre) for operational control and flight preparation purposes. This EDTO status of the aeroplane depends on:
 - a) the certified EDTO capability of the aeroplane;
 - b) the configuration of the aeroplane versus the applicable configuration requirements of the EDTO CMP document;

- c) the compliance of the aeroplane versus the applicable maintenance requirements of the EDTO CMP document;
- d) the capability of relevant TLS(s); and
- e) any inoperative system (MEL).
- 3.5.5.2.2 The relevant maintenance organisation (typically the maintenance control centre) of the operator should issue this EDTO maintenance release statement as part of the maintenance release (e.g., certificate of release to service) of the aeroplane. This EDTO maintenance release statement, which is typically included in the aircraft maintenance logbook, should clearly indicate:
 - a) whether the concerned aeroplane is EDTO capable (yes or no); and
 - b) the related maximum diversion time capability.
- 3.5.5.2.3 The flight dispatcher should carefully consider this information when preparing an EDTO flight for a given aeroplane, in order to ensure that the aeroplane will be dispatched within its EDTO capability.
- 3.5.5.2.4 Figures 3.5-15 and 3.5-16 are typical examples of EDTO release statements for two-engine aeroplane EDTO operations up to 180 minutes.
- 3.5.5.2.5 As shown in Figure 3.5-15, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is capable of EDTO; and
 - b) its maximum diversion time is 120 minutes (approved OEI speed/ISA/no wind).

| EDTO Status | | Diversion Time (min) | | | | |
|-------------|----|----------------------|-----|-----|--|--|
| YES | NO | 60 | 120 | 180 | | |
| | | | | | | |

Figure 3.5-15. Example of EDTO release statement (120 minutes)

- 3.5.5.2.6 As shown in Figure 3.5-16, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is restricted to non-EDTO operations; and
 - b) accordingly, its maximum diversion time is 60 minutes (OEI speed/ISA/no wind).

| EDTO | Status | Diversion Time (min) | | | | |
|------|--------|----------------------|-----|-----|--|--|
| YES | NO | 60 | 120 | 180 | | |
| | | | | | | |

Figure 3.5-16. Example of EDTO release statement (60 minutes)

- 3.5.5.2.7 As explained in 3.5.4.3, for EDTO operations beyond 180 minutes the operator has to check that the diversion flight times (plus 15 minutes) along the planned flight track do not exceed the time specified in the AFM (or other relevant aeroplane manufacturer documentation):
 - a) for the aeroplane's cargo fire suppression system, considering a diversion at the AEO speed and altitude; and
 - b) for the aeroplane's most TLS time (other than cargo fire suppression), considering a diversion at the OEI diversion speed and altitude.
- 3.5.5.2.8 Therefore, a dedicated process for the check and tracking of the time capability of the relevant EDTO TLS(s), if any, should be implemented in order to ensure that this information is adequately provided by the relevant maintenance organisation (typically the maintenance control centre) of the operator, and taken into consideration by the flight operations organisation (dispatchers and flight crews).
- 3.5.5.2.9 This may be done by including in the EDTO release statement the necessary check boxes for each of the possible values of time capability of the relevant TLS(s). The corresponding values should be updated, as part of the aeroplane's maintenance release, any time there is a situation impacting the time capability of the concerned TLS(s), e.g., in case of:
 - a) the system being inoperative;
 - b) the system being replaced by another with a lesser/greater time capability; and
 - c) maintenance action impacting the time capability of the system.
- 3.5.5.2.10 Figure 3.5-17 provides a typical example of an EDTO release statement for EDTO operations beyond 180 minutes. As shown in this example, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is capable of EDTO beyond 180 minutes;

- b) its maximum OEI diversion time is 325 minutes (340 minutes 15 minutes), at the OEI speed, considering forecasted wind and temperature; and
- c) its maximum AEO diversion time is 235 minutes (250 minutes 15 minutes), at the AEO speed, considering forecasted wind and temperature.

| EDTC |) Status | Diversion Time (min) | | | | |
|--------------|----------|---|-----|-----|-------------|--|
| YES | NO | 60 | 120 | 180 | >180 | |
| \checkmark | | | | | | |
| | | EDTO time-limited system capability (min): | | OEI | ☐ 290 ✓ 340 | |
| | | | | AEO | 250 250 300 | |

Figure 3.5-17. Example of EDTO release statement (EDTO beyond 180 minutes)

- 3.5.5.3 Maintenance release aeroplanes with more than two engines
- 3.5.5.3.1 As discussed in 2.1.5, it has been confirmed that for aeroplanes with more than two engines, both the basic type certification standards and maintenance programme provide the required level of safety for EDTO and are suitable for EDTO operations. Accordingly, the EDTO Standards do not introduce additional maintenance requirements or any additional certification requirements for aeroplanes with more than two engines. Nevertheless, it has also been concluded that a review of the time limitation of relevant TLSs, if any, is necessary for aeroplanes with more than two engines engaged in EDTO.
- 3.5.5.3.2 Therefore, the EDTO status of aeroplanes with more than two engines is linked to the status of the relevant TLS. In other words, only maintenance or configuration changes to the relevant TLS may impact the EDTO status of aeroplanes with more than two engines.
- 3.5.5.3.3 Per definition, the number of items that may impact this EDTO status should be very limited, and it may therefore not be necessary to implement a process for EDTO release statement as for twin-engine aeroplanes. Typically, the impact of an unserviceable TLS (e.g., an inoperative cargo fire suppression bottle) could be handled through the existing deferred defect

list, and the related diversion time limitation should be duly taken into consideration when planning the EDTO flight, as for any other MEL items.

- 3.5.5.3.4 Regardless, a system of EDTO release statements may still be implemented to facilitate the management of this EDTO status. Figure 3.5-18 provides an example of an EDTO release statement adapted to aeroplanes with more than two engines (the EDTO threshold has been set at 180 minutes).
- 3.5.5.3.5 As shown in Figure 3.5-18, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is capable of EDTO; and
 - b) its maximum AEO diversion time is 285 minutes (300 minutes 15 minutes), at the approved AEO speed, considering forecasted wind and temperature.



Figure 3.5-18. Example of EDTO release statement (aeroplanes with more than two engines

- 3.5.5.3.6 In Figure 3.5-19, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is restricted to non-EDTO operations; and
 - b) its maximum AEO diversion time is 180 minutes (195 minutes 15 minutes), at the approved AEO speed (ISA/no wind)





- 3.5.5.4 Minimum equipment list (MEL)
- 3.5.5.4.1 General
- 3.5.5.4.1.1 The operator's MEL should be developed based on the MMEL provided by the aeroplane manufacturer. The MMEL, which is approved by the State of Design in accordance with Annex 6, Part I₇ may be customised by the operator as a function of its operational policies and considering relevant national operational requirements. The operator should take the necessary steps to ensure that operator's MEL complies with all applicable EDTO requirements for the relevant aeroplane fleet type(s) and approved EDTO maximum diversion time capability.
- 3.5.5.4.1.2 The operator's MEL should also consider the specificities of the EDTO area of operation, such as:
 - a) maximum diversion time;
 - b) availability of en-route alternate aerodromes, and available facilities and equipment;
 - c) navigation and communication means; and
 - d) prevailing meteorological conditions.
- 3.5.5.4.1.3 The MMEL may include restrictions that are specific to EDTO operations. For example, a given MMEL item may require re-routing of the flight to remain within a lower maximum diversion time or even restrict the operation to a non-EDTO route as necessary. These specific requirements for EDTO flights must be clearly identified in the operator's MEL, and the operator's MEL cannot be less restrictive than the MMEL as appropriate to the approved maximum diversion time.

3.5.5.4.1.4 The EDTO restrictions of the MMEL/MEL may be related to:

- a) the allowable maximum diversion time;
- b) the capability of the TLS(s); and
- c) the applicable weather minima.

Note.— MMEL documents may use different terms in some cases to describe EDTO dispatch restrictions. For example, the term "ER" ("extended range") may be used to represent EDTO within the context of the MMEL/MEL or a flight time restriction to landing at an alternate aerodrome may be imposed without a specific reference to EDTO.

3.5.5.4.2 MEL with EDTO restrictions related to maximum diversion time

These EDTO restrictions are typically related to the number of equipment or systems required to be operative at dispatch for a flight with a given maximum diversion time. These restrictions may typically be formulated as follows:

- a) "May be inoperative provided that EDTO is not conducted", i.e. the aeroplane should be restricted to non-EDTO flights only; or
- b) "May be inoperative provided that EDTO beyond xxx minutes is not conducted", i.e. the aeroplane should not be dispatched on a flight with a diversion time above xxx minutes.
- 3.5.5.4.3 MEL with EDTO restrictions related to TLSs

These EDTO restrictions are typically related to components or equipment of the EDTO TLS(s), which may reduce the time capability of the system when they are degraded or inoperative (e.g. the cargo fire suppression system). These restrictions may typically be formulated as follows:

- a) "May be inoperative provided that EDTO beyond xxx minutes is not conducted", i.e., the aeroplane should not be dispatched on a flight with diversion time above xxx minutes; or
- b) "May be inoperative provided that operations beyond xxx minute diversion time are not conducted."
- 3.5.5.4.4 MEL with EDTO restrictions related to weather minima
- 3.5.5.4.4.1 These EDTO restrictions are typically related to components or equipment necessary in the conduct of satellite-based or ground-based instrument approaches. There may be MEL limitations affecting the instrument approach capability of the aeroplane. In this case, those MEL limitations affecting instrument approach capability should be considered in assessing the EDTO alternate aerodrome minima (see 3.5.2.4). The operator's EDTO flight preparation procedures should ensure that

aeroplane's approach capability including any MEL restrictions will meet the EDTO dispatch weather minima requirements for the designated EDTO alternate aerodromes.

3.5.5.4.4.2 These restrictions may typically be formulated as related to the aeroplane's approach capability and not necessarily connected to EDTO:

"May be inoperative provided approach minima do not require its use", i.e., the aeroplane's ability to conduct low visibility approaches is impacted.

3.6 In-Flight considerations

3.6.1 General

Most EDTO unique flight operations requirements are addressed in the EDTO flight preparation process (see 3.5). The additional in-flight considerations for EDTO primarily consist of enhanced awareness of aeroplane system and fuel status and monitoring of EDTO alternate aerodrome conditions to ensure a safe approach and landing during a potential EDTO diversion. Normal and non-normal aeroplane operating procedures are typically equally applicable to both EDTO and non-EDTO operations and are validated by the manufacturer to support EDTO during the certification process, if required. Other concurrent en-route operational considerations such as long-range navigation, long-range communication and airspace constraints (e.g., RVSM, MNPS, RNP) are also equally applicable to both EDTO flights within a given operational area.

Note 1. — In-flight considerations for EDTO are separate but complementary to the flight preparation considerations discussed in 3.5. The pilot-in-command is not bound by the EDTO planning assumptions and may exercise discretionary authority to deviate from these assumptions in the event of an in-flight emergency.

Note 2.— The in-flight assessment criteria for fuel, aeroplane system and EDTO alternate weather status differ from the assessment criteria used for EDTO flight preparation. These differences are noted where applicable in the following paragraphs.

- 3.6.2 In-flight monitoring
- 3.6.2.1 Communication/Navigation
- 3.6.2.1.1 EDTO operations typically include route segments which are outside the range of ground-based navigation and communication aids, and therefore long-range navigation and communication capability is generally required to support these operations. The requirement for long-range communication/navigation capability is, for the most part, not specifically connected to EDTO, but may be concurrent with an EDTO operation depending on the particular en-route airspace environment.

- 3.6.2.1.2 EDTO operators should establish procedures and minimum equipment requirements for the long-range navigation airspace regions of their approved EDTO areas of operation. This would typically include dual independent long-range navigation systems installed on the aeroplane, MEL equipment considerations, flight crew position monitoring and/or plotting procedures and contingency procedures in the event of a loss of long-range navigation capability. Long-range communication requirements are typically satisfied with dual high frequency (HF) radio installations and may also be supplemented with satellite-based voice and/or datalink communication systems. In addition to being able to communicate with oceanic control centres while en-route, EDTO communication capability should also consider the capability to communicate with the operator's maintenance and operations control facilities in the event that assistance is needed by the flight crew to manage a non-normal en-route situation. This company communication capability may be addressed in several ways including contracting with radio service providers, communication patches or relays and/or a dedicated operator HF station.
- 3.6.2.1.3 Some additional communication and navigation considerations for EDTO include the following:
 - a) for all EDTO operations where voice communication facilities are available, voice communication should be provided. While planning an EDTO flight, an operator should consider potential route and altitudes necessary for diversion to EDTO alternate aerodromes in determining whether voice communications facilities are available. Where voice communication facilities are not available or are of poor quality and voice communication is not possible, communications using an alternative system should be substituted;
 - b) for EDTO operation beyond 180 minutes, the aeroplane should be equipped with an additional communication system that is capable of providing immediate satellite-based voice communication. The system should provide communication capability between the flight crew and air traffic control, and between the flight crew and the air operator's operational control centre. While planning an EDTO flight beyond 180 minutes, an air operator should consider potential route and altitudes necessary for diversion to EDTO alternate aerodromes to determine whether immediate, satellite-based voice communications are available. Where immediate, satellite-based voice communications are not available or are of poor quality, communications using alternative system should be substituted;
 - c) communication facilities are available to provide reliable two-way communications between the aeroplane and the appropriate ground communication facility over the planned route of flight and the routes to any EDTO alternate aerodrome to be used in the event of a diversion.

It should be shown that current weather information, adequate status monitoring information and crew procedures for all aeroplane and ground facilities' critical systems are available to enable the flight crew to make go/no-go and diversion decisions;

- d) non-visual ground aids are available and located so as to provide, taking account of the navigation equipment installed in the aeroplane, the navigation accuracy required over the planned route and altitude of flight, and the routes to any alternate aerodrome and altitudes to be used in the event of a diversion; and
- e) visual and non-visual aids are available at the specified EDTO alternate aerodromes as required for the authorised types of approaches and operating minima.
- 3.6.2.2 Alternate aerodrome status (weather minima)
- 3.6.2.2.1 Once the flight is dispatched, the flight crew and the flight dispatcher should remain informed of any significant changes at the EDTO alternate aerodromes and should be updated with the latest weather and aerodrome information.
- 3.6.2.2.2 Prior to proceeding beyond the EEP, the pilot-in-command and the flight dispatcher should complete a review of all the EDTO alternate aerodromes identified on the operational flight plan and should ensure that the forecast weather is equal to or exceeds the published operating minima for the expected runway and approach procedure during the applicable validity period (see 3.5.2.3). For cases where the weather forecast does not meet the required published operating minima for landing, the flight plan should be amended where possible to include another EDTO alternate aerodrome (i.e., one which does meet the landing minima requirements) within the maximum authorised EDTO diversion time and within the aeroplanes EDTO TLS capability. If this cannot be done, the EDTO area of operation is compromised and the flight should continue as non-EDTO.

Note. — The in-flight EDTO alternate weather check prior to proceeding beyond the EEP is not the same as the flight preparation weather minima check described in 3.5.2.3. The in-flight check is based on published operating minima whereas the flight preparation check is based on the more conservative EDTO dispatch planning minima.

3.6.2.2.3 Once the flight has entered the EDTO area of operation, if the forecast for any of the designated EDTO alternate aerodromes is revised to below the landing limits or the EDTO alternate aerodrome becomes inadequate, the EDTO flight may continue at the pilot-in-command's discretion.

Note.— Despite the above consideration, it is good practice for the flight crew to continue to monitor the status of the EDTO alternate aerodromes

after the flight has entered the EDTO sector. This is typically done for the next primary alternate when approaching an EDTO ETP.

- 3.6.2.3 Fuel progress monitoring
- 3.6.2.3.1 As with any flight, it is important for the flight crew to monitor and maintain awareness of the fuel state of the aeroplane. This is particularly critical for an EDTO flight, given the potential for a long diversion to the nearest enroute alternate aerodrome.
- 3.6.2.3.2 As previously discussed in 3.5.3, the EDTO critical fuel calculation, which is an integral element of the EDTO flight preparation process, is intended to ensure that the planned fuel load is sufficient to support an en-route diversion from the most critical EDTO ETP critical point (CP) in the event of an engine failure, a depressurisation, or both, with appropriate planning allowances. This does not preclude the importance of en-route fuel progress monitoring, which is complementary to the flight preparation process. EDTO operators should develop appropriate en-route procedures for flight crews to track actual versus planned fuel burn on the operational flight plan (OFP) and appropriate contingency procedures in the event that the fuel state of the aeroplane becomes unacceptable to complete the intended mission. The importance of adhering to these procedures should be addressed in the EDTO training programme which is discussed in 3.9.
- 3.6.2.3.3 The EDTO critical fuel calculation (see 3.5.3) is strictly a flight preparation consideration and does not apply once en-route, as operational variances such as more adverse winds than forecast may result in actual fuel burns which differ from the assumptions used to produce the OFP. EDTO operators should develop a minimum en-route fuel policy as the basis for the flight crew to determine if the fuel remaining on the aeroplane is sufficient to complete the mission. It is not necessary for the calculated critical fuel to be on board when passing the EDTO ETPs including the CP provided these en-route policy reserves are satisfied.

Note. — Standards for in-flight fuel management including minimum fuel are provided in 4.3.7 of CAD 6, Part 1.

- 3.6.2.4 Procedures to support EDTO maintenance programme
- 3.6.2.4.1 General
- 3.6.2.4.1.1 While the EDTO programme requirements for flight operations and maintenance are discussed in Chapters 3 and 4, there is a necessary interface or connection between the two programmes in certain areas of shared responsibility. These programme interfaces should be addressed in EDTO flight operations manual (FOM) procedures (see Error! Reference source not found.) and training programmes (see 3.9) to ensure that all affected departments and personnel understand their roles

in supporting the EDTO operation. Specific areas where EDTO flight operations procedures may be implemented to support the EDTO maintenance programme are addressed in the paragraphs below.

Note.— As explained in 2.1.5 and 4.1.1, there are no additional EDTO airworthiness certification, maintenance procedures or maintenance programme requirements for aeroplanes with more than two engines. Although an operator may consider as good practice for its operations with aeroplanes with more than two engines some elements detailed in 3.6, it is primarily intended for and applicable to EDTO operations of twinengine aeroplanes only.

- 3.6.2.4.2 Auxiliary power unit (APU) in-flight start programme
- 3.6.2.4.2.1 EDTO operators should monitor the in-flight start performance of the APUs installed on their EDTO fleets as part of the EDTO reliability programme (see 4.10 and 4.16). Where an APU in-flight start programme is required, the sampling intervals and reliability tracking procedures are established under the EDTO maintenance programme. The primary role of flight operations is to actually execute the in-flight start attempts when directed and to record the success or failure for appropriate maintenance action. Specific procedures to address the flight operations role should include:
 - a) notification of APU in-flight start requirement to flight crews through the flight release process;
 - b) in-flight start instructions including number of start attempts, allowable altitudes and time required in cruise (cold soak) before initiating start attempts; and
 - c) documentation procedures for recording success or failure of start attempts.

Note.— The APU in-flight start sampling programme is in addition to cases where the APU must be started and running to support EDTO operations due to aeroplane configuration architecture, in-flight verifications, MEL status or en-route failure conditions.

- 3.6.2.4.3 Maintenance verification flights
- 3.6.2.4.3.1 The EDTO maintenance verification programme (see 4.12) is typically accomplished through positive system verification on the ground using procedures provided by the aeroplane manufacturer. There are, however, cases where an EDTO significant system fault resolution may require inflight verification through monitoring or exercising of the system by the flight crew. These cases are relatively infrequent, but may occur if a fault is dependent upon specific en-route conditions such as temperature or altitude.

| 3.6.2.4.3.2 | EDTO operators should establish flight operations procedures to address maintenance verification flights when required to include the following: | | | | |
|-------------|---|--|--|--|--|
| | a) identification of verification flight requirement through the operational control and flight release process; | | | | |
| | b) instructions to flight crew to identify the affected system(s) and what should be monitored or exercised; and | | | | |
| | recording and coordination procedures following success or failure of system verification. | | | | |
| 3.6.2.4.3.3 | An EDTO verification flight may be accomplished during an EDTO flight (e.g., prior to entering the EDTO sector) or a non-EDTO flight or on a dedicated non-revenue flight. The latter option is rarely used but is an option in meeting the requirement. | | | | |
| 3.6.2.4.4 | EDTO significant system discrepancies | | | | |
| 3.6.2.4.4.1 | EDTO significant systems are defined in 2.2.3 and their applicability to the EDTO maintenance programme is addressed in 4.6. The application to the EDTO flight operations programme is often confused because some systems identified as EDTO significant for maintenance programme purposes may also have flight preparation and/or en-route implications. As such, EDTO operators should clearly establish the relevance of system discrepancies to the respective areas in their EDTO programme documentation. | | | | |
| 3.6.2.4.4.2 | The "EDTO significant systems list" is developed by the operator | | | | |

- 3.6.2.4.4.2 The EDTO significant systems list is developed by the operator (typically based on aeroplane manufacturer guidance) and approved by the CAAM as an integral component of the EDTO maintenance programme. This list is applicable to the EDTO reliability (see 4.10) and EDTO verification programmes (see 4.12). The EDTO significant systems list is not intended for en-route purposes or for flight preparation purposes except as provided by the MEL.
- 3.6.2.4.4.3 Aeroplane systems which have EDTO flight preparation or flight release implications are a separate consideration from the EDTO significant systems list and should be addressed in the operator's MEL as discussed in 3.5.5.4. The MEL EDTO restrictions are typically based on the MMEL issued by the State of Design, which supports the certified EDTO capability of the aeroplane. Additional EDTO flight release restrictions may be included in the operator's MEL to reflect the specifics of the authorisation. The MEL should also include guidance on system failure responses after pushback and prior to take-off.
- 3.6.2.4.4.4 En-route flight crew responses to non-normal aeroplane system conditions are a separate consideration from the EDTO maintenance

programme and flight release procedures. Non-normal conditions and flight crew procedures which call for a technical diversion are provided by the aeroplane manufacturer in the quick reference handbook (QRH) or by other methods (e.g., electronic checklists). These procedures are validated during the EDTO certification of the aeroplane and are typically common to both EDTO and non-EDTO operations.

3.6.2.4.5 EDTO flight release after non-technical diversions

The release of an EDTO flight typically requires completion of an EDTO service check performed by properly qualified maintenance personnel (see 4.9). Qualified maintenance personnel may not, however, be available on-site following a non-technical diversion to an en-route alternate aerodrome from which a subsequent EDTO flight release is required. For such situations, EDTO operators may establish procedures to allow flight crews to accomplish the flight release by coordinating remotely with EDTO maintenance personnel. The roles, responsibilities and qualifications of involved personnel should be consistent with requirements set by the CAAM and should be clearly identified in the operator's EDTO procedures documentation.

Note. – Organisation may issue a limited certification authorisation to the commander and/or the flight engineer on the basis of the flight crew license held subject to being satisfied that sufficient practical training has been carried out

- 3.6.3 Diversion considerations
- 3.6.3.1 General
- 3.6.3.1.1 Many of the potential scenarios that could lead to an EDTO en-route diversion are events that rarely happen. However, like all the other events that could occur during flight, the flight crew should be prepared to handle the situation safely and effectively.
- 3.6.3.1.2 A key element of being well prepared for an EDTO diversion is the pre-flight briefing where possible areas of concern can be reviewed, and the potential plans of action communicated to all members of the flight crew without the added stress of required immediate action. A review of the weather and terrain along possible EDTO diversion tracks should ensure that the crew has a common plan for handling possible contingencies. On long flights, with crew members transitioning from a duty station to crew rest and back, it is important that standard operating procedures be followed to minimise any possible confusion about the aeroplane's position relative to EDTO ETPs and the direction of turn required to proceed to the nearest designated enroute alternate aerodrome on the operational flight release.

Note.— The EDTO alternate aerodromes determined during the EDTO flight preparation process provide one potential course of action in the event of an en-route diversion; however, the flight crew is not bound by the dispatch

assumptions and may select another diversion aerodrome if determined to be more suitable for the prevailing operational conditions.

- 3.6.3.2 Diversion decision-making
- 3.6.3.2.1 It is not possible to cover every combination of circumstances that might occur during a diversion so operator guidance to flight crews may be general only. It is left up to the judgment of the flight crew to conduct the flight in the safest manner possible in light of the prevailing operational conditions that exist at the time.

Note.— The specific guidance provided by EDTO operators to their flight crews should also include the details of terrain clearance or oxygen limited escape route policies and procedures which the operator has established. Terrain clearance and oxygen requirements are generally independent of EDTO and should be covered as needed in other applicable sections of the operator's operations manual.

3.6.3.2.2 There are a number of events that might prompt the flight crew to consider diverting on an EDTO flight. Some of these events are "technical" in nature and are addressed by non-normal procedures established by the aeroplane manufacturer which are generally common to all (EDTO and non-EDTO) operations. Typical examples of these technical events might include an engine failure or fire, cabin fire or smoke, decompression, multiple loss of AC power sources, multiple loss of hydraulic system power sources, a cargo fire or any other relevant "technical" situation that may have an adverse effect on the safety of flight.

Note.— Flight crew guidance and checklists for en-route technical failures including technical diversion criteria are provided by the aeroplane manufacturer in the aeroplane operating manual or through other methods (e.g., electronic checklists). The aeroplane operating manual thus provides the basis of technical diversion decision-making, as opposed to the MEL (see 3.5.5.4) or EDTO significant systems list (Paragraph 4.6) which are intended for use on the ground and are not relevant to en-route operations.

- 3.6.3.2.3 However, the vast majority of diversions that have occurred in actual EDTO service have been due to non- technical causes. Passenger and crew medical emergencies, adverse en-route weather conditions or EDTO alternate aerodromes becoming unavailable may also result in a diversion or air turn back. The nature of the emergency and its possible consequences to the aeroplane, passengers and crew will dictate the best course of action suitable to the specific situation. The flight crew must decide on the best course of action based on all available information. Operator procedures documentation and training programmes should support this decision-making process.
- 3.6.3.2.4 As noted above, the EDTO alternate aerodromes listed in the flight release for a particular EDTO flight provide one diversion option to the pilot-in-

command, as do the selected EDTO diversion planning speeds established by the operator. However, the EDTO alternates selected at dispatch may not be the only aerodromes available for the diversion and the EDTO OEI or AEO speeds used at the planning stage may not be the best choice for a particular circumstance. Operator policy should specify the authority of the pilot-in-command to deviate from these dispatch planning parameters in the event of an actual EDTO diversion.

3.6.3.3 Diversion strategies

- 3.6.3.3.1 Once the need for an EDTO diversion has been established and an en-route alternate aerodrome selected, the flight crew will need to consider how to actually conduct the diversion based on the nature of the emergency and prevailing operational considerations. Non-technical diversions or technical diversions which do not have a significant impact on the performance of the aeroplane would normally be performed at a typical cruise flight condition or at a higher all-engine cruise speed to minimise the diversion time as permitted by the aeroplane's fuel state.
- 3.6.3.3.2 For an engine failure diversion, the consequences of speed selection on the aeroplane's performance (e.g., fuel, altitude) can be significant particularly for a two-engine aeroplane. As such, it is important for the flight crew to understand these consequences and to have appropriate guidance to choose the safest and most appropriate diversion strategy. Typically, there are three primary considerations to determine the best course of action from the standpoint of OEI speed selection which may be described as follows:
 - a) Time strategy:

If minimum diversion time and getting the aeroplane on the ground as soon as possible are the most critical considerations, a high OEI speed strategy may be selected as permitted by the aeroplane's fuel state, altitude capability and structural integrity. For two-engine aeroplanes, the time strategy is sometimes considered to be equivalent to the approved OEI speed, but a higher speed approaching VMO/MMO could be selected if conditions warrant. The flight crew is not bound by the speed assumptions used for EDTO flight preparation purposes (see 3.5.

b) Fuel strategy:

If the fuel remaining to accomplish the diversion is the most critical consideration, OEI long-range cruise (LRC) speed or even maximum range cruise (MRC) speed could be selected to optimise fuel management during the diversion. EDTO critical fuel planning (see 3.5.3) will generally preclude the possibility of a fuel-critical EDTO diversion; however, fuel may nevertheless be a primary consideration in managing the diversion.

c) Obstacle strategy:

If the diversion track following engine failure will traverse high terrain, additional care should be taken in speed selection to ensure that enroute terrain clearance margins are maintained. The speed associated with maximum lift over drag ratio (L/Dmax) will provide the best OEI altitude performance and should be selected until clear of any limiting terrain.

3.6.3.3.3 Diversion decision-making and strategy considerations should be addressed in EDTO flight crew training programmes and procedures documentation. Aeroplane type specific information should be included such as flight management system (FMS) functionality to support a diversion and available engine inoperative performance data (e.g., altitude capability, diversion fuel, power setting) as implementations may vary for different EDTO fleets. The EDTO flight preparation assumptions (see 3.5) and associated margins as relate to en-route diversion strategy considerations should also be addressed.

3.7 Aeroplan performance data

- 3.7.1 An aeroplane should not be released on an EDTO flight unless the air operator's operations manual (see 3.8) contain(s) sufficient performance data to support all phases of any applicable EDTO operation, including flight preparation and enroute operations. The performance data should be based on information provided or referenced in the approved aeroplane flight manual (AFM) or from other operational documentation or software tools provided by the aeroplane manufacturer.
- 3.7.2 The following aeroplane performance data should be available to support EDTO flight and en-route operations as discussed in 3.5 and 3.6, respectively:
 - a) EDTO area of operations (diversion distance);
 - b) detailed OEI performance data for standard and non-standard atmospheric conditions covering:
 - 1) driftdown (includes net performance);
 - 2) cruise performance (altitude coverage including 3 000 m (10 000 ft));
 - 3) fuel requirements;
 - 4) altitude capability (includes net performance); and
 - 5) holding;
 - c) detailed AEO performance data, including nominal fuel flow data, for standard and non-standard atmospheric conditions covering:
 - 1) cruise performance (altitude coverage including 3 000 m (10 000 ft)); and
 - 2) holding;

d) details of any other conditions relevant to EDTO flight preparation including fuel used for thermal anti-ice, ice accretion on the unprotected surfaces of the aeroplane, and APU usage, as appropriate.

3.8 Operations Manual

- 3.8.1 Background
- 3.8.1.1 The operator should include EDTO information in the relevant part(s) of the basic operations manual.

Note. — See Appendix 2 of CAD 6 Part 1 for contents of Operations Manuals.

- 3.8.1.2 The EDTO content of the basic operations manual define EDTO flight operations practices supporting these operations as well as responsible persons and/or organisations. The manual should include, either directly or by reference to incorporated documents, the requirements described in Chapter 3.
- 3.8.2 Purpose
- 3.8.2.1 The purpose of the EDTO content of the basic operations manual is to provide involved personnel and EDTO authorised persons with a descriptive means aimed at ensuring safe and efficient EDTO operations.
- 3.8.2.2 Accordingly, all EDTO requirements, including supportive programme procedures, duties and responsibilities, should be identified as being related to EDTO. The operations manual should be submitted to CAAM for review and authorisation by specific approval with sufficient lead-time prior to the scheduled commencement of EDTO operations of the particular aeroplane type, model or variant (AEC).
- 3.8.2.3 The EDTO content of the operations manual should typically address the following topics:
 - a) general information on applicable EDTO rules and the operator's EDTO programme;
 - b) scope of operator's EDTO authorisation (routes, fleet, threshold and diversion time(s) and speed(s), etc.);
 - c) EDTO flight planning considerations;
 - d) EDTO en-route considerations; and
 - e) EDTO training.

3.8.3 Revision control

Revisions to the EDTO content of the basic operations manual should be reviewed and approved as applicable by the CAAM for changes to the programme.

3.9 EDTO training programme

3.9.1 General

- 3.9.1.1 An operator's flight operations personnel should complete approved training on EDTO prior to the operator receiving an EDTO authorisation. Flight crews, dispatchers and other relevant flight operations personnel should be trained in the appropriate background in EDTO regulations and processes and the operator's specific EDTO procedures in order to properly support the operation. An operator's training programme should take into consideration the background and experience of the personnel being trained. Changes in EDTO regulations and operator policy related to the EDTO operation should be emphasised on a regular basis. This may be included in regular recurrent training or through circulation of printed training material, as applicable.
- 3.9.1.2 EDTO training programmes should include the specific regulations, authorisations (fleets, operational areas), policies, procedures and documentation related to the particular EDTO operation and therefore they can vary in both content and delivery. One EDTO operator may, for example, employ computer-based training (CBT) resources for EDTO academic training while another may elect to use classroom instruction or a combination of both. The duration of initial EDTO training programmes may vary as may the frequency and content of recurrent training.
- 3.9.1.3 What is important from the standpoint of EDTO flight operations training programme approval is that the programme be well defined and well suited to support the nature and specificity of the particular EDTO operation(s). Flight crew training programmes should include the content and duration of academic training, simulated flight demonstrations, line checks and currency requirements. Dispatcher training programmes should also address academic training considerations as well as the specific tools and methods used for EDTO flight preparation. Some operators may choose to combine the academic training sections for flight crews and dispatchers to promote a better understanding of how the respective functions support the EDTO programme.

Note.— EDTO operators should establish a system to track and identify the EDTO training status of their flight operations personnel to ensure that all personnel supporting the EDTO operations have completed the approved training programme and have satisfied any currency requirements.

3.9.2 EDTO flight operations academic training

The following academic curriculum elements should be addressed in an operator's EDTO training programme for flight operations personnel as applicable to the particular operation. Typically, an instructor-led CBT or combined course of up to one day is sufficient to address the basic training requirements but this may be extended if warranted for the particular circumstances. The curriculum elements are considered relevant and applicable for both flight crews and flight dispatch
personnel in a combined training programme but may have different degrees of emphasis in the flight preparation and en-route areas if separate programmes are tailored for each audience.

- a) Familiarity with ICAO EDTO Standards and the relevant standards in CAD 6 Part 1 and CAGM 6008 (IV)
- b) EDTO operational programme acceptance(s)
 - 1) EDTO fleet(s)
 - 2) EDTO area(s) of operations
 - 3) EDTO threshold(s), maximum diversion time(s) and speed(s)
- c) EDTO flight planning considerations
 - 1) EDTO area(s) of operations
 - 2) Alternate aerodromes for EDTO
 - 3) EDTO fuel reserves
 - 4) TLS considerations
 - 5) EDTO technical status and MEL considerations
 - 6) EDTO flight release and computer flight plan
- d) EDTO en-route considerations
 - 1) Standard operating procedures
 - 2) In-flight monitoring
 - 3) Diversion considerations
 - 4) Non-normal and contingency procedures
- e) Aeroplane performance data
- f) EDTO content in the basic operations manual.
- 3.9.3 EDTO flight operations practical training
- 3.9.3.1 The EDTO academic training considerations discussed in 3.9.2 provide a basic EDTO training foundation which should be supplemented by practical training as appropriate to the particular roles and responsibilities of flight operations personnel involved in the EDTO operation. For flight dispatch and operations control personnel, this should include training and practical exercises in the specific tools and methods used to support the operation (e.g., EDTO flight planning system). The demonstration of operational procedures related to flight preparation and adherence to any task-related checklists should also be included in the practical training.
- 3.9.3.2 For flight crew, practical EDTO training typically consists of a line-oriented flight training (LOFT) exercise conducted in a flight simulator device to demonstrate both normal and non-normal EDTO procedures. A typical EDTO LOFT scenario may include the elements listed below and is normally two to four hours in duration. Other en-route considerations specific to the particular operational

area such as long-range navigation and communication procedures should be addressed in addition to the EDTO specific training elements.

- a) Pre-flight briefing
- b) EDTO flight release
- c) Cockpit preparation
- d) En-route (normal)
 - 1) Entering EDTO sector
 - 2) En-route monitoring procedures
 - 3) FMS procedures (as applicable)
 - 4) Navigation and communication
- e) En-route (non-normal)
 - 1) Contingency procedures
 - 2) Selected non-normal conditions and checklists
 - 3) Diversion decision-making
 - 4) FMS procedures (as applicable)
 - 5) En-route diversion
- f) Post-flight procedures.
- 3.9.4 EDTO recurrent training
- 3.9.4.1 Recurrent training for EDTO flight operations personnel is typically conducted annually; however, the frequency and duration can vary from this general guideline, and specific currency requirements should be defined in each EDTO operator's approved training programme. A condensed or shortened refresher academics course is typically suitable for recurrent training purposes for personnel who have maintained an active role in supporting the EDTO operation, while the initial training course may be more appropriate for personnel who are no longer current as defined by the approved programme.
- 3.9.4.2 Practical recurrent training should consider student exposure to different potential operational situations as opposed to repeating the same scenarios in each training cycle. A recurrent EDTO LOFT should, for example, introduce different non-normal diversion conditions (engine failure, decompression, cargo fire, etc.) over time to provide a more meaningful training experience. Selection of the demonstrated contingencies may be recorded in each student's training records to ensure that different scenarios are introduced in each recurrent training session.

4 EDTO Maintenance And Reliability Requirements

4.1 General

- 4.1.1 Background
- 4.1.1.1 As explained in Paragraph 2.1.5, there are no additional EDTO airworthiness certification, maintenance procedures or maintenance programme requirements for aeroplanes with more than two engines. Although an operator may consider as good practice for its operations with aeroplanes with more than two engines some elements detailed in the following sections of this chapter, these are primarily intended for, and applicable to, EDTO operations of twin-engine aeroplanes only.
- 4.1.1.2 There are no additional EDTO certification, maintenance procedures or maintenance programme requirements for aeroplanes with more than two engines.
- 4.1.2 EDTO awareness
- 4.1.2.1 The CAMO is responsible to develop and control the EDTO maintenance programme for each type of aeroplane that is intended to apply for EDTO operational approval.
- 4.1.2.2 The EDTO maintenance programme should be used by all personnel involved in the continuing airworthiness and maintenance of the aeroplane. The CAMO should specify in the EDTO maintenance programme the standards, guidance and directions necessary to support the proposed EDTO operations.
- 4.1.3 Assessment
- 4.1.3.1 The AWI having jurisdiction over the operator will assess over an appropriate period of time (e.g., three months, or as found appropriate by the CAAM) the maintenance programme's suitability to support the proposed EDTO operations before the authorisation by specific approval for EDTO can be granted.

4.2 EDTO maintenance programme

- 4.2.1 General
- 4.2.1.1 In the context of this manual, the term "EDTO maintenance programme" means the maintenance related elements (maintenance tasks, organisation manuals, procedures, etc.) that must be implemented by the operators to support their EDTO operations. In this context, the aircraft maintenance programme for EDTO is one element of the operator's EDTO maintenance programme.

- 4.2.1.2 The operator's EDTO maintenance programme should contain the standards, guidance and directions necessary to support the intended EDTO operations. All personnel involved with EDTO should be made aware of the special nature of EDTO and have the knowledge, skills and ability to accomplish their specific areas of responsibility to the programme. The EDTO maintenance programme should identify personnel and areas where an EDTO qualification is required (see 4.7 and 4.17).
- 4.2.2 Elements of the EDTO maintenance programme
- 4.2.2.1 The typical elements of an operator's EDTO maintenance programme are identified below:
 - a) EDTO maintenance procedures manual (see 4.3)
 - b) EDTO CMP document (see 4.4)
 - c) Aeroplane maintenance programme for EDTO (see 4.5)
 - d) EDTO significant systems (see 4.6)
 - e) EDTO-related maintenance tasks/EDTO qualified staff (see 4.7)
 - f) Parts control programme (see 4.8)
 - g) EDTO service check (see 4.9)
 - h) Reliability programme (see 4.10)
 - i) Propulsion system monitoring (see 4.11)
 - j) Verification programme (see 4.12)
 - k) Dual maintenance limitations (see 4.13)
 - I) Engine condition monitoring programme (see 4.14)
 - m) Oil consumption monitoring programme (see 4.15)
 - n) APU in-flight start monitoring programme (see 4.16)
 - control of the aeroplane's EDTO status: EDTO release statement (see 4.17)
 - p) EDTO training (see 4.18).
- 4.2.2.2 The elements in 4.2.2.1 are further detailed in this chapter. These elements should be set up by operators as part of their demonstration of compliance against the maintenance criteria of applicable EDTO operational requirement. The EDTO maintenance programme should be established by the CAMO into their Continuing Airworthiness Management Exposition (CAME) or "stand alone" as a "EDTO Maintenance Programme.

- 4.2.2.3 The required elements of the EDTO maintenance programme should be reviewed in conjunction with the applicable aeroplane maintenance programme to ensure that they are adequate to meet the specific EDTO maintenance requirements as defined in the EDTO CMP document (see 2.2.2.3) for the AEC and any applicable instructions for continued airworthiness (ICA) that may affect EDTO requirements.
- 4.2.2.4 Maintenance personnel and other personnel involved should be made aware of the special nature of EDTO and have the knowledge, skills and ability to accomplish the requirements of the programme. Refer to Paragraphs 4.7 and 4.18 for further guidance on the need for EDTO qualification of relevant personnel.

4.3 EDTO maintenance procedures manual (EMPM)

- 4.3.1 Background
- 4.3.1.1 The operator should include EDTO information in the relevant part(s) of the basic maintenance procedures manual (MPM) or publish this information as a "stand alone" EDTO maintenance procedures manual (EMPM).

Note. – Basic Maintenance Procedures Manual (MPM) is referring to Continuing Airworthiness Management Exposition (CAME)

- 4.3.1.2 This EMPM or the EDTO content of the basic MPM defines EDTO maintenance practices supporting these operations as well as responsible persons and/or organisations. The manual should include, either directly or by reference to incorporated documents, the requirements described in Chapter 4.
- 4.3.2 Purpose
- 4.3.2.1 The purpose of the EMPM (or EDTO content of the basic MPM) is to provide involved personnel and EDTO authorised persons with a descriptive means aimed at ensuring safe and efficient EDTO operations.
- 4.3.2.2 Accordingly, all EDTO requirements, including supportive programme procedures, duties and responsibilities, should be identified as being related to EDTO. The EMPM (or the EDTO content of the basic MPM) should be submitted to the CAAM for review and acceptance with sufficient lead-time (lead-time as agreed on the pre-application/formal application phase) prior to the scheduled commencement of EDTO operations of the particular aeroplane type, model or variant (AEC).
- 4.3.2.3 The EMPM (or EDTO content of the basic MPM) should typically address the following topics:
 - a) general information on applicable EDTO rules and the operator's EDTO programme;

- b) scope of operator's EDTO authorisation (routes, fleet, diversion time, etc.);
- c) responsibilities (maintenance control centre, engineering, quality, training, planning and production, etc.);
- d) processes (daily review, reporting, dual maintenance limitations, etc.);
- e) EDTO maintenance procedures (aircraft release, EDTO service check, oil consumption monitoring, etc.); and
- f) EDTO maintenance training.
- 4.3.3 Revision control
- 4.3.3.1 Revisions to this EMPM (or the EDTO content of the basic MPM) will be reviewed and approved as applicable by the CAAM for changes to the programme.

4.4 EDTO configuration, maintenance and procedures (CMP) document

- 4.4.1 General
- 4.4.1.1 The EDTO CMP document defines the minimum standards for EDTO relative to any system improvements (configuration), maintenance tasks or operational procedures required for the EDTO operational approval. These standards are defined and approved by the State of Design of the aeroplane manufacturer in the frame of the EDTO certification of the aeroplane (see 2.2.2).
- 4.4.1.2 Operators should comply with the applicable requirements stated in this document for each aeroplane for which an EDTO authorisation is requested. Any deviation from these requirements should be approved by the CAAM.
- 4.4.1.3 The EDTO maintenance programme must include all tasks and related intervals as defined in the CMP, and the operational programme must include any procedures required by the CMP and be coordinated with the maintenance organisation, where applicable.

4.5 Aeroplane maintenance programme for EDTO

4.5.1 General

4.5.1.1 The aeroplane maintenance programme for EDTO should contain the standards, guidance and directions necessary to support the intended EDTO operations. However, it is acceptable if the Aeroplane Maintenance Programme for EDTO which consist of elements as in para 4.5.1.2, are combined with existing Aircraft Maintenance Programme (AMP) especially for operator which have a mixed aircraft (EDTO approved and non-EDTO approved). The operator is required to clearly indicate the required task related to the EDTO requirements as in this para, in the AMP.

- 4.5.1.2 The aeroplane maintenance programme for EDTO should consider:
 - all scheduled tasks applicable to both EDTO and non-EDTO operations, coming typically from the maintenance review board report/maintenance planning document (MRBR/MPD) or certification maintenance requirements (CMR) documents;
 - b) the additional specific task intervals coming typically from the EDTO CMP document; and
 - c) unscheduled maintenance affecting EDTO significant systems that must be managed according to the details provided in this chapter.
- 4.5.2 Applicability of the aeroplane maintenance programme for EDTO
- 4.5.2.1 The aeroplane should be maintained in accordance with the aeroplane maintenance programme for EDTO as long as it is operated on EDTO flights.
- 4.5.2.2 It is not mandatory to comply with the aeroplane maintenance programme for EDTO while the aeroplane is not operated on EDTO. However, compliance with this aeroplane maintenance programme for EDTO becomes mandatory as soon as the EDTO operations are resumed, which may entail execution of some tasks before EDTO operations can be resumed in order to restore the EDTO status of the aeroplane (see 4.5.3).
- 4.5.3 Applicability of the aeroplane maintenance programme for EDTO during mixed EDTO/non-EDTO operations
- 4.5.3.1 The applicability of the aeroplane maintenance programme for EDTO in case of mixed EDTO/non-EDTO operations should be as follows:
 - any tasks to be performed prior to an EDTO flight (e.g., tasks from the EDTO service check – see 4.9) are not required to be performed before the non-EDTO flights. Nevertheless, some tasks such as oil consumption monitoring may need to be continuously applied to maintain data continuity; and
 - b) the other EDTO maintenance tasks (i.e., those tasks required only for EDTO or those tasks with an interval specific to EDTO) must be performed, otherwise the aeroplane status should be downgraded to non-EDTO.
- 4.5.3.2 It is not mandatory to perform the above-mentioned EDTO maintenance tasks if the aeroplane is not operated on EDTO for an extended period of time. However, should the aeroplane be put back into EDTO operations, an assessment of the aeroplane maintenance status should be performed as follows:
 - any task to be performed prior to an EDTO flight (e.g., tasks from the EDTO service check – see 4.9) is to be performed prior to each EDTO flight of the aeroplane;

- b) any task required only for EDTO should be performed as per the applicable interval; and
- c) any task with an interval specific to EDTO must be performed as per the applicable "EDTO" interval to ensure it is not exceeded when EDTO operations are resumed, i.e., should the time since last execution of the concerned task be more than the EDTO interval then the task should be executed before the first EDTO flight.

4.6 EDTO significant systems

- 4.6.1 Definition
- 4.6.1.1 The EDTO significant systems are the systems or functions that help preclude and protect a diversion once the aeroplane is dispatched on an EDTO flight. The EDTO significant systems are usually defined as systems:
 - a) whose failure could adversely affect the safety of an EDTO flight (preclusion of a diversion); and
 - b) whose functioning is important to continued safe flight and landing during an EDTO diversion (protection of the diversion).
- 4.6.1.2 This list of EDTO significant systems is required mainly to allow the EDTO operator to track and report through the reliability programme the "EDTO relevant" events and to comply with the dual maintenance limitations criteria of the EDTO/ETOPS regulations.
- 4.6.1.3 Paragraph 2.2.3 defines the process to identify these EDTO significant systems and defines how the operator should manage its EDTO maintenance programme based on these EDTO significant systems. Paragraph 4.6.2 further details the maintenance activities which need EDTO significant systems.
- 4.6.2 Applicability to EDTO maintenance programme
- 4.6.2.1 The operator should identify a list of EDTO significant systems for each fleet of a given aeroplane type that will be operated on EDTO.
- 4.6.2.2 This list of EDTO significant systems is primarily defined by engineering judgment considering the systems' safety analyses and/or design requirements. It is normally provided by the aeroplane manufacturer as a recommendation, designed to help the EDTO operators establish their own list of EDTO significant systems.
- 4.6.2.3 An operator may add other equipment or systems that are considered important for EDTO operations (whether it is for safety or for economic reasons).
 Conversely, an operator may find a given section of the list provided by the manufacturer too conservative; according to its own experience or internal

policies, this operator may well slightly alleviate the content of the EDTO significant systems list provided by the manufacturer.

- 4.6.2.4 These EDTO significant systems impact the EDTO maintenance programme in the following areas:
 - a) maintenance activities for which it is necessary to adopt precautions to avoid multiple human errors. Typically, on such systems, the same mechanics should not do maintenance on two channels at the same time, unless a dual verification is performed (see 4.13). These activities typically include:
 - 1) the EDTO service check these systems must have positive corrective action or MEL coverage prior to EDTO dispatch;
 - dual maintenance the operator should consider dual maintenance activities prior to an EDTO flight;
 - verification the operator should have accomplished positive verification (ground verification or flight verification only if necessary) prior to an EDTO flight or MEL relief applied prior to dispatch; and
 - for those operators who identify EDTO tasks, the associated task cards will be flagged for these systems;
 - b) activities related to maintaining and monitoring EDTO reliability (aeroplane configuration for EDTO, failure rate trend monitoring):
 - 1) EDTO parts control the operator should track parts associated with these EDTO significant systems for reliability and reporting;
 - 2) EDTO reliability these systems would impact the event-based reliability programme for EDTO; and
 - EDTO significant system related occurrences for which the authorities want periodic reporting and analysis (event-oriented reporting of EDTO occurrences in service);
 - c) activities related to qualification of the EDTO maintenance staff:
 - 1) EDTO training and qualification the operator's EDTO training and qualification programme will be impacted by these systems.

4.7 EDTO-related maintenance tasks/EDTO qualified staff

- 4.7.1 An EDTO qualified staff is a person who has received the EDTO training (see 4.18). The operator identifies in its approved EMPM the requirements to be met for being rated as an EDTO qualified personnel. The EMPM should also identify the tasks that shall be accomplished by an EDTO qualified personnel.
- 4.7.2 As explained in Paragraph 2.2.2.5, the maintenance tasks related to EDTO are tasks impacting EDTO significant system(s) tasks or sub-tasks which are not

impacting any EDTO significant system(s), e.g., tasks supporting the overall verification process should not be considered as EDTO-related tasks.

- 4.7.3 The EDTO-related tasks may be scheduled tasks (from the aeroplane maintenance programme for EDTO) as well as unscheduled tasks performed using manuals such as aeroplane maintenance manuals, fault isolation manuals, and troubleshooting manuals.
- 4.7.4 The operator should select from the list of EDTO-related tasks those tasks which may be required to be performed by EDTO qualified personnel.
- 4.7.5 The selected EDTO-related tasks should be retained for their EDTO relevance and could include the installation, testing and/or servicing of airframe and propulsion systems identified in the EDTO significant systems list, such as:
 - a) removal/installation of engine or APU;
 - b) removal/installation of a component and involving work on fuel/oil/hydraulic/electric/pneumatic systems (VFG, fuel pump, oil system, gearbox, etc.) which could lead, in case of improper execution, to the loss of the concerned engine. This would typically mean tasks related to "Group 1" EDTO significant systems (see 2.2.3.3); and
 - c) servicing and which may be typically performed during EDTO pre-departure service check (e.g., engine oil, VFG, APU).
- 4.7.6 The filtering process for identification of these selected EDTO-related tasks should be implemented by the operator.
- 4.7.7 A typical flow chart for this filtering of the selected EDTO-related tasks is provided in Figure 4.7-1.



Figure 4.7-1. Filtering of the selected EDTO related tasks

4.8 Parts control programme

4.8.1 General

- 4.8.1.1 An EDTO operator should have a programme Identified in its EMPM that defines its management process of EDTO parts. This should include the ability to recognise and restrict EDTO based on part capability (90, 120, 180 minutes, etc.). This process should define how the maintenance organisation identifies EDTO part capability and the coordination within the operator to ensure the flight does not exceed the configuration capability (90, 120, 180 minutes, etc.). This definition should include parts pooling arrangements and any part borrowing capability.
- 4.8.1.2 EDTO restricted parts are, in most cases, derived from configuration improvements mandated by the CMP. These parts can be applicable to hardware and/or software part numbers (P/Ns), and/or be specific to a group of serialised parts (e.g., an identified batch of parts with a given part number). The engine manufacturer identifies the restricted EDTO parts in its associated illustrated parts catalogue/data (IPC/IPD). The operator should ensure the qualified personnel of the maintenance organisation must be able to recognise these restricted parts and be familiar with the process to ensure the aeroplane is dispatched in accordance with the limitations of the restricted parts.
- 4.8.1.3 Operators should have processes in place to ensure compliance with the new CMP requirement until the IPC/IPD has been revised. If the operator allows non-EDTO parts to be installed on the aeroplane, the EMPM should define the processes to restrict the aeroplane and ensure the EDTO-approved parts are installed prior to EDTO dispatch.

4.8.1.4 Agreements where part pooling arrangements have been made should include propulsion system standards, as applicable. Some operators borrow parts on short-term notice and should have similar processes to ensure the correct part is installed to support the EDTO requirement.

4.8.2 Identification of EDTO parts

- 4.8.2.1 The operator must develop a parts control programme to ensure that proper configuration is maintained for EDTO. These EDTO configuration standards for a given aeroplane model are detailed in the applicable EDTO CMP document. Indeed, per EDTO operational criteria, it is the responsibility of the operator to ensure that the aeroplane is configured in compliance with the applicable EDTO CMP document when dispatched on EDTO flights.
- 4.8.2.2 As explained in Chapter 2, 2.2.2.3, the EDTO CMP document is defined and approved by the State of Design in the frame of the EDTO certification of a given aeroplane model. The required EDTO configuration is usually defined through service bulletin or modification numbers in the EDTO CMP document.
- 4.8.2.3 Therefore, an EDTO parts list should be developed in order to identify and to manage the EDTO components. This EDTO parts list, which may be provided by the aeroplane manufacturer, should reflect the configuration requirements of the EDTO CMP document. For each CMP configuration item, the EDTO parts list should identify the part numbers (P/Ns) that are "not approved for EDTO" and those that are "approved (or mandatory) for EDTO". The pre-modification P/Ns are those with EDTO restriction (e.g., "not approved for EDTO" P/Ns), while the post-modification P/Ns are the P/Ns "approved (or mandatory) for EDTO".
- 4.8.2.4 The EDTO status of a given part may be identified on its tag, and this information may also be included in the illustrated parts catalogue. In case of doubt about EDTO status of a specific part, the EDTO CMP document should be used as the reference for assessment of the required EDTO configuration.
- 4.8.2.5 The EMPM should detail the process in place to ensure the proper identification of the EDTO status of the parts. This process should continuously ensure that any new EDTO configuration restrictions (e.g., coming from revised CMP standards) are properly identified.
- 4.8.3 EDTO parts provisioning
- 4.8.3.1 The EDTO requirements have an indirect impact on parts provisioning policy. These requirements may be split in two areas, standard and quantity of parts to be provisioned:
 - a) Standard of parts to be provisioned: This aspect is discussed in 4.8.2.

- b) Quantity of parts to be provisioned: There is no required minimum quantity of spare parts in the EDTO rules; however, the more restrictive MEL may have an impact on the operator's policy for spare provisioning. The assessment of spare requirement will have to take into account the different dispatch allowance between EDTO and non-EDTO, as well as the level of EDTO (e.g., 120 or 180 minutes) and area of operations. Spare requirement may be different if the return leg to main base can be done along a non-EDTO route (or with a lower diversion time). Dispatch reliability may also be used as a criterion for the assessment of spare parts requirements, as for non-EDTO operations.
- 4.8.3.2 The operator should ensure that the maintenance organisation engaged to support the EDTO operation is competence to perform a functions as applicable in para 4.8

4.9 EDTO service check

- 4.9.1 General
- 4.9.1.1 EDTO operators will ensure that an EDTO service check is performed prior to each EDTO flight by appropriately qualified personnel from approved maintenance organisation in order to confirm adequate operation of significant systems prior to EDTO dispatch.
- 4.9.1.2 The systems to be checked are derived from the operator list of EDTO significant systems; indeed, the list of relevant systems depends on the design and technology of the aircraft. Furthermore, the EDTO CMP document may also not contain the service check tasks, as these tasks may not be identical for all operators and may depend on the route structure (network) and maintenance organisation and processes in place (e.g., cockpit-based checks at transit).
- 4.9.1.3 The check is intended to ensure there are no existing EDTO log book items that are applicable to EDTO significant systems remaining prior to EDTO dispatch. The two objectives are to prevent system failures during the next EDTO flight and to correct system failures (before the next EDTO flight) that are not allowed by the MEL.
- 4.9.2 Typical content of the EDTO service check
- 4.9.2.1 At a minimum, the EDTO service check should contain:
 - a) verification that all EDTO significant systems defects have been resolved or have sufficient MEL coverage;
 - b) review of the aeroplane technical log for EDTO significant system items and servicing entries;

- c) performance of an interior and exterior inspection. The exterior inspection is intended to be a general visual inspection (GVI) from ground level;
- verification of engine oil level to include the APU if it is required for EDTO; and
- e) assessment of the EDTO status of the aeroplane and related EDTO maintenance release (see 4.17).
- 4.9.2.2 The intent of item a) of 4.9.2.1 (EDTO significant systems), is not to perform a test on each item but to review the technical log and aeroplane messaging system for discrepancies in this area. Maintenance level messages are not typically reviewed or evaluated during this check as those soft faults are designed for planning during higher level maintenance checks.
- 4.9.2.3 Oil consumption for each propulsion system should be verified as acceptable prior to EDTO dispatch and that it meets the mission requirements of the EDTO flight. For operations where the APU must be running for the entire flight (e.g., MEL with generator inoperative), the APU oil consumption rate should support the operation. Some aeroplanes have only three generator sources and are at the minimum requirement for EDTO at dispatch. This requires the APU to be running during the EDTO portion of the flight or in some cases allow the APU to be available during EDTO. The CMP defines the specific operational requirements.
- 4.9.2.4 The EMPM should identify the EDTO qualification requirements for completing the EDTO service check. These qualifications are defined in the training section of the EMPM and should define the areas of the check which require EDTO qualification. The EMPM should also define how the check is signed for and how the flight crew determine if the check has been completed. The EDTO service check is required to be completed only prior to an EDTO flight, so the EMPM should define how the non-EDTO flights are to be managed. If the EDTO service check is not completed on these flights, the oil consumption and engine condition monitoring (ECM) data collection should continue. This check is not typically found in the scheduled maintenance programmes (e.g., MRBR/MPD) as these are driven by the structured MSG-3 analysis. This check, however, does need to be managed through the scheduled maintenance process of tracking and reporting.
- 4.9.3 EDTO service check and line check policy
- 4.9.3.1 The approach of single EDTO pre-departure service checks may not be compatible with the flight programme (e.g., the mission could be a sequence of EDTO/non-EDTO legs).
- 4.9.3.2 The EDTO service check items in the existing line checks are allowed but distinct identification for the EDTO tasks should be marked on the service check

task card. The qualification required for signature should also be indicated to ensure the person accomplishing the task understands its limitations.

4.9.3.3 In this case, the single EDTO pre-departure service check is replaced by an EDTO service check policy as illustrated in Figure 4.9-1.



Figure 4.9-1.EDTO service check policy

- 4.9.4 Execution of EDTO service check
- 4.9.4.1 The EDTO service check should be accomplished or verified by EDTO qualified personnel (see 4.7).
- 4.9.5 Physical check versus cockpit check
- 4.9.5.1 The accuracy of indicating systems and reliability of aeroplane systems and engines, combined with the low level of oil consumption of today's engines, make it possible to increase the number of legs between physical checks of the system or component. In this case, flight deck verification is acceptable. In addition, verification from the flight deck minimises the risk of human error during physical check.

4.10 Reliability programme

- 4.10.1 Purpose
- 4.10.1.1 The EDTO operator should create an event-based EDTO reliability programme based on its EDTO significant systems list. This programme would enhance any existing reliability programme be it a statistical-based programme or a continuing analysis and surveillance (CASS) programme. The programme should be designed with the objective to allow early identification and prevention of EDTO-related significant events and ensure that EDTO reliability

is maintained. The EDTO reliability report/data tracked by the EDTO operator needs to be submitted to the CAAM in every 6 months or as and when requested by the CAAM.

- 4.10.1.2 The programme should be event-oriented and incorporate reporting procedures for EDTO significant events and trends detrimental to EDTO flights. This information should be readily available for use by the operator and the CAAM to help determine that the reliability level is adequate, and to assess the operator's competence and capability to safely perform EDTO. An EDTO reporting programme should be established which ensures that the AWI is notified, typically monthly, on the previous month's activities or more often if adverse trends reportable through this programme are identified.
- 4.10.1.3 Air operators who contract any part of their maintenance control system and/or reliability programmes that support their EDTO authorisation to any other organisation remain responsible for ensuring that all elements of this programme are addressed and continue to meet the applicable requirements. The EMPM should identify the processes and procedures of this agreement and identify the air operator's accountable staff.
- 4.10.2 Impact on EDTO diversion time capability
- 4.10.2.1 Air operator procedures to manage the EDTO diversion time capability of a given aeroplane or fleet of aeroplanes should be established and implemented. These procedures should provide the continuing airworthiness manager with the authority to limit, as may be deemed necessary, this EDTO diversion time capability of the applicable aeroplane or to reinstate it once adequate corrective actions have been identified and implemented.
- 4.10.2.2 A reduction of this EDTO diversion time capability may be needed if:
 - a) an unresolved significant event is identified on any flight, including non-EDTO flights, of the operator's EDTO approved aeroplane type affected; or
 - b) an adverse trend is identified through the reliability programme; or
 - c) the approved EDTO capability of the aeroplane, granted by the State of Design, has been reduced.
- 4.10.3 APU in-flight start monitoring
- 4.10.3.1 The CAAM requires the EDTO operator to perform periodic high altitude and cold soak APU in-flight starts, typically when the APU is a back-up source for electrical or pneumatic power.

Note.— This requirement typically applies to twin-engine aeroplanes only as aeroplanes with more than two engines usually have more redundant power sources provided by the higher number of installed engines.

- 4.10.3.2 The capability of the APU to perform cold soak starts throughout the flight envelope is usually demonstrated by the manufacturer during the EDTO/ETOPS certification of the aeroplane.
- 4.10.3.3 Therefore, the purpose of the APU in-flight start monitoring programme by the operator is primarily to demonstrate and/or confirm the continued ability of the APU to perform high altitude cold soak starts and to ensure that the maintenance programme provides adequate support for that intent.
- 4.10.3.4 The APU in-flight start monitoring programme should demonstrate that a 95 % success rate is achieved for high altitude cold soak starts.

Note.— In this context, a successful start is usually defined as being one where the APU starts within three attempts. The maximum number of start attempts should be within the limits specified in the applicable aeroplane or APU documentation.

4.10.3.5 The APU in-flight starts should be performed within the concerned EDTO fleet of the operator, as well as the non-EDTO fleet, if any, if these APUs are configured and maintained in accordance with the EDTO CMP requirements.

Note.— Refer to Paragraph 4.16 for additional guidance on an APU in-flight start monitoring programme.

- 4.10.4 Propulsion system reliability monitoring
- 4.10.4.1 Where reliability data indicate that the applicable in-flight shutdown (IFSD) rate of the propulsion system is no longer being met, the AWI should be notified of the corrective measures taken. If the reliability data show a continual degradation below the applicable target reliability level, a substantiated plan for resolution should be submitted and consideration for a reduction in EDTO capability may be warranted, as explained in Paragraph 4.11.
- 4.10.4.2 The IFSD rate of the operator's fleet may be impacted significantly if the fleet is small in count (typically fewer than 15 aircraft). In this case, the IFSD rate computation will mainly be used as a trending mechanism. Exceedance of the target rate should therefore not be used as the only reason to suspend EDTO operation. Indeed, when the number of engine hours over a year is not sufficient to be statistically representative, the reliability of EDTO operation should be reviewed on an individual event basis. An event-orientated analysis of each inservice event should therefore be performed. This analysis shall identify the root cause of the event and define the related corrective actions (if any).
- 4.10.5 Tracking and reporting of EDTO relevant events
- 4.10.5.1 The following events should be included in the reporting programme:
 - a) in-flight shutdowns or flameouts;
 - b) diversion or turn-back;

- c) uncommanded power changes or surges;
- d) inability to control the engine or obtain desired power; and
- e) significant events or adverse trends with EDTO significant systems.
- 4.10.5.2 The report should also identify the following:
 - a) aeroplane identification;
 - b) engine identification (make and serial number);
 - c) total time, cycles and time since last shop visit;
 - d) for systems, time since overhaul or last inspection of the defective unit;
 - e) phase of flight;
 - f) corrective action; and
 - g) resulting action by the flight crew (divert, return, continue, etc.).
- 4.10.6 Assessment of EDTO reliability indicators
- 4.10.6.1 Where statistical assessment alone may not be applicable (i.e., when the fleet size is small), the air operator's performance should be reviewed on a case-by-case basis.
- 4.10.6.2 The review may include such items as actual data populating the air operator's reliability programme and this being compared, where possible, to worldwide fleet data of the concerned AEC and related EDTO maintenance significant systems, as well as air operator events, including IFSDs and loss of thrust, with the results of investigation into the cause(s) of the events.
- 4.10.6.3 This recommendation to focus on the root-cause of the events and the corrective action(s) taken, rather than on the reliability figures alone, may actually apply to any fleet.
- 4.10.6.4 Indeed, regardless of the reliability level, it is possible that a particular event may also warrant corrective action implementation even though the applicable reliability indicators are not being exceeded. It also implies that any EDTO relevant event in the operator's fleet (i.e., EDTO and non-EDTO) should be reviewed.
- 4.10.6.5 Analysis of propulsion reliability is only one part of the whole assessment that should be performed in the frame of decision process to grant, maintain or reduce the EDTO authorisation.

4.11 Propulsion system monitoring

4.11.1 Background

- 4.11.1.1 The engine reliability is tracked at two levels:
 - a) by the manufacturers and the State of Design as part of the continued airworthiness surveillance of a given AEC (worldwide fleet). The goal of this tracking is to ensure that the EDTO capability of a given AEC is demonstrated and maintained (see 1.5);
 - b) by the EDTO operator for the fleet (of this operator) of a given AEC. The goal of this tracking is to provide an indicator, but not the only indicator, of the reliability of the concerned operators' EDTO operations (see 1.6).

Note. – The engine reliability data tracked by the EDTO operator needs to be submitted to the CAAM on a monthly basis.

- 4.11.2 In-flight shutdown (IFSD) rate
- 4.11.2.1 The IFSD rate is a statistical indicator commonly used to assess the reliability of the concerned engine model versus the target rate.
- 4.11.2.2 The IFSD rate is a reliability figure calculated by dividing the chargeable number of in-flight shutdowns by the total engine operating hours accrued during the same period. The IFSD rate is usually computed over a 12-month rolling average basis for the concerned AEC; it is, therefore, the count of IFSD(s) over the total engine hours cumulated during the last 12 months.
- 4.11.2.3 The IFSD rate may be computed for the worldwide fleet of the concerned AEC; this is the rate monitored by the State of Design to assess the EDTO capability of a given AEC.
- 4.11.2.4 The IFSD rate should also be computed by the operator for its fleet of concerned AEC. The CAAM considers this rate as part of the continued reliability assessment of the concerned operators' EDTO operations.
- 4.11.2.5 The IFSD rate shall not exceed the established rate as follows:

| Number of Engines | Engine Hours EDTO | EDTO Approval |
|----------------------|-------------------|--|
| 2 | 0.05/1000 | Up to and including 120 minutes |
| 2 | 0.03/1000 | Beyond 120 minutes up to and including 180 minutes and 207 minutes in North Pacific |
| 2 | 0.02/1000 | Greater than 180 minutes (Except for 207 minutes in North Pacific) |

- 4.11.2.6 The applicable IFSD alert levels are typically defined for a given maximum diversion time (e.g., 120, 180 minutes and beyond 180 minutes), the alert levels should be established and agreed to by the CAAM.
- 4.11.2.7 These IFSD levels for the operator may also consider the size of the fleet as this may have a great impact on the operator's IFSD rate; indeed, due to a smaller number of cumulated hours during 12 months, the impact of one engine failure on an operator's IFSD rate may be significantly higher than on the worldwide fleet rate.
- 4.11.3 IFSD definition
- 4.11.3.1 The definition of an IFSD for EDTO is when an engine ceases to function (when the aeroplane is airborne) and is shutdown, whether self-induced, flight-crew initiated or caused by an external influence.
- 4.11.3.2 Typical examples of engine in-flight shutdown causes retained for the computation of the IFSD rate are: flameout, internal failure, flight-crew initiated shutdown, foreign object ingestion, icing, inability to obtain or control desired thrust or power, and cycling of the start control, however briefly, even if the engine operates normally for the remainder of the flight.
- 4.11.3.3 It should also be noted that the following events are normally not counted as IFSD:
 - a) engine failures before take-off decision speed or after touchdown;
 - b) airborne cessation of the functioning of an engine when immediately followed by an automatic engine relight; and
 - c) engine does not achieve desired thrust or power but is not shut down.
- 4.11.3.4 These events are not counted as IFSD but should still be reported to the CAAM in the frame of continued airworthiness for EDTO.
- 4.11.4 IFSD rate monitoring
- 4.11.4.1 The assessment of propulsion systems' reliability for the EDTO fleet should be made available to the AWI (with supporting data) in accordance with the approved EDTO maintenance control system.
- 4.11.4.2 Where the combined EDTO fleet is part of a larger fleet of the same AEC, data from the air operator's total fleet may be acceptable. The reporting requirements of Paragraph 4.10 should still be observed for the EDTO fleet.
- 4.11.4.3 Any adverse trend requires an immediate evaluation to be done. The CAAM needs to be advised of the result of the evaluation. The evaluation may result in corrective action and/or operational restrictions being applied.

- 4.11.4.4 The operator should investigate any indication of high IFSD rate.
- 4.11.4.5 However, as explained in Paragraph 4.10.3, in the case of a smaller fleet, the high IFSD rate may be due to the limited number of engine operating hours used for the rate calculation. This can cause an IFSD rate being well above the target rate because of a single event. The underlying causes for such a jump in the rate should be considered by the AWI in assessing the need for corrective actions.
- 4.11.4.6 Conversely, implementation of corrective actions may be warranted further to a series of IFSDs occurring in a larger fleet, typically in case of common cause events, even if these events have not led to an exceedance of the applicable IFSD alert level.

4.12 Verification programme

- 4.12.1 General
- 4.12.1.1 The operator should have a verification programme that ensures positive corrective action on all-engine in-flight shut down occurrences and EDTO significant system failures, or that MEL relief is applied prior to an EDTO flight. The approved ground verification tasks should be defined in the EMPM and should promote positive ground verification prior to EDTO dispatch. These may include, but are not limited to, the aeroplane maintenance manual, fault isolation manual, troubleshooting manual, scheduled maintenance task, MPD, operator approved procedures or any other approved instruction manual.
- 4.12.1.2 If an in-flight verification programme is approved, it should be defined in the EMPM. It is acceptable to use EDTO or non-EDTO flights for this verification process. The verification should be completed prior to reaching the EEP.
- 4.12.1.3 The operator should establish means to assure proper accomplishment of these verification actions. A clear description of who should initiate verification actions and the section or group responsible for the determination of what action is necessary should be identified in the programme.
- 4.12.2 Purpose and content
- 4.12.2.1 The purpose of this verification programme is to ensure the effectiveness of maintenance actions taken on EDTO significant systems.
- 4.12.2.2 Troubleshooting procedures and maintenance tasks published by the aeroplane or engine manufacturers are basically considered as adequate verification action. Nevertheless, the operator may be required to develop further verification action based on its own in-service experience.
- 4.12.2.3 The EMPM should include the list of EDTO significant systems or conditions (dual maintenance action, heavy maintenance, etc.), if any, requiring specific

verification actions, considering the operator's own in-service experience and any applicable national regulations or guidance.

- 4.12.3 Typical verification actions
- 4.12.3.1 These specific verification actions may typically be required in case of:
 - a) simultaneous maintenance action/tasks on parallel EDTO significant systems. Typical additional verification action in this case would be an inflight verification of relevant parameters prior to entry into the EDTO sector (e.g., during the first 60 minutes of the flight) or during a non-EDTO flight.
 - b) Another acceptable verification action could be that the tasks are performed by different qualified personnel on each EDTO significant system or performed by one qualified personnel directly supervised during the task application by another EDTO qualified technician. In both cases, the required ground verification test (and/or in-flight verification test, if needed) is performed by a qualified personnel.
 - c) maintenance action on items that cannot be fully verified on ground. An example of a condition that would require an in-flight verification is the replacement of an APU component that could affect the APU's ability to start at the EDTO cruise altitude after cold soak.
 - d) review of the relevant operator's EDTO maintenance experience indicating that the ground verification actions published in the aeroplane maintenance manual or troubleshooting manual may not be fully effective for EDTO. Note that unless otherwise demonstrated by this review, it should be considered that the troubleshooting procedures and maintenance tasks published by the manufacturers are verification actions fully adequate and valid for EDTO.
- 4.12.4 Verification actions after complex maintenance check
- 4.12.4.1 Following multiple maintenance actions/tasks performed during a heavy check, it may be considered that the first flight after such a complex maintenance check cannot be an EDTO flight. In this case, this non-EDTO flight (which may be a commercial flight) may therefore be considered as the relevant verification action.
- 4.12.4.2 Nevertheless, it should be noted that the proper accomplishment of appropriate verification actions after the heavy check aims at ensuring that the aeroplane is airworthy. Therefore, it is also acceptable to consider that an in-flight verification for EDTO may not be needed. The operator should make this decision on the need for a dedicated in-flight verification for EDTO and accordingly seek authorisation from the CAAM.
- 4.12.4.3 Concerning the particular case of single-engine replacement, it is not required to perform a verification flight after such maintenance action. The

instructions and verification actions provided in the aeroplane or engine maintenance manuals should therefore apply. Nevertheless, as the engine replacement involves the deactivation/reactivation of several EDTO significant systems (electrical generators, hydraulic pumps, bleed air system, engine oil system, etc.), an operator may choose to call for an in-flight verification. The concerned parameters to be monitored should obviously include any relevant parameters indicating a proper engine functioning (fuel flow, EGT, etc.) but also be related to proper functioning of the other impacted EDTO significant systems. Depending on applicable policy, such verification may be performed before entering the EDTO sector of an EDTO flight.

- 4.12.4.4 The operator should include the applicable procedure for such a case in the EMPM, based on its own in-service experience and any applicable requirements or guidance imposed by the CAAM.
- 4.12.4.5 Since the verification flight involves the integration between CAMO, Flight Operations of the organisation and maintenance organisation, the CAMO should ensure that all affected departments and personnel understand their roles in supporting the EDTO operations as reflected in para 3.6.2.4 of this CAGM

4.13 Dual maintenance limitations

- 4.13.1 Background
- 4.13.1.1 EDTO operators should have an approved programme to ensure maintenance performed on the same element of identical but separate EDTO significant systems during the same routine or non-routine maintenance visit prevents duplication of a human error. Dual maintenance is commonly defined as any maintenance performed that could induce the same fault into redundant components of the same EDTO significant system or function.
- 4.13.1.2 The purpose is to minimise the risk of errors while performing the maintenance task on these parallel or identical EDTO significant systems. Indeed, such maintenance error(s) could lead to dual system failure which could potentially cause aeroplane diversions in degraded configurations.
- 4.13.2 Applicability and general recommendations
- 4.13.2.1 The "same" EDTO significant system is typically one that is in the same ATA reference and would reduce the redundancy level designed into the twin-engine aeroplane to support EDTO. An example would be maintenance on the left-engine-driven electrical generator and the right-engine-driven electrical generator.
- 4.13.2.2 Simultaneous maintenance on different engine driven components on both engines should also be considered as dual maintenance due to the possibility

of affecting both propulsion system oil or fuel supplies. An example of this would be maintenance performed on the number one engine-driven electrical generator and the number two engine hydraulic pump. Each are in separate ATA references, but a similar human error could cause a dual engine failure.

- 4.13.2.3 In this context, the list of EDTO significant systems may identify the systems that are identical (see 4.13.2.9) and those that are similar (see 4.13.2.10). The "similar" category may be further split in two sub-categories "substantially similar" and "redundant", as indicated in Paragraph 4.13.2.10.
- 4.13.2.4 Any maintenance actions on EDTO significant systems which are not falling in these categories are therefore not subject to dual maintenance limitations.
- 4.13.2.5 Some (but not necessarily all) of the maintenance actions on EDTO significant systems which are in these categories may therefore be subject to dual maintenance limitations.
- 4.13.2.6 The determination can be made by evaluating common mechanical tasks that historically have created this situation of dual system fault or loss, or through an evaluation of the maintenance tasks and aeroplane level of consequences of improper maintenance. Consideration should be given to the difficulty of the task, accessibility to the component, and testing procedures.
- 4.13.2.7 The selected tasks are commonly those that are mechanical in nature and are managing fluid or pneumatics (fuel, oil, air, etc.) that may be used for control purposes. In case of improper maintenance, these components may develop some leakage after a period of time in the next flight. Some examples are engine-driven component installation, fuel couplings, pneumatic couplings and control pressure lines to actuators or valves.
- 4.13.2.8 Tasks that should not be selected are typically maintenance tasks on electronic systems or software which are using internal monitoring and fault detection. The risk of inducing twice the same non-detected human error is minimal due to the design of the system and software, especially those systems which include an operational and/or functional verification check following maintenance action.
- 4.13.2.9 Identical EDTO significant systems
- 4.13.2.9.1 Two or more systems may be identified as "identical" EDTO significant systems when they are the same (fit, form and function). Examples of "identical" EDTO significant systems are the left engine-driven electrical generator and the right engine-driven electrical generator.
- 4.13.2.10 Similar EDTO significant systems
- 4.13.2.10.1 Two or more systems may be identified as "similar" when they are either:

- a) "substantially similar" EDTO significant systems: These are enginedriven components mounted on both engines with similar attach procedures. Examples of "substantially similar" EDTO significant systems are the electrical generator mounted on engine one and the engine-driven hydraulic pump mounted on engine two. Improper installation of these components could result in oil loss on both engines; and
- b) "redundant" EDTO significant systems: These are systems providing the same redundant function. Examples of "redundant" EDTO significant systems are the engine-driven electrical generator and the APU-driven electrical generator. Improper maintenance could lead to multiple loss of EDTO significant systems and/or loss of redundancy in the related EDTO significant function (e.g., dual loss of electrical power sources). Even though the tasks may not be exactly the same, the potential impact of a maintenance error on the level of redundancy should be considered to retain (or not) the related tasks as dual maintenance action. This could typically be the case of tasks involving complex removal/installation procedures where possibilities exist to induce a fault that could lead to the same consequence (i.e., loss of concerned system or function) in both systems.
- 4.13.3 Compliance
- 4.13.3.1 An acceptable programme of dual maintenance limitations to prevent loss of EDTO significant system redundancy should be defined in the operator's EMPM. This programme should take into account the aeroplane design architecture and systems reliability, the operator's experience and any applicable national regulations or guidance.
- 4.13.3.2 There are different ways to comply with this dual maintenance limitation requirement. It may include (but is not limited to) the following processes:
 - a) the execution of tasks performed on identical or similar EDTO significant systems is staggered;
 - b) the task is performed by separate EDTO-qualified technicians;
 - c) the maintenance action on each of the elements in the EDTO significant system is performed by the same qualified personnel under the direct supervision of a second EDTO qualified individual; and
 - d) the operator verifies the corrective action to those EDTO significant systems as per applicable verification actions.
- 4.13.3.3 The servicing of fluids and gases is not considered maintenance; however, this should be conducted properly as defined in the manufacturer procedures manual. One qualified personnel serving two separate, but similar systems is not considered dual maintenance, but the servicing instructions should be

followed to ensure EDTO reliability standards are maintained. Operators should emphasise this in their EDTO training programme.

4.13.3.4 EDTO operators should ensure that the dual maintenance limitations appropriately performed by qualified personnel from approved maintenance organisation in accordance with this para 4.13 based on operator's EMPM.

4.14 Engine condition monitoring programme

- 4.14.1 The EDTO operator should implement an engine condition monitoring programme to detect deterioration at an early stage to allow for corrective action before safe operation is affected, and to ensure internal limit margins (e.g., rotor speeds, exhaust gas temperatures) are maintained to support single-engine diversion scenarios. Engine margins preserved through this programme should also account for the effects of additional engine loading demands (e.g., anti-icing, electrical) which may be required during the single-engine flight phase associated with the diversion.
- 4.14.2 This programme should describe the parameters to be monitored, the method of data collection, and the corrective action process. The programme should reflect the type certificate holder's instructions and the industry practice.
- 4.14.3 At a minimum, the programme should record these parameters consistently during a benign part of flight, typically at cruise, and record them electronically or manually. These parameters can be defined by the engine manufacturers but could typically include N1, N2, N3, FF, EGT, oil pressure and oil temperature.
- 4.14.4 Monitoring should be on a continual basis. The information should be collected and trended in a timeline to ensure these parameters are maintained in an acceptable interval. If an electronic reporting and transmitting system is being used, a back-up method should be created to take the place of any automated system that is failed for greater than this interval.
- 4.14.5 Operators may choose to use engine manufacturer support for this programme. These programmes offered by the manufacturer provide even further enhanced information and protection and are acceptable to meet this requirement. This information should be sent to the operator in a timely manner (interval to be agreed by the authority) and include procedures to ensure that the information is continuous regardless of day or time. Most engine manufacturer data exceed the minimum requirement for this programme and would enhance the operator internal procedures.

4.15 Oil consumption monitoring programme

4.15.1 Purpose

4.15.1.1 The oil consumption monitoring programme is required to allow operators to detect unexpected oil consumption that could be the result of an oil leak or

unforeseen engine wear which can impact the EDTO dispatch capability of the aircraft.

- 4.15.2 Content
- 4.15.2.1 The maximum oil consumption rate is not specified for EDTO (i.e., it can be the same as for non-EDTO operations) and what procedure should be applied to compute the consumption rate and detect unusual oil uplift. The oil consumption programme should reflect the type certificate holder's recommendations and be sensitive to oil consumption trends as well as unusual oil uplifts.
- 4.15.2.2 The dispatch procedures for EDTO segments are to take into account peak consumption and current running average consumption, including consumption on the immediately preceding segments. If oil analysis is meaningful to this make and model, it should be included in the programme. If the APU is required for EDTO operation, it should be included in the oil consumption programme.
- 4.15.2.3 This oil consumption monitoring programme for EDTO should define a baseline consumption rate (normal usage) and detect oil consumption based on the previous flight results. This oil consumption or loss must not exceed the manufacturer's maximum allowable usage rate and is defined in the aeroplane maintenance manual.
- 4.15.2.4 An evaluation must be made prior to the next EDTO flight to ensure the consumption supports the mission requirements. The programme should ensure there were no sudden increases in consumption/loss and, if there were, to initiate proper corrective action.

4.16 APU in-flight start monitoring programme

- 4.16.1 Purpose
- 4.16.1.1 The purpose of the APU in-flight start monitoring programme is to demonstrate and/or confirm that the APU is able to start at altitude while in flight. This inflight verification is necessary as the capability of the APU to start at altitude can usually not be demonstrated while the aeroplane is on ground.
- 4.16.1.2 The requirement for APU in-flight start monitoring in the frame of EDTO is an operational requirement.
- 4.16.1.3 The EDTO CMP document contains the configuration and maintenance items necessary to meet the reliability objectives for the APU (run reliability and inflight start reliability), as defined by the certification requirements. As the continued monitoring of the APU in-flight start capability is an operational requirement, it is usually not reflected in the EDTO CMP document or other aircraft/engine maintenance document (e.g., MRBR or MPD). It allows the

operator to adapt, as necessary, its programme for APU in-flight start monitoring to reflect its own utilisation of the APU.

- 4.16.1.4 Since the introduction of the initial ETOPS rules, it is usually a requirement for certification that the aeroplane manufacturers demonstrate the in-flight start reliability of the APU when the following two conditions are met:
 - a) the in-flight start of the APU and use of the APU electrical and/or bleed power source(s) is required in case of in-flight failure of another power source(s) within the EDTO sector; and
 - b) the continued operation of the APU is not required in the EDTO sector when the aeroplane is dispatched in fully operational electrical or bleed configuration (no MEL/MMEL).
- 4.16.1.5 This in-flight start capability demonstrated by the manufacturers in the frame of the certification activities should be maintained and monitored by the EDTO operators. This is why the operator should develop a programme to monitor the APU cold soak in-flight start and run reliability. Furthermore, tracking and reporting of APU run reliability (including failed in-flight starts) should also be implemented when the APU is classified as an EDTO significant system.
- 4.16.2 Content
- 4.16.2.1 The operator is expected to perform these initial in-flight starts on a routine basis typically for the first 6 to 12 months of EDTO operations. The CAAM may still ask the operator to perform high-altitude/cold soak start of the APU on a regular basis even after the first months of operations. The operator may adjust the sampling intervals according to system performance and fleet maturity. In particular, experience has shown that oversampling has the potential to actually degrade the APU in-flight start capability, therefore care should be taken in establishing appropriate sampling intervals.
- 4.16.2.2 In other words, it is expected that the initial programme may be alleviated, and the interval increased, further to a review of relevant maintenance records performed by the CAAM when satisfactory in-service experience has been accumulated. Note that the interval should also take into account the normal utilisation of the APU (e.g., on ground). An operator having a low utilisation of the APU may have to check it more frequently.
- 4.16.2.3 The typical interval to initially check the APU is once per month per aircraft. As noted above, this interval may be increased, typically to once every three months per aircraft. Some highly experienced EDTO operators have increased this interval up to once or twice per year per aircraft.
- 4.16.2.4 Therefore, the operator should propose an APU in-flight start/run programme that is acceptable to the CAAM, considering its own experience and any applicable requirements or guidance published by the CAAM. The proposed

programme should include periodic sampling of each aeroplane's APU in-flight start capabilities, i.e., the operator should ensure that each aeroplane's APU of the operator's EDTO fleet is periodically checked rather than repeatedly sampling the same APUs.

- 4.16.2.5 The APU in-flight start tests do not need to be performed systematically during EDTO flights. The start attempts should also not be performed systematically at the top of the aeroplanes and APU operating envelope. However, the duration of the cold soak as well as the altitude of the test should be representative of typical EDTO operations. In other words, the objective of the programme should be to collect data points spread between a range of typical cruise duration and altitudes.
- 4.16.2.6 In addition to the in-flight starts performed on a routine basis, as described in the Paragraph 4.12, it may be recommended to perform a high-altitude cold soak start test after maintenance action(s) that may impact the start capability of the APU (APU change, replacement of electronic control box, fuel control unit, igniters, etc.).
- 4.16.3 APU in-flight start reliability objective
- 4.16.3.1 A 95 % success rate of APU high altitude re-light is expected to be demonstrated.
- 4.16.3.2 An APU in-flight start attempt should be classified as "successful" when the APU is started within three start attempts.
- 4.16.3.3 This 95 % criterion serves to monitor the APU in-flight start capability once the EDTO operation has begun. In other words, it is not required to demonstrate the 95 % success rate prior to starting EDTO. Accordingly, this analysis/evaluation of in-flight start capability should be done only once a significant set of data has been collected for comparison versus the 95 % figure. The number of high-altitude starts required to demonstrate a 95 % success rate is a minimum of 20 attempts.
- 4.16.3.4 It is the concerned EDTO fleet of the operator that must be monitored. The non-EDTO fleet, if any, may also be included in the programme but only if these APUs are also configured and maintained in accordance with the EDTO CMP requirements.
- 4.16.4 Procedure
- 4.16.4.1 The APU in-flight start test is not a maintenance task. The primary role of the maintenance and engineering organisation is to actually:
 - a) launch the request of an APU in-flight start check which will be executed by the flight operations organisation (see 3.6.2.4.2); and

- b) record the success or failure for appropriate further maintenance action(s).
- 4.16.4.2 Specific procedures to address the CAMO and approved maintenance organisation roles should include:
 - a) notification of the APU in-flight start requirement to flight crews through the maintenance release process; and
 - b) documentation procedures for recording and tracking of success or failure of start attempts as well as reporting to the CAAM.

4.17 Control of the aeroplane's EDTO status: EDTO release statement

- 4.17.1 Purpose
- 4.17.1.1 As explained in Chapter 2, the EDTO certification of the aeroplane entails the issuance of an EDTO CMP document which gathers the required configuration, maintenance, procedures and dispatch standards. For EDTO operations, the aeroplane should therefore be configured, maintained and operated according to the EDTO CMP document requirements. This means that the operator should implement tools and/or procedures to control any aeroplane discrepancies that may impact the EDTO serviceability of the aeroplane. This may require the implementation of a system to continuously track and manage the EDTO status of the aeroplane.

Note.— As explained in Paragraph 2.1.5, the basic type certification standards and maintenance programme of aeroplanes with more than two engines provides the required level of safety intended for EDTO and remains suitable for EDTO operations. Accordingly, the EDTO Standards do not introduce additional maintenance requirements or any additional certification requirements for aeroplanes with more than two engines. Therefore, in this case the EDTO status of aeroplanes with more than two engines is directly linked to the status of the relevant TLS(s). In other words, only maintenance or configuration changes (e.g., as identified by the associated configuration, maintenance, and procedures CMP document, if applicable) to the relevant TLS(s) may impact the EDTO status of aeroplanes with more than two engines.

- 4.17.1.2 In addition, as per CAD 6 Part1, paragraph 4.7.2, it is the responsibility of the operator to ensure that the relevant time limitations of the aeroplane engaged in EDTO operations are not exceeded, and for aeroplanes with two turbine engines, that the aeroplane is certified for EDTO and configured for the planned EDTO mission.
- 4.17.1.3 As the time limitations of a given aeroplane may be impacted by the configuration and/or the maintenance programme of the aeroplane, the operator should implement tools and/or procedures to ensure that the relevant EDTO capability and time limitation(s) of the aeroplane dispatched are compatible with the contemplated EDTO flight, as explained in Paragraph 3.5.4.

- 4.17.1.4 An EDTO maintenance release statement should therefore be provided to the flight crew to confirm that:
 - a) the aeroplane condition has been checked and confirmed to comply with the applicable EDTO dispatch requirements set forth in the company policies and applicable MEL;
 - b) the EDTO items of the applicable maintenance line check have been accomplished;
 - c) the aeroplane configuration has been checked and confirmed to comply with the applicable configuration standards set forth in the EDTO CMP document (as applicable); and
 - d) the capability of relevant TLS(s) has been assessed.
- 4.17.1.5 The EDTO maintenance procedures manual (or equivalent) should define the content of the EDTO service check, and the procedures associated with the EDTO maintenance release (see also 4.3 and 4.9).
- 4.17.2 EDTO status: Downgrading and restoration
- 4.17.2.1 If the MEL cannot be complied with for EDTO, or if the aeroplane configuration and/or maintenance do not comply with the applicable EDTO CMP Standards, the "non-EDTO" status of the aeroplane should be indicated in the aeroplane journey logbook
- 4.17.2.2 The discrepancy should be recorded and reported to the personnel within flight operations in charge of preparation of the EDTO flights. For example, the deferred discrepancy could be entered in the deferred defects list, and the "non-EDTO" status recorded on the aeroplane journey logbook.
- 4.17.2.3 To restore the aeroplane back to "EDTO" status, all the EDTO discrepancies should be assessed and/or rectified in line with the applicable EDTO CMP configuration and maintenance standards and/or the MEL EDTO requirements. For example, the corresponding deferred defect item should be cleared and the restored "EDTO" status recorded in the aeroplane technical log or maintenance logbook. The up-to-date EDTO status should be recorded and reported to the personnel within flight operations in charge of preparation of the EDTO flights.
- 4.17.2.4 The changing of the aeroplane EDTO status to "EDTO/non-EDTO" should be carried out by the EDTO qualified personnel responsible for the aeroplane and advised to the maintenance control centre (or other control system) prior to aeroplane release for service.

- 4.17.3 EDTO release statement twin-engine aeroplanes
- 4.17.3.1 The EDTO status of the aeroplane should be indicated to the flight crew prior to each EDTO flight. For that purpose, an EDTO release statement should be issued and it may be included in the aeroplane journey logbook.
- 4.17.3.2 This EDTO status of the aeroplane depends on:
 - a) the certified EDTO capability of the aeroplane;
 - b) the configuration of the aeroplane versus the applicable configuration requirements of the EDTO CMP document;
 - c) the compliance of the aeroplane versus the applicable maintenance requirements of the EDTO CMP document;
 - d) the capability of relevant TLS(s); and
 - e) any inoperative system (MEL).
- 4.17.3.3 An EDTO maintenance release statement should therefore be issued as part of the maintenance release (e.g., certificate of release to service) of the aeroplane. This EDTO maintenance release statement, which is typically included in the aeroplane maintenance logbook, should be provided to the operator's flight operations organisation for operations control and flight preparation purposes. It should clearly indicate:
 - a) whether the concerned aeroplane is EDTO capable (yes or no); and
 - b) the related maximum diversion time capability.
- 4.17.3.4 Figures 4.17-1 and 4.17-2 are typical examples of EDTO release statements for two-engine aeroplane EDTO operations up to 180 minutes.

Note. – As an alternative to the Figure 4.17-1 and 4.17-2 for operators that do not use the below template, it is acceptable for the operator to clearly indicate the statement to confirm the EDTO status and Maximum Diversion Time in their Journey Log Book prior to each EDTO dispatch.

- 4.17.3.5 As shown in Figure 4.17-1, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is capable of EDTO; and
 - b) its maximum diversion time capability is 120 minutes.

| EDTO Status | | Diversion Time (min) | | | |
|-------------|----|----------------------|-----|-----|--|
| YES | NO | 60 | 120 | 180 | |
| | | | | | |

Figure 4.17-1. Example of EDTO release statement (120 minutes)

- 4.17.3.6 As shown in Figure 4.17-2, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is restricted to non-EDTO operations; and
 - b) accordingly, its maximum diversion time capability is 60 minutes.

| EDTO Status | | Diversion Time (min) | | |
|-------------|----|----------------------|-----|-----|
| YES | NO | 60 | 120 | 180 |
| | | | | |



- 4.17.3.7 As explained in Paragraph 3.5.4.3, for EDTO operations beyond 180 minutes, the operator has to check that the diversion flight times (plus 15 minutes) along the planned flight track do not exceed the times specified in the AFM (or other relevant aeroplane manufacturer documentation) for the aeroplane's cargo fire suppression system, referred to as the AEO time capability, and for the aeroplane's most TLS time (other than cargo fire suppression), referred to as the OEI time capability.
- 4.17.3.8 Therefore, a dedicated process for the check and tracking of the time capability of the relevant TLS(s), if any, should be implemented in order to ensure that this information is adequately transferred to the flight operations organisation (dispatchers and flight crews).
- 4.17.3.9 It may be done by including in the EDTO release statement the necessary check boxes for each of the possible values of time capability of the relevant TLS(s). The corresponding values should be updated as part of the aeroplane's maintenance release anytime there is a situation impacting the time capability of the concerned TLS(s), e.g., in case of:

- a) the system being inoperative;
- b) the system being replaced by another with a lesser/greater time capability; and
- c) maintenance action impacting the time capability of the system.
- 4.17.3.10 Figure 4.17-3 is a typical example of an EDTO release statement for EDTO operations beyond 180 minutes. In this example, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is capable of EDTO beyond 180 minutes;
 - b) its maximum OEI time capability is 340 minutes; and
 - c) its maximum AEO time capability is 250 minutes.

| EDTO Status | | Diversion Time (min) | | | |
|-------------|----|---|-----|-----|----------------|
| YES | NO | 60 | 120 | 180 | >180 |
| | | | | | |
| | | EDTO time-limited system capability (min): | | OEI | ☐ 290 ✓ 340 |
| | | | | AEO | 250 300 |

Figure 4.17-3.Example of EDTO release statement (EDTO beyond 180 minutes)

- 4.17.4 EDTO release statement aeroplanes with more than two engines
- 4.17.4.1 As discussed in Paragraph 2.1.5, it has been confirmed that for aeroplanes with more than two engines, both the basic type certification standards and maintenance programme provide the required level of safety for EDTO and are suitable for EDTO operations. Accordingly, the EDTO Standards do not introduce additional maintenance requirements or any additional certification requirements for aeroplanes with more than two engines. Nevertheless, it has also been concluded that a review of the time limitation of relevant TLSs, if any, is necessary for aeroplanes with more than two engines engaged in EDTO.
- 4.17.4.2 Therefore, the EDTO status of aeroplanes with more than two engines is linked to the status of the relevant TLS. In other words, only maintenance or configuration changes to the relevant TLS may impact the EDTO status of aeroplanes with more than two engines.

- 4.17.4.3 The number of items that may impact this EDTO status should be very limited and it may therefore not be necessary to implement a process for EDTO release statement as for twin-engine aeroplanes unless there is an associated CMP document (see 4.17.3). Typically, the impact of an unserviceable TLS (e.g., an inoperative cargo fire suppression bottle) could be handled through the existing deferred defect list, and the related diversion time limitation should be duly taken into consideration when planning the EDTO flight, as for any other MEL items.
- 4.17.4.4 A system of EDTO release statement may still be implemented to facilitate the management of this EDTO status. Figure 4.17-4 provides an example of an EDTO release statement adapted to aeroplanes with more than two engines (assuming that the EDTO threshold has been set at 180 minutes).
- 4.17.4.5 As shown in Figure 4.17-4, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is capable of EDTO; and
 - b) its maximum AEO time capability is 300 minutes.



Figure 4.17-4. Example of EDTO release statement (aeroplane with more than two engines)

- 4.17.4.6 In Figure 4.17-5, the EDTO status of the concerned aeroplane is as follows:
 - a) the aeroplane is restricted to non-EDTO operations; and
 - b) its maximum AEO time capability is 195 minutes.

Note. – As an alternative to the Figure 4.17-1 and 4.17-2 for operators that do not use the above template, it is acceptable for the operator to clearly indicate the statement to confirm the EDTO status and Maximum Diversion Time in their Journey Log Book prior to each EDTO dispatch.

| EDTO Status | | Diversion Time (min) | | |
|-------------|---------------------------------------|----------------------|------|--|
| YES | NO | Up to 180 | >180 | |
| | | | _ĴĹ | |
| E | ✓ 195☐ 300 | | | |

Figure 4.17-5. Example of non-EDTO release statement (aeroplane with more than two engines)

4.18 EDTO training

- 4.18.1 EDTO operators should create an EDTO training programme to support EDTO qualifications but also to educate personnel on the special nature of EDTO and to assure that EDTO programme tasks are properly accomplished. This training course is an integral part of the operator's EDTO maintenance programme as defined in Paragraph 4.2 and may be in addition to any specific aeroplane technical training required for the position. The course is to ensure that all personnel who have assigned EDTO responsibilities are provided with the necessary training so that EDTO tasks are properly planned and accomplished. The course requires approval by the CAAM and written into the EMPM.
- 4.18.2 The training programme should include consideration of any contracted maintenance provider and contain the process of qualification of individuals. The EMPM should define how the training records are tracked and stored, and a notification process should be implemented to notify qualified personnel when training is required. The process of delegating any training should be defined in the EMPM. Any recurrent training requirements should be included in the description.
- 4.18.3 The EDTO maintenance training should cover:
 - a) *initial training* to ensure that all maintenance personnel have the knowledge, skills and ability to perform an adequate EDTO technical procedure for the specific AEC; and
 - b) *recurrent training* to ensure that all maintenance personnel maintain and update, if necessary, their awareness of EDTO maintenance specificities.
- 4.18.4 If recurrent training is part of the operator-approved programme, the recurrent time line should be defined in the programme, and a notification system should be in
place to notify personnel and management of any required training. A process should be in place to manage contract maintenance personnel as personnel change due to attrition. Recurrent training can be accomplished through a test process and controlled through management personnel at the individual stations. Failure of this test requires the staff to retake the training programme.

- 4.18.5 This EDTO training programme should typically include:
 - a) introduction to EDTO regulations;
 - b) focus on applicable elements of national EDTO regulation;
 - c) overview of EDTO certification of twin-engine aircraft;
 - d) EDTO significant systems;
 - e) EDTO authorisation (maximum diversion times, TLSs, operator's approved diversion time, EDTO routes, EDTO MEL);
 - f) CMP and EDTO maintenance programme;
 - g) EDTO pre-departure service check (including the EDTO maintenance release, see 4.17);
 - h) EDTO reliability programme procedures, for example, (as applicable):
 - 1) Parts control programme (see 4.8);
 - 2) EDTO service check (see 4.9);
 - 3) Reliability programme (see 4.10);
 - 4) Propulsion system monitoring (see 4.11);
 - 5) Verification programme (see 4.12);
 - 6) Dual maintenance limitations (see 4.13);
 - 7) Engine condition monitoring (see 4.14);
 - 8) Oil consumption monitoring (see 4.15); and
 - 9) APU in-flight start monitoring programme (see 4.16);
 - i) additional procedures for EDTO (as applicable).
- 4.18.6 The training format can be created as an instructor-led course or as a computerbased training course and should include the general nature of EDTO. The programme should also reflect the specific operator EDTO maintenance programme requirements. As revisions to the EMPM are developed, the training programme should be revised to include any major changes to the EDTO maintenance programme.
- 4.18.7 The training course can be created by the operator or it can be contracted for development from an outside source. In either case, the programme is the responsibility of the operator and should have the authorisation of the CAAM.
- 4.18.8 The operator determines the level of qualification required for EDTO signature authority which should be defined in the EMPM and approved by the CAAM. The

Chapter 4 – EDTO Maintenance and Reliability Requirements

specific theoretical, practical, and/or process training should be defined in the associated syllabus. EDTO training may not differ greatly between aeroplane models but those differences should be defined in the programme. The intent is not to revise the training programme for small administrative changes to the EMPM but to focus on major changes to the programme driven by a new procedure or process.

5 Operational Approval

5.1 General Application process

- 5.1.1 The approval process consists of the following phases:
- 5.1.1.1 **Step 1** <u>**Pre-application phase:</u>** Prior to initiating the approval process, the operator will review the requirements and guidelines outlined in the relevant regulations, CADs, and CAGMs which are published by the CAAM.</u>

A pre-application usually commences when a prospective applicant makes his initial inquiries regarding application for an approval in the form of a letter or a personal visit to the CAAM. If the proposed application is complex, the operator may need to obtain advice and assistance from OEMs or other design organisations, training establishments, data providers, etc.

This Phase will include both Flight Operations and Airworthiness division to assist the applicant in queries and highlighting the requirements.

5.1.1.2 **Step 2** <u>— Formal application phase:</u> The operator submits to the CAAM a formal, written application for approval, the CAAM will then appoint a Specific Approvals Manger (SAM) to oversee the application

Note. – An example application form is contained in Attachment A.

- 5.1.1.3 **Step 3** <u>Document evaluation phase:</u> The CAAM FOI and AWI evaluate the formal written application for approval to determine if all the requirements are being met. The FOI and AWI, may need to obtain advice and assistance from other departments within CAAM or organisations such as regional agencies or experts in other States.
- 5.1.1.4 **Step 4 <u>Demonstration and inspection phase</u>:** During a formal inspection by the FOI and AWI (assisted as necessary by a team from the CAAM), the operator demonstrates how the requirements are being met.
- 5.1.1.5 **Step 5 <u>Approval phase</u>**: Following a successful formal inspection by the CAAM, approval is given via:
 - c) an amendment to the OM; and
 - d) an Ops Spec associated with the AOC.

Note 1. – The demonstration and inspection phase may not be required depending upon the type of operation used, subject to the consideration of the CAAM

5.2 Approval Process

5.2.1 An operator wishing to obtain an EDTO authorisation must submit an application form (Attachment A) with all the supporting data. This application will be for a specific airplane- engine combination and should address all the regulatory



requirements for EDTO. The operator may follow the guidance found in this CAGM to complete the application. The application should be submitted at least 60 up to 90 working days for In-Service EDTO operational approval days prior (180 working days for the Accelerated EDTO method of application) to the proposed start of extended range operation with the specific airplane-engine combination.

6 Appendices

6.1 Appendix 1: Accelerated EDTO approval

In addition to the para 1.4.2.9 of this CAGM, the criteria defined in this section permit approval of EDTO operations up to 120 minutes, when the operator has established that those processes necessary for successful EDTO are in place and are proven to be reliable. The basis of the accelerated approval is that the operator will meet equivalent levels of safety and satisfy the objectives of this guidance.

The Accelerated EDTO approval process will be based on Chapter 5 of this CAGM.

Step – 1 Pre - Application phase

Prior to initiating the approval process, the operator should review the applicable regulations in CAD 6 and guidelines outlined in this CAGMs.

A pre-application usually commences when a prospective applicant makes his/her initial inquiries regarding application for an approval in the form of a letter or a personal visit to the CAAM. If the proposed application is complex, the operator may need to obtain advice and assistance from OEMs or other design organisations, training establishments, data providers, etc

Step – 2 Formal Application phase (Application phase)

The operator should submit an Accelerated EDTO Operations Approval Plan to the Authority six (6) months before the proposed start of EDTO. This time will permit the CAAM to review the documented plans and ensure adequate EDTO processes are in place.

(A) Accelerated EDTO Operations approval plan:

The Accelerated EDTO Operations approval plan should define:

1. the proposed routes and the EDTO diversion time necessary to support those routes;

2. The proposed one-engine-inoperative cruise speed, which may be area specific depending upon anticipated aeroplane loading and likely fuel penalties associated with the planned procedures;

3. How to comply with the EDTO Processes listed in paragraph (B);

4. The resources allocated to each EDTO process to initiate and sustain EDTO operations in a manner that demonstrates commitment by management and all personnel involved in EDTO continuing airworthiness and operational support;

5. How to establish compliance with the build standard required for Type Design Approval, e.g. CMP document compliance;

6. Review Gates: A review gate is a milestone of the tracking plan to allow for the orderly tracking and documentation of specific provisions of this section. Normally, the review gate process will start six months before the proposed start of EDTO and should continue until at least six months after the start of EDTO. The review gate process will help ensure that the

proven processes comply with the provisions of this CAGM and are capable of continued EDTO operations.

(B) Operator EDTO process elements

The operator seeking Accelerated EDTO Operational Approval should also demonstrate to the CAAM that it has established an EDTO process that includes the following EDTO elements:

1. Airframe/engine combination and engine compliance to EDTO Type Design Build Standard (CMP) as stated in CAD 6;

2. Compliance with the EDTO Maintenance Programme as defined in Chapter 4.2 of this CAGM, which should include:

- a. A proven EDTO Reliability Programme;
- b. A proven Oil Consumption Monitoring Programme;
- c. A proven Engine Condition Monitoring programme and;
- d. A proven plan for resolution of aeroplane discrepancies.
- 3. EDTO operations manual supplement or its equivalent in the Operations Manual;

4. The operator should establish a programme that results in a high degree of confidence that the propulsion system reliability appropriate to the EDTO diversion time would be maintained;

5. Initial and recurrent training and qualification programmes in place for EDTO related personnel, including flight crew and all other operations personnel;

6. Compliance with the Flight Operations Programme as defined in this AMC;

7. Proven flight planning and dispatch programmes appropriate to EDTO;

8. Procedures to ensure the availability of meteorological information and MEL appropriate to EDTO; and

9. Flight crew and dispatch personnel familiar with the EDTO routes to be flown; in particular the requirements for, and selection of EDTO en-route alternate aerodromes.

(C) Process elements Documentation:

Documentation should be provided for the following elements:

1. Technology new to the operator and significant differences in EDTO significant systems (engines, electrical, hydraulic and pneumatic), compared to the aeroplanes currently operated and the aeroplane for which the operator is seeking Accelerated EDTO Operations Approval;

2. The plan to train the flight and continuing airworthiness and maintenance personnel to the different EDTO process elements;

3. The plan to use proven or manufacturer validated Training and Maintenance and Operations Manual procedures relevant to EDTO for the aeroplane for which the operator is seeking Accelerated EDTO Operations Approval;



Chapter 6 – Appendices

4. Changes to any previously proven or manufacturer validated Training, Maintenance or Operations Manual procedures described above. Depending on the nature of any changes, the operator may be required to provide a plan for validating such changes;

5. The validation plan for any additional operator unique training and procedures relevant to EDTO, if any;

6. Details of any EDTO support programme from the airframe/engine combination or engine (S)TC holder, other operators or any third country authority or other competent authority; and

7. The control procedures when a contracted maintenance organisation or flight dispatch organisation is used.

<u>Step – 3 Documentation evaluation phase</u> (Validation of the operator's EDTO <u>Processes</u>)

This section identifies process elements that need to be validated and approved prior to the start of Accelerated EDTO. For a process to be considered proven, the process should first be described, including a *flow chart of process elements*. The roles and responsibilities of the personnel managing the process should be defined including any training requirement. The operator should demonstrate that the process is in place and functions as intended. This may be accomplished by providing data, documentation and analysis results and/or by demonstrating in practise that the process works and consistently provides the intended results. The operator should also demonstrate that a feedback loop exists to facilitate the surveillance of the process, based on in-service experience.

If any operator is currently approved for conducting EDTO with a different engine and/or airframe/engine combination, it may be able to document proven EDTO processes. In this case only minimal further validation may be necessary. It will be necessary to demonstrate that processes are in place to assure equivalent results on the engine and/or airframe/engine combination being proposed for Accelerated EDTO Operations Approval.

(A) Reduction in the validation requirements:

The following elements will be useful or beneficial in justifying a reduction by the CAAM in the validation requirements of EDTO processes:

1. Experience with other airframes and/or engines;

2. Previous EDTO experience;

3. Experience with long range, over-water operations with two, three or four engine aeroplanes;

4. Any experience gained by flight crews, continuing airworthiness personnel and flight dispatch personnel, while working with other EDTO approved operators, particularly when such experience is with the same airframe or airframe/engine combination. Process validation may be done on the airframe/engine combination, which will be used in Accelerated EDTO operation or on a different aeroplane type than that for which approval is being sought.



(B) Validation programme:

A process could be validated by demonstrating that it produces equivalent results on a different aeroplane type or airframe/engine combination. In this case, the validation programme should address the following:

1. The operator should show that the EDTO validation programme can be executed in a safe manner;

2. The operator should state in its application any policy guidance to personnel involved in the EDTO process validation programme. Such guidance should clearly state that EDTO process validation exercises should not be allowed to adversely impact the safety of actual operations, especially during periods of abnormal, emergency, or high cockpit workload operations. It should emphasise that during periods of abnormal or emergency operation or high cockpit workload EDTO process validation exercises may be terminated;

3. The validation scenario should be of sufficient frequency and operational exposure to validate maintenance and operational support systems not validated by other means;

4. A means should be established to monitor and report performance with respect to accomplishment of tasks associated with EDTO process elements. Any recommended changes resulting from the validation programme to EDTO continuing airworthiness and/or operational process elements should be defined.

(C) Documentation requirements for the process validation

The operator should:

1. Document how each element of the EDTO process was utilised during the validation;

2. Document any shortcomings with the process elements and measures in place to correct such shortcomings;

3. Document any changes to EDTO processes, which were required after an in-flight shut down (IFSD), unscheduled engine removals, or any other significant operational events;

4. Provide periodic Process Validation reports to the CAAM (this may be addressed during Review Gates).

(D) Validation programme information

Prior to the start of the validation process, the following information should be submitted to the competent authority CAAM:

1. Validation periods, including start dates and proposed completion dates;

2. Definition of aeroplane to be used in the validation (List should include registration numbers, manufacturer and serial number and model of the airframe and engines);

3. Description of the areas of operation (if relevant to validation) proposed for validation and actual operations;

4. Definition of designated EDTO validation routes. The routes should be of duration required to ensure necessary process validation occurs;

5. Process validation reporting. The operator should compile results of EDTO process validation.



6. Information related to maintenance arrangement to support the EDTO operations at en-routes alternate aerodrome

<u>Step – 4</u> Demonstration and inspection phase (Validation of Operator EDTO Continuing Airworthiness and Operations Capability)

The operator should demonstrate competence to safely conduct and adequately support the intended operation. Prior to EDTO approval, the operator should demonstrate that the EDTO continuing airworthiness processes are being properly conducted. The operator should also demonstrate that the interfaces between CAMO and operations and/or maintenance support for EDTO flight dispatch and release practices, policies, and procedures are established for operations. An operational validation flight may be required so that the operator can demonstrate dispatch and normal in-flight procedures. The content of this validation flight will be determined by the CAAM based on the previous experience of the operator. Upon successful completion of the validation flight, when required, the operator should modify the operational manuals to include approval for EDTO as applicable

Step 5 Approval phase (EDTO Operations Approval issued by the CAAM)

Operations approvals granted with reduced in-service experience may be limited to those areas determined by the CAAM at time of issue. An application for a change is required for new areas to be added.

The approval issued by the CAAM for EDTO up to 180 minutes should be based on the information required in Chapter 3.5 of this CAGM



6.2 Appendix 2: EDTO training program

The operator EDTO training programme should provide initial and recurrent training for flight crew as follows:

- 1 Introduction to EDTO Regulations
 - a) Brief overview of the history of EDTO;
 - b) EDTO regulations;
 - c) Definitions;
 - d) Approved One-Engine-Inoperative Cruise Speed and drift down procedures;
 - e) EDTO Type Design Approval a brief synopsis;
 - f) Maximum approved diversion times and time-limited systems capability;
 - g) Operator's Approved Diversion Time;
 - h) Routes and aerodromes intended to be used in the EDTO area of operations;
 - i) EDTO Operations Approval;
 - j) EDTO Area and Routes;
 - k) EDTO en-route alternates aerodromes including all available let- down aids;
 - I) Navigation systems accuracy, limitations and operating procedures;
 - m) Meteorological facilities and availability of information;
 - n) In-flight monitoring procedures;
 - o) Computerised Flight Plan;
 - p) Orientation charts, including low level planning charts and flight progress charts usage (including position plotting);
 - q) Equal Time Point;
 - r) Critical fuel.
- 2 Normal Operations
 - a) Flight planning and Dispatch
 - 1) EDTO Fuel requirements
 - 2) Route Alternate selection weather minima
 - 3) Minimum Equipment List EDTO specific
 - 4) EDTO service check and journey log
 - 5) Flight crew pre departure check
 - 6) Pre-flight FMS Set up



Chapter 6 – Appendices

- b) Flight performance progress monitoring
 - 1) Flight management, navigation and communication systems
 - 2) Aeroplane system monitoring
 - 3) Weather monitoring
 - 4) In-flight fuel management to include independent cross checking of fuel quantity
- 3 Abnormal and Contingency Procedures
 - a) Diversion Procedures and Diversion 'decision making'.

Initial and recurrent training to prepare flight crews to evaluate potential significant system failures. The goal of this training should be to establish crew competency in dealing with the most probable contingencies. The discussion should include the factors that may require medical, passenger related or non-technical diversions.

- b) Navigation and communication systems, including appropriate flight management devices in degraded modes.
- c) Fuel Management with degraded systems.
- Initial and recurrent training which emphasis abnormal and emergency procedures to be followed in the event of foreseeable failures for each area of operation, including:
 - Procedures for single and multiple failures in flight affecting EDTO sector entry and diversion decisions. If standby sources of electrical power significantly degrade the cockpit instrumentation to the pilots, then training for approaches with the standby generator as the sole power source should be conducted during initial and recurrent training.
 - 2) Operational restrictions associated with these system failures including any applicable MEL considerations.
- 4 Specific EDTO training requirements
- 4.1 The flight crew must be provided with detailed initial and recurrent training which emphasises abnormal and emergency procedures to be followed in the event of unforeseeable failures for each area of operation, including:
 - a) Procedures for single and multiple failures in-flight affecting EDTO entry and diversion decisions. For example, if standby sources of electrical power significantly degrade cockpit instrumentation, then training which simulates approach with the standby generator as the sole power source should be conducted during initial and recurrent training
 - b) Operational restrictions associated with these failures (including any applicable MEL considerations)
 - c) Crew incapacitation



- d) Use of emergency equipment
- e) Procedures to be followed in the event that there is a change in conditions at designated EDTO en-route alternates for the flight, which would preclude safe approach and landing

5 Flight Operations Personal Other Than Flight Crew

The operator's training programme in respect to EDTO should provide training where applicable for operations personnel other than flight crew (e.g. dispatchers), in addition to refresher training in the following areas:

- a) EDTO Regulations/Operations Approval
- b) Aeroplane performance/Diversion procedures
- c) En-route alternate aerodromes
- d) Area of Operation
- e) Fuel Requirements as per Appendix 2, para 5.1, 5.2 & 5.3, of this CAGM
- f) Dispatch Considerations MEL, CDL, weather minima, and alternate airports
- g) Pre-flight system serviceability
- h) Availability of relevant performance information
- i) Documentation
- j) Communication facility

7 Attachments

7.1 Attachment A: EDTO application form About this Application Form:

This form is approved by the Civil Aviation Authority of Malaysia (CAAM) for the issuance of specific approvals. The application form is made up of five sections as follows:

- 1) Section A- Details of the Applicant
- 2) Section B- Details of Proposed/ Approved Type of Operations
- 3) Section C- Applicant(s) Declaration
- 4) Section D- Flight Operations Section
- 5) Section E- Airworthiness Section

Abbreviations

| AFM | = | Aircraft Flight Manual |
|----------|---|--|
| AMMD | = | aircraft moving map display |
| AMO | = | Approved Maintenance Organisation |
| AOC | = | Air operator certificate |
| AWI | = | Airworthiness Inspector |
| CAAM | = | The Civil Aviation Authority of Malaysia |
| CAD | = | Civil Aviation Directives |
| CAGM | = | Civil Aviation guidance manual |
| CAMO | = | Continuing Airworthiness Management Organisation |
| DG | = | Dangerous goods |
| EDTO | = | Extended diversion time operations |
| EFB | = | Electronic. Flight bag |
| FOI | = | Flight Operations |
| HEMS (H) | = | Helicopter Emergency Medical Service |
| HHO (H) | = | Helicopter Hoist Operations |
| HOFO (H) | = | Helicopter Offshore Operations |
| IMC | = | Instrument meteorological conditions |
| LVO | = | Low Visibility Operations |
| MCAR | = | Malaysian Civil Aviation Regulations |
| MOE | = | Maintenance Organisation Exposition |
| NAT-HLA | = | North Atlantic High-Level Airspace |
| NVIS (H) | = | Night Vision Imaging Systems |

| Chapter 7 – | Attachm | ents |
|-------------|---------|--|
| PMI | = | Principal Maintenance Inspector |
| POI | = | Principal Operations Inspector |
| PBN | = | Performance based navigation |
| RVSM | = | Reduced Vertical Separation Minimum |
| SET-IMC | = | Single - Engined Turbine Aeroplane Operations at night or in IMC |
| SPA | = | Specific approval |
| SAM | = | Specific Approvals Manger |
| SME | = | Subject Matter Expert |
| TSO | = | Technical Standard Order |

GUIDELINES FOR COMPLETING THIS APPLICATION FORM

All applicants shall fill all sections of this application form. If applying for multiple specific approvals, only ONE section A to section C is required, followed with all the relevant section D and section E as applicable to the SPA being applied for.

All information will be used to assess if the applicant is entitled to a Specific Approval. An incomplete, poorly prepared or inaccurate application may:

- Result in rejection of the application
- Result in delays

1

• Result a refusal to issue the SPA.

Please remember it is an offence to make a false declaration in this form in accordance with Regulation 164 of the Civil Aviation Regulations 2016 (MCAR 2016)

If the form is filled by hand, use block letters and either a black or blue ballpoint pen. Some questions contain check boxes. Annotate with a \checkmark where appropriate. This information is used by the F.O.I/A.W.I when going through the application package.

| Section A – Detail | Section A – Details of the applicant | | | | | | | |
|---------------------|--|--------------------|--------------|-------------|-----------|------------------|----|-----------|
| Applicant type: | | | AOC Number: | | | | | |
| | to exis | ting Specific Appr | oval | Proposed | l Start D | ate: | | |
| Details of the ope | Details of the operator of the aircraft: | | | | | | | |
| Name of Operator | | | | | | | | |
| Trading name if dif | ferent | | | | | | | |
| Phone | | | | Fax | | | | |
| | | | | | | | | |
| Registered Address | s | | | City | | | | |
| | | State | | Postcode | | | | |
| Details of the pers | son th | at you wish CA | AM to conta | ict in rela | tion to | this application | on | |
| Full Name | | | | | | | | |
| Phone | | | | Mobil | е | | | |
| Email | | | | | | | | |
| Section B – Detail | s of p | roposed type o | f operations | 5 | | | | |
| | | PBN | | LVO | | EDTO | | EFB |
| | | PBCS | | CPDLC | | ADS-C | | ADS-B OUT |
| D ADS-B IN | | NVIS(H) | | HHO(H) | | HEMS(H) | | HOFO(H) |
| | | DG | | Others | Specify | /: | | |
| Proposed/Approv | ed typ | e of operations | 3 | | | | | |
| So So | chedu | le 🗆 No | on-Schedule | | Pa | assenger 🗆 | | Cargo |



Authorisation and Aircraft Details – Provide details of the aircraft.

*Note: the column "SPA being applied for" is only applicable when applying for different SPA's on different aircraft. If applying for similar SPA's on all aircraft listed below as ticked in section B, the column need not be filled.

| # | Aircraft Manufacturer | Aircraft Model | MSN | Registration Mark | Is it a new Aircraft? (Y/N) | Est. date of entry into service dd/mmm/yy. (applicable to new aircraft only) | SPA being applied for.* |
|---|--------------------------|-------------------|-----|-------------------|-----------------------------------|--|-------------------------|
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

(Use additional sheets if necessary)



Section C- Applicants Declaration

DECLARATION

 I declare and undersign below that the statements, answers and attachments provided in this application form is true and correct to the best of my knowledge in accordance with Civil Aviation Regulations 2016 (MCAR) and Civil Aviation Directives (CAD).

Giving false or misleading information is an offence under Regulation 164 of the Civil Aviation Regulations 2016 (MCAR)

- 2. I understand that processing the application may be delayed if:
 - The application does not accurately and completely identify my/our requirements; or
 - The details in this application are subsequently changed; or
 - Adequate supporting documentation has not been provided.
- 3. I understand and agree that for CAAM to proceed with this application, I must:
 - Accept the cost as per civil aviation (fees and charges) regulation; and
 - Forward the prescribed payment; and
 - Forward all supporting documentation as required by the specific approval being applied for.

Note. – CAAM may send materials/responses relating to this application by email or by mail.

| Name of DFO | | | gnature | | | Da | ite | |
|---|--------------|-----------------------|---------|-----------|--------------|----------|--------|-----|
| FOR CAAM USE ONLY | | | | | | | | |
| Date of Initial application Received by administrator | | | | | | | | |
| Fee payable | | | | | | | | |
| Cash / Credit Card | | | | | | | | |
| Receipt No.: | | | Name 8 | Signature | of CAAM Pers | onnel | | |
| Subject | Responsib | e division | Date | | r | Name & S | Signat | ure |
| Application Form and application package checke for completeness. | ed SAM & Air | worthiness SM | 1E | | | | | |
| Airworthiness Recommendation granted | Airworthi | Airworthiness SME/PMI | | | | | | |
| Operational Approval granted (AOC, AOC Extract, letter of Authorisation). | or P | OI/SAM | | | | | | |
| Approval process administratively completed (OPS Spec Update, Billing, ar Exchange of Certificates). | Adn | Administrator | | | | | | |
| Approved (if no, state reasons below)) | YES | | | N | C | | | |
| Withdrawal of Approval rea | son. | | | | | | | |
| Remarks: | | | | | | | | |

Section D – Flight Operations

Part 1 – EDTO Approval Details

Note1. - Documented evidence and/or extracts of manuals must be provided to support answers listed below.

Note2. – Either world fleet data or similar and/or other relevant aircraft type experience to date should be presented as a supplement.

| # | Scope of Application | Yes | No | Remarks |
|--------|---|----------|-------|-----------------------------|
| 1 | Application for EDTO 90 minutes | | | |
| 2 | Application for EDTO 120 minutes | | | |
| 3 | Application for EDTO 180 minutes | | | |
| 4 | Application for EDTO 240 minutes | | | |
| 5 | Application for EDTO >240 minutes | | | |
| 6 | Other (e.g. 138, 207 minutes, etc) Specify in remarks column | | | |
| 7 | Accelerated Approval (any time frame greater than 90 minutes) | | | |
| If spa | ce insufficient for remarks, provide addi | tional r | emark | s accordingly (If required) |

| Number of months/years of operational experience with specific airframe/engine combination: | |
|--|--|
| Total number of long range and/or domestic operations conducted with specific airframe/engine combinations | |

Part 2 – Operational information

Operating Practices and Procedures. To be completed by applicant. Operators EDTO operating practices and procedures reference. (add manual reference, chapter and sub-chapter)

| Subject | Requirements | Operations manual reference |
|--|--|-----------------------------|
| a. Regulatory and directive requirements | a. MCAR regulation 122 b. CAD 6 part 1 or CAD 6 part 2 c. CAGM 6008(IV) EDTO | |
| b. Best practice reference | | |
| Definitions | Extended operations Adequate aerodrome Approved one-engine inoperative cruise speed. Threshold distance/time. Adequate EDTO en-route alternate. Equal time points. Rule distance/time. EDTO segment EDTO significant system. Maximum approved diversion time. Dispatch. | |
| Criteria | Applicant's AOC-defined operating area. Approved aircraft Type airframe/engine combination | |
| Approval | Approved diversion time | |
| Qualification | Crew qualifications. EDTO qualified dispatcher personnel. EDTO qualified operations staff. EDTO qualified maintenance personnel. | |
| Training (Initial & recurrent) and checking | Flight Crew Training and Operations Manuals. Flight currency requirements. | |
| Operations Manual – | Part A (General) | |
| EDTO Authorisation | Commander's responsibilities. Statement to show when EDTO was approved. | |
| EDTO Flight Preparation and Planning | Aircraft serviceability and MEL. Communication and navigation facilities. Critical fuel scenario. Critical fuel reserve. EDTO alternate aerodrome selection. EDTO alternate planning minima. Pre-dispatch and post-dispatch weather minima. Computerised flight planning. Delayed dispatch | |



| | Maintenance check (pre-departure service check). | |
|--|---|--|
| | Verification flights. | |
| | Crew responsibilities. | |
| | Flight documentation handling. | |
| | Fuel management. | |
| | Weather monitoring. | |
| Flight Crew Procedures | Change of routing. Diversion decision making | |
| | Diversion decision-making. Icing | |
| | Crew workload management | |
| | Minimum altitudes applicable to the routes to | |
| | be flown and any diversionary routes. | |
| Operations Manual – | Part B (Type – Specific) | |
| | Identification of EDTO aeroplane. | |
| Type-related EDTO | Types of EDTO approved operations. | |
| Operations | Placards and Limitations. | |
| | One-engine inoperative speed. | |
| Type-specific Planning | | |
| Requirements | | |
| | | |
| EDTO Fuel Planning | Include critical fuel scenario. | |
| | | |
| | EDTO – Specific MEL/CDL items. | |
| | Performance data. | |
| Aeroplane Systems | Aerodrome technical differences, navigation fit communication fit | |
| | Navigation failures | |
| | Action to be taken on EDTO-significant | |
| Non-normal Procedures | system failure. | |
| | Low fuel scenario. Crew incapacitation. | |
| Operations Manual – | Part C (Route and Aerodromes Instructions) | |
| | Approved area of operation. | |
| | EDTO en-route alternates. | |
| | Performance restrictions and weather minima | |
| | for en-route alternates. | |
| EDTO Areas and Routes | Meteorological facilities/information. | |
| | Low attitude cruise information. Bouto minimum diversion altitudes | |
| | Noute minimum diversion allitudes. MSA restrictions | |
| | Route-specific oxygen requirements | |
| | | |
| Operations Manual – | Part D (Training) | |
| | General. | |
| | EDTO overview. | |
| Ground Simulator and | EDTO regulations. | |
| Line Training | EDIO type design approval. Definitions | |
| - · · ································ | Approved one-engine inoperative speed | |
| | Maximum approved diversion time. | |
| | Applicant's approved diversion time. | |
| | EDTO area of operation. | |
| | EDTO routes | |



| | EDTO alternate aerodromes and weather minima Navigation system accuracy, limitations and operating procedures. Meteorological facilities and information. In-flight monitoring and procedures. Computerised flight plan. Charts and position plotting. Equal time point. Critical fuel. Normal Procedures: Flight planning and dispatch. fuel requirements. Route alternate selection – weather minima. MEL – equipment-specific. EDTO service check and technical log. Pre-flight FMS set-up. Flight performance progress monitoring. Flight management. navigation and | |
|--|--|--|
| | Aeroplane system monitoring. Meather monitoring. In-flight fuel management (to include independent cross-checking of fuel quantity) Non-normal Procedures: | |
| | Diversion procedures and diversion "decision-making". Navigation and communication systems, including appropriate flight management devices in degraded modes. Fuel management with degraded systems. Procedures for single and multiple in flight during EDTO sector entry and diversion decisions. Operating on standby power. Operational restrictions associated with system failures including any applicable MEL considerations. | |
| EDTO Simulator Training and Line Flying under Supervision. | Pilot's conversion course. Annual refresher course. Outline of training syllabus to include: | |
| Flight Operations Staff and Dispatchers. | EDTO regulation. Operational approval. Aeroplane performance. Diversion procedures. Area of operation. Fuel requirements. Dispatch considerations: MEL, CDL, weather minima and alternate airports. Delayed dispatch. Documentation. | |



| Part 3 – Recovery plan | |
|--|--|
| Passengers and crew member recovery plans for diversions to en-route alternates if relevant to the proposed | |
| operation. | |

Section E – Airworthiness

To be completed by applicant. Operators EDTO operating practices and procedures reference. (add manual reference, chapter and sub-chapter)

Part 1 – Applicants experience and propulsion system reliability

Operator's total number of airframe/engine hours and cycles with specific airframe/engine combinations

| | 1 | | | |
|--|---|--|---|---------------------------|
| Total airframe fleet hours | | | | |
| Total airframe fleet cycle | | | | |
| Total engine hours | | | | |
| Hours of operator's high engine | | | | |
| In-flight shutdown (FSD) rate (all causes), including t the world fleet (FSD per 1000 engine flight hours) | he 12-month r | olling averag | e for both ope | erator and |
| IFSD rate of operator's fleet | | | | |
| IFSD rate of world fleet | | | | |
| Unscheduled engine removal rate (URR) for both ope flight hours) (Tick appropriate box below) | erator and the | world fleet (l | JRR rate per | 1000 engine |
| URR of operator's fleet | YES | | NO | |
| URR of world fleet | YES | | NO | |
| Records of mean time between failures (MTBF) for major components available (unit flight hours/number of unit failure) | YES | | NO | |
| Records of APU start and run reliability available (if the APU is required for EDTO) | YES | | NO | |
| Records of delays and cancellations due to technical issues relevant to EDTO, with cause, by specific aeroplane systems (if available) | YES | | NO | |
| Records of the following significant operator events where available: (including the phase of flight where the event occurred | | | | |
| Inability to control engine or obtain desired power | | | | |
| In-flight shutdown events | | | | |
| Part 2 – Supplement to the maintenance program | me and main | tenance pro | cedure | |
| The applicant is required to establish the following procedures: | To be comple described in (subchapter, e | eted by applic added manu e.g. MCM 16. | ant. The proc al reference, (4.1): | edures are chapter and |
| | | | | |

Procedures to preclude simultaneous actions from being applied to multiple similar elements in any



| EDTO system | |
|--|---|
| An EDTO pre-departure service check shall be developed to verify that the status of the aircraft and certain critical items are acceptable. This check shall be accomplished and signed off by an EDTO qualified authorised person immediately prior to an EDTO flight. | |
| Procedures for reviewing and documenting of log books to ensure proper MEL procedures, deferred items and maintenance checks and that system verification procedures have been properly performed | |
| EDTO related tasks shall be identified on the routine work forms and related instructions. | |
| EDTO related procedures, such as involvement of centralised maintenance control, shall be clearly defined in the applicant's programme. | |
| Part 3 – EDTO Maintenance Manual | |
| Applicant should develop a manual for use by pers al is to identify the supplementary procedures and rea minimum, contain the procedures listed below. | onnel involved in EDTO. The purpose of the EDTO quirements for EDTO operations. This manual should, |
| Engine/APU oil consumption monitoring program | me |
| Procedures that monitor oil consumption rates for engine and APU (if the APU is required for the EDTO) for EDTO and non-EDTO flight. | |
| Procedures for calculating oil consumption rate prior to departure to address any sudden shift in consumption. | |
| Procedures for monitoring of long term data for increasing trends | |
| Part 4 – Engine condition monitoring programme | |
| Procedures for detecting deterioration of engine at an early stage to allow for corrective action before safe operation are affected. | |
| Parameters to be monitored, method of date collection and corrective action process. | |
| Procedures for engine limit margin monitoring to ensure that a prolonged single-engine diversion maybe conducted without exceeding approved engine limits. | |

| Part 5 – Verification programme after maintenance | | |
|---|---|--|
| List of primary systems critical to EDTO | | |
| Conditions that require verification flights | | |
| Procedures for initiating verification actions | | |
| Procedures that ensure corrective actions is taken after engine shutdown and any other significant failure. | | |
| Procedures that identify any reverse adverse trends | | |
| Procedures that preclude repeat items from occurring | | |
| Procedure that monitor and evaluate corrective actions. | | |
| Procedures that preclude simultaneous actions from being applied to multiple similar elements in any EDTO significant system | | |
| Part 6 – Reliability Programme | | |
| Event-oriented program for EDTO, in addition to the normal reliability program, to allow early identification and prevention of EDTO problems. | | |
| Procedures to ensure reporting of significant individual events (in-flight shutdown, flight diversions or turn-back, un-commanded power changes or surges, inability to control the engine or obtain desired power) problems with systems critical to EDTO and any other event detrimental to EDTO | | |
| Reporting criteria for the reporting to CAAM of events reportable through this programme. | | |
| Procedures for downgrade/upgrade criteria (diversion time). | | |
| Procedures for monitoring of APU high altitude in- flight start and run capability. | | |
| Part 7 – Propulsion system monitoring programm | e | |
| Procedures for the monitoring of propulsion system in-flight shutdown (IFSD) rate, evaluation of sustained trends and corrective actions. Procedures for the monitoring of long term IFSD | | |
| trends (12-month moving average). Reporting criteria for the assessment of propulsion system reliability and reporting to CAAM of results of | | |
| operator's assessment. | | |

| Part 8 – APU in-flight start capabilities | |
|---|--|
| Technical log entry of result APU In-flight start to ensure starting and operational capability after work performed on the APU that may affect the starting and operation of the APU. | |
| Technical log entry of result of APU In-flight start every 3 months for each aircraft of EDTO fleet. | |
| Part 9 – Maintenance training programme | |
| Training programs to ensure each person, including contract personnel, involved in EDTO is adequately trained on operator's EDTO procedures and is competent to perform his/her duties (EDTO awareness training) Procedures for ensuring that maintenance personnel have completed EDTO awareness training and have | |
| satisfactorily performed EDTO maintenance tasks under supervision, within the framework of MCAR and FOD. | |
| Part 10 – Parts control programme | |
| Procedures that ensure that proper EDTO parts are used and EDTO configuration is maintained. Control procedures for parts pooling and borrowing. | |
| | |
| | |

Part 11- Applicants additional Declaration

The undersigned certifies the above information to be correct and true and that aeroplane system installation, continuing airworthiness of systems, minimum equipment for dispatch, operating procedures and flight crew training comply with the requirement of regulation 122 of the MCAR 2016 and CAGM 6008 (IV)- EDTO

| Continuing Airworthiness Manager | Name & signature | Date | |
|----------------------------------|------------------|------|--|
| | | | |
| | | | |
| Quality Assurance Manager | Name & Signature | Date | |