
MALAYSIA

PHONE: 6-03-8778 4106
Email: ais@caam.gov.my
URL: aip.caam.gov.my

CIVIL AVIATION AUTHORITY OF MALAYSIA
AERONAUTICAL INFORMATION SERVICES
AIR TRAFFIC CONTROL TOWER (TOWER WEST)
JALAN KLIA 2/4,
64000 KLIA,
SELANGOR DARUL EHSAN
MALAYSIA.

AIRAC AIP SUP 02/25

Effective Date: 20 MAR 2025
to PERM
Publication Date: 09 JAN 2025

KUALA LUMPUR INTERNATIONAL AIRPORT (WMKK) IMPLEMENTATION OF DEPARTURE CLEARANCE (DCL) VIA DATA LINK ON SELECTED ROUTES

(This AIRAC AIP Supplement replaces AIRAC AIP Supplement 65/24)

1 INTRODUCTION

- 1.1 The purpose of this AIP Supplement is to notify aircraft operators of the implementation of Departure Clearance (DCL) via data link on selected ATS routes at Kuala Lumpur International Airport (WMKK), effective 20th March 2025.
- 1.2 DCL service provides an automated platform for requesting and issuing departure clearance via data link between the pilot and air traffic control (ATC). This service aims to provide an efficient and reliable DCL, reduce radio frequency congestion, and reduce pilot and ATC workload.
- 1.3 This AIP Supplement supersedes AIP SUP 65/24 starting from the designated effective date.

2 DATA LINK SERVICE

- 2.1 Using DCL, the pilot sends a Request for Departure Clearance Downlink (RCD) and receives a Departure Clearance Uplink (CLD) from ATC, which contains the cleared destination, cleared runway, type of departure, squawk code, departure time, the next frequency, current Automatic Terminal Information Service (ATIS) identifier. The pilot can then send an acknowledgement by Departure Clearance Readback Downlink (CDA).
- 2.2 ATC clearance request through VHF using the existing voice procedures is still available for non-participating aircraft operators.

3 OPERATORS' EQUIPMENT REQUIREMENT

- 3.1 Aircraft need to be equipped with Aircraft Communications Addressing and Reporting System (ACARS) equipment and compliant with European Organization for Civil Aviation Equipment (EUROCAE) ED-85A and Airlines Electronic Engineering Committee (AEEC) 623 may utilise DCL over the data link.
- 3.2 DCL service is only applicable for flights departing from WMKK to the following destinations:
 - a) Destinations in Peninsular Malaysia;
 - b) Destinations in Singapore via ATS Route A464;
 - c) Destinations in Indonesia via ATS Route R461;
 - d) Destinations in Thailand via ATS Route Y501, Y502, Y530, Y531, A457, R325, M769, G466 and M751; and
 - e) Destinations in Vietnam via ATS Route R208 and M765.
- 3.3 DCL via data link will be applied under the following principle:
 - a) The planned flight level (PFL) filed in flight plan field 15b will be used as requested level unless otherwise specified by pilot;
 - b) An initial level will be assigned according to the runway used for departure. The initial climb altitude will be included in the free text (eg; IL040, which means initial climb altitude is 4000ft;

- c) No on-ground flight level negotiation and reservations; and
- d) Final cruising level will be assigned by Lumpur ATC after airborne and it is subjected to traffic disposition.

4 DCL MESSAGE

- 4.1 The definition of commonly used terms in DCL and examples of message formats are provided below:

| | |
|--|--|
| Request for Departure Clearance Downlink (RCD) | <p>Message of the pilot requesting an ATC Clearance.</p> <p>Example:</p> <p>RCD080 ABC0123 - WMKK - GATE B09 – WSSS ATIS W TYP/B738 < FREE TEXT ></p> |
| Flight System Uplink Message (FSM) | <p>Automatic acknowledgement of receipt of RCD / CDA by the ATC system, or the termination of the DCL service.</p> <p>Example 1:</p> <p>FSM 1025 230101 WMKK ABC0123 RCD RECEIVED REQUEST BEING PROCESSED</p> <p>Example 2:</p> <p>FSM 1035 230101 WMKK ABC0123 CDA RECEIVED CLEARANCE CONFIRMED</p> <p>Example 3 (NEGATIVE FSM MESSAGE):</p> <p>FSM 1035 230101 WMKK ABC0123 RCD REJECTED ERROR IN MESSAGE REVERT TO VOICE PROCEDURES</p> |
| Departure Clearance Uplink Message (CLD) | <p>Issuance of the ATC Clearance by the air traffic controller.</p> <p>Example:</p> <p>CLD 1035 230101 WMKK PDC 150 ABC0123 CLRD TO WSSS OFF 32R VIA RUSBU1D IL 5000 FT SQUAWK 7031 NEXT FREQ 121.9 ATIS W < FREE TEXT ></p> |
| Departure Clearance Readback Downlink (CDA) | <p>Confirmation of ATC Clearance by pilot.</p> <p>Example:</p> <p>CDA 1035 230101 WMKK PDC 150 ABC0123 CLRD TO WSSS OFF 32R VIA RUSBU1D SQUAWK 7031 NEXT FREQ 121.9 ATIS W < FREE TEXT ></p> |

5 DCL OPERATING PROCEDURES

- 5.1 The ground system's logon ID for the DCL service provision is WMKK.
- 5.2 Pilot utilising the DCL service on selected routes shall request ATC clearance through RCD message no earlier than 20 minutes before Target Start-Up Approval Time (TSAT).

- 5.3 The DCL ground system will check the received request and verify that it corresponds to an existing flight plan. The ground system will then send a positive or negative request acknowledgement. As soon as the ATC system has received the RCD message, an FSM message will be transmitted automatically. If the RCD message is rejected through a negative FSM message, the pilot shall revert to voice procedures.
- 5.4 The controller uses his DCL terminal to issue the clearance, the CLD, which will be automatically sent to the pilot via the ACARS data link network. The pilot can check and print the approval at his convenience.
- 5.5 ATC will revert with CLD within 5 minutes of receipt of the RCD message. If no CLD message is received, the pilot shall call on Clearance delivery frequency.
- 5.6 Within 5 minutes after receiving the CLD message, pilot shall select the "ACCEPT" function to acknowledge the ATC clearance. Failure to comply may result in a "revert to voice procedures" message.

Note 1: *Departure Clearance issued by voice procedures always supersedes a departure clearance transmitted via the DCL service.*

Note 2: *DCL service is not capable of clearance revision. ATC will revise the clearance issued via data link through voice communications.*

- 5.7 Pilot will receive a confirmation message "CDA RECEIVED CLEARANCE CONFIRMED". Within 5 minutes pilot should contact the appropriate LUMPUR GROUND and state:
- a) "received datalink clearance"; and
 - b) initial climb altitude (ex: IL 4000 FT).
- 5.8 ATC will reject the DCL request and revert to voice procedures if the following occurs:
- a) Flight's destination is not stated in paragraph 3.2;
 - b) RCD message does not comply with ED-85A or has inaccurate flight data; or
 - c) When required by ATC.

6 CONTACT

- 6.1 Any feedback on the DCL is welcome and should be sent to cns@caam.gov.my.

7 CANCELLATION

- 7.1 This AIRAC AIP Supplement supersedes AIRAC AIP Supplement **65/24** and shall remain valid until it is incorporated into AIP Malaysia, or until a new instruction is issued.

- END -